

SINCLAIR MARKETING INC -- LIGHT FUEL OIL (DIESEL) -- 9140-00-286-5296

===== Product Identification =====

Product ID:LIGHT FUEL OIL (DIESEL)

MSDS Date:01/01/1992

FSC:9140

NIIN:00-286-5296

MSDS Number: BQNQF

=== Responsible Party ===

Company Name:SINCLAIR MARKETING INC

Address:550 EAST SOUTH TEMPLE

Box:31825

City:SALT LAKE CITY

State:UT

ZIP:84131

Country:US

Info Phone Num:801-363-5100

Emergency Phon

e Num:801-363-5100

CAGE:5X969

=== Contractor Identification ===

Company Name:SINCLAIR MARKETING INC

Address:550 EAST SOUTH TEMPLE

Box:31825

City:SALT LAKE CITY

State:UT

ZIP:84131

Country:US

Phone:801-363-5100

CAGE:5X969

===== Composition/Information on Ingredients =====

Ingred Name:TOLUENE (SARA III)

CAS:108-88-3

RTECS #:XS5250000

Fraction by Wt: 0.1-1.0%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:200 PPM/150 STEL

ACGIH TLV:50 PPM; 9293

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000

LBS

Ingred Name:NAPHTHALENE (SARA III)
CAS:91-20-3
RTECS #:QJ0525000
Fraction by Wt: 2-12.5%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:10 PPM/15 STEL
ACGIH TLV:10 PPM/15 STEL; 9293
EPA Rpt Qty:100 LBS
DOT Rpt Qty:100 LBS

===== Hazards Identification =====

LD50 LC50 Mixture:ORAL LD50 (RAT) IS 7.5 G/KG
Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:EYE-CONTACT MAY CAUSE IRRITATION.

SKIN-CONTACT MAY IRRITATE OR BURN SKIN. ABSORPTION THROUGH THE SKIN MAY CAUSE SYMPTOMS OF INTOXICATION, FOLLOWED BY KIDNEY DAMAGE. INGESTION-ASPIRATION MAY RESULT IN SEVERE LUNG DAMAGE & PULMONARY EDEMA, NERVOUS SYSTEM DEPRESSION OR EXCITEMENT.

Explanation of Carcinogenicity:IARC HAS CONCLUDED THAT THERE IS INADEQUATE EVIDENCE FOR THE CARCINOGENICITY IN HUMANS OF DIESEL FUEL.

Effects of Overexposure:INHALATION-OVEREXPOSURE MAY CAUSE WEAKNESS, HEADACHE, DROWSINESS, CONFUSION, BLURRED VISION, OR NAUSEA; GREATER EXPOSURE MAY CAUSE DIZZINESS, IRREGULAR HEARTBEAT, COMA, COLLAPSE & DEATH. INGESTION-NAUSEA, VOMITING, DIARRHEA AND ABDOMINAL PAIN MAY OCCUR.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

===== First Aid Measures =====

First Aid:EYE-FLUSH IMMEDIATELY WITH WATER FOR AT LEAST 15 MINUTES MINIMUM. SEEK MEDICAL ATTENTION PROMPTLY. SKIN-DISCARD CONTAMINATED CLOTHING. WASH CONTACT AREAS WITH SOAP & WATER. INGESTION-DO NOT INDUCE VOMITING. GET MEDICAL ASSISTANCE PROMPTLY. INHALATION-REMOVE FROM FURTHER EXPOSURE. IF UNCONSCIOUSNESS OCCURS, SEEK IMMEDIATE MEDICAL ASSISTANCE.

===== Fire Fighting Measures =====

Flash Point:100F TO 190F
Autoignition Temp:Autoignition Temp Text:350F
Extinguishing Media:FOAM, DRY CHEMICAL, CARBON DIOXIDE, WATER FOG, VAPORIZING LIQUID (HALON).
Fire Fighting Procedures:

FIRE FIGHTING SHOULD USE SELF-CONTAINED
BREATHING APPARATUS IN CONFINED SPACES, & FULL PROTECTIVE EQUIPMENT
(BUNKER GEAR). COOL ADJACENT STRUCTURES AND DRUMS.
Unusual Fire/Explosion Hazard:VAPORS WILL BE RELEASED ABOVE FLSAH POINT
& WHEN MIXED WITH AIR, CAN BURN OR EXPLODE IN CONFINED SPACE IF
EXPOSED TO SOURCES OF IGNITION.

===== Accidental Release Measures =====

Spill Release Procedures:TREAT SPILL AS AN OIL SPILL. REPORT SPILLS.
ELEMIMATE IGNI
TION SOURCES. REMOVE LEAKING CONTAINERS TO A SAFE
AREA. CONTAIN & REMOVE BY MECHANICAL MEANS. GUARD AGAINST
CONTAMINATION OF WATER SUPPLIES.

===== Handling and Storage =====

Handling and Storage Precautions:STORE AWAY FROM IGNITION SOURCES IN A
COOL AREA. OUTSIDE OR DETACHED STORAGE IS PREFERRED. USE
NON-SPARKING TOOLS & EQUIPMENT. USE ONLY AS FUEL.
Other Precautions:GROUND & BOND ALL TRANSFER & STORAGE EQUIPMENT. DRUMS
MUST BE GROUNDED/BO
NDED/EQUIPPED WITH SELF-CLOSING VALVES, PRESSURE
VACUUM BUNGS, & FLAME ARRESTORS. DO NOT USE AS A CLEANER OR
SOLVENT. DO NOT SI PHON BY MOUTH.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:APPROVED RESPIRATORY PROTECTION MUST BE USED
WHEN VAPOR OR MIST CONCENTRATIONS ARE UNKOWN OR EXCEDD THE TLV.
AVOID PROLONGED OR REPEATED BREATHING OF VAPORS OR MISTS.
Ventilation:NONE SPECIFIED BY MANUFACTURER.
Protective Gloves:IMPERVIOUS GLOVES.
Eye Protection:FULL FACE SHIELD, CHEMICAL GOGGLES.
Other Protective Equipment:IMPERVIOUS GLOVES, BOOTS & WHOLE BODY
PROTECTION. LAUNDER CONTAMINATED CLOTHING BEFORE REUSE.
Work Hygienic Practices:WASH THOROUGHLY AFTER USE.
Supplemental Safety and Health
NOTE TO PHYSICIAN: MATERIAL IF ASPIRATED INTO THE LUNGS MAY CAUSE
CHEMICAL PNEUMONITIS. TREAT APPROXIATELY.

===== Physical/Chemical Properties =====

HCC:F4
Vapor Pres: