

JAMAK FABRICATION INC, DBA PORTER SEAL CO -- SOLASIL 2200 -- 5970-00-449-5161  
===== Product Identification =====

Product ID: SOLASIL 2200  
MSDS Date: 04/30/1993  
FSC: 5970  
NIIN: 00-449-5161  
Kit Part: Y  
MSDS Number: BQSDZ  
=== Responsible Party ===  
Company Name: JAMAK FABRICATION INC, DBA PORTER SEAL CO  
Address: 1401 NORTH BOWIE DRIVE  
City: WEATHERFORD  
State: TX  
ZIP: 76086  
Country: US  
Info Phone Num: 817-594-8771

Emergency Phone Num: 817-594-8771  
CAGE: 1EF46  
=== Contractor Identification ===  
Company Name: JAMAK FABRICATION INC, DBA PORTER SEAL CO  
Address: 1401 NORTH BOWIE DRIVE  
Box: City: WEATHERFORD  
State: TX  
ZIP: 76086  
Country: US  
Phone: 817-594-8771  
CAGE: 1EF46  
Company Name: PORTER SEAL CO  
Address: 1401 N BOWIE DR  
Box: City: WEATHERFORD  
State: TX  
ZIP: 76086  
Country: US  
Phone: 817-594-8771  
CAGE: 4F044

===== Composition/Information on Ingredients =====

Ingred Name: IRON OXIDE/FERRIC OXIDE  
CAS: 1309-37-1

RTECS #:NO7400000  
Fraction by Wt: 30%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:10 MG/M3 (FE)  
ACGIH TLV:5 MG/M3(FE),B2; 9293

=====  
===== Hazards Identification =====  
=====

Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:ACUTE AND CHRONIC - NO ADVERSE  
EFFECTS.  
Effects of Overexposure:NONE  
Medical Cond Aggravated by Exposure:NOT KNOWN.

=====  
===== First Aid Measures  
=====

First Aid:GET MEDICAL ATTENTION IF SYMPTOMS DEVELOP. EYE/SKIN:FLUSH  
WITH WATER. INHALED:UNLIKELY. INGESTION:DO NOT INDUCE VOMITING. IF  
CONSCIOUS, DRINK LARGE AMOUNT OF WATER AND GET MEDICAL ATTENTION.  
NEVER GIV E ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.

=====  
===== Fire Fighting Measures =====  
=====

Extinguishing Media:CARBON DIOXIDE OR FOAM  
Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A  
SELF CONTAINED  
BREATHING APPARATUS.  
Unusual Fire/Explosion Hazard:NOT KNOWN

=====  
===== Accidental Release Measures =====  
=====

Spill Release Procedures:REMOVE USING ABSORBENT MATERIALS.  
Neutralizing Agent:NOT APPLICABLE.

=====  
===== Handling and Storage =====  
=====

Handling and Storage Precautions:KEEP AWAY FROM STRONG OXIDIZING  
AGENTS.  
Other Precautions:WASH THOROUGHLY AFTER HANDLING.

=====  
===== Exposure Controls/Personal Protection =====  
=====

Respirato

ry Protection:NO SPECIAL REQUIREMENTS  
Ventilation:NO SPECIAL REQUIREMENTS  
Protective Gloves:NO SPECIAL REQUIREMENTS  
Eye Protection:SAFETY GOGGLES  
Other Protective Equipment:EYE WASH STATION, EMERGENCY SHOWER, NORMAL  
WORK CLOTHING COVERING ARMS AND LEGS  
Work Hygienic Practices:NORMAL PRACTICES FOR A LABORATORY.  
Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:N1  
Spec Gravity:1.50  
Solubility in Water:NIL  
Appearance and Odor:RED PASTE WIT  
H SLIGHT ETHANOL ODOR

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES  
OXIDIZING AGENTS  
Stability Condition to Avoid:EXCESSIVE HEAT  
Hazardous Decomposition Products:SILICON DIOXIDE AND CARBON DIOXIDE

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH ALL LOCAL, STATE  
AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.