

PRATTVILLE BUILDERS INC -- PRIMER, EPOXY CTG, CORRINHIB, LEAD & CHR FR --
8010-01-193-0517

===== Product Identification =====

Product ID:PRIMER, EPOXY CTG, CORRINHIB, LEAD & CHR FR

MSDS Date:06/16/1992

FSC:8010

NIIN:01-193-0517

Kit Part:Y

MSDS Number: BQSLV

=== Responsible Party ===

Company Name:PRATTVILLE BUILDERS INC

Address:474 E MAIN ST

Box:2153

City:PRATTVILLE

State:AL

ZIP:36067

Country:US

In

fo Phone Num:205-365-2396/2145/312-455-2662NIGHT

Emergency Phone Num:205-365-2396/2145/312-455-2662NIGHT

Preparer's Name:W. A. ELLISON

CAGE:0EAH4

=== Contractor Identification ===

Company Name:PRATT AND LAMBERT INC

Box:6027

City:CLEVELAND

State:OH

ZIP:44101-1027

Country:US

Phone:216-566-2902

CAGE:61196

Company Name:PRATTVILLE BUILDERS INC

Address:474 E MAIN ST

Box:2153

City:PRATTVILLE

State:AL

ZIP:36067

Country:US

Phone:205-365-2396/2145/312-455-2662NIGHT

CAGE:0EAH4

===== Composition/I

Information on Ingredients =====

Ingred Name:ALIPHATIC AMINE ADDUCT (RESIN)

CAS:31326-29-1

Fraction by Wt: 25%

Other REC Limits:NONE SPECIFIED

Ingred Name:N-BUTYL ALCOHOL (SOLVENT) (SARA 313) (VAPOR PRESSURE 6 MM
HG @ 20C) (LFL 1.4 / UFL 11.2) (SKIN)

CAS:71-36-3

RTECS #:EO1400000

Fraction by Wt: 15%

Other REC Limits:NONE SPECIFIED

OSHA PEL:100 PPM

ACGIH TLV:S, C 50 PPM; 9293

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:PROPYLENE GLYCOL MONOMETHYL ETHER (SOLVENT) (VAPOR PR
ESSURE

11 MM HG @ 20 C)

CAS:107-98-2

RTECS #:UB7700000

Fraction by Wt: 50%

Other REC Limits:NONE SPECIFIED

OSHA PEL:100 PPM/STEL 150

ACGIH TLV:100 PPM/STEL 150

Ingred Name:TOLUENE (SOLVENT) (SARA 313) (VAPOR PRESSURE 22 MM HG @
20C) (LFL 1.7 / UFL 7.1)

CAS:108-88-3

RTECS #:XS5250000

Fraction by Wt: 5%

Other REC Limits:NONE SPECIFIED

OSHA PEL:200 PPM/150 STEL

ACGIH TLV:50 PPM; 9293

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:DIETHYLENETRIAMINE (ADDITIVE) (VAPOR PRESSURE 1 MM H

G @
20C)
CAS:111-40-0
RTECS #:IE1225000
Fraction by Wt: 5%
Other REC Limits:NONE SPECIFIED
OSHA PEL:1 PPM/4 MG/M3
ACGIH TLV:1 PPM/SKIN 4 MG/M3

Ingred Name:2-METHOXY-1-PROPANOL (SOLVENT) (LFL 1.5 / UFL 10.9)
CAS:1589-47-5
Fraction by Wt: < 5%
Other REC Limits:NONE SPECIFIED

Ingred Name:VOC: 5.65 LB/GL; 678 G/L
RTECS #:9999999VO
Other REC Limits:NONE SPECIFIED

Ingred Name:DIETHYLENETRIAMINE (VAPOR PRESSURE 1 MM HG @ 20C)
CAS:111-40-0
RTECS #:IE1225000
Fraction by Wt: 5%
Other REC Limits:NON
E SPECIFIED
OSHA PEL:1 PPM, 4 MG/M3
ACGIH TLV:1 PPM, 4 MG/M3 SKIN

Ingred Name:BISPHENOL-A (SARA III)
CAS:80-05-7
RTECS #:SL6300000
Fraction by Wt: 5%
Other REC Limits:NONE SPECIFIED

Ingred Name:N-BUTYL ALCOHOL (SOLVENT) (VAPOR PRESSURE 6 MM HG @ 20C)
(SARA III) (LFL 1.4; UFL 11.2) (SKIN)
CAS:71-36-3
RTECS #:EO1400000
Fraction by Wt: THAN AIR
Spec Gravity:1.0
pH:4-7STD
Viscosity:63-73 KU
Evaporation Rate & Reference:SLOWER THAN DIETHYL ETHER
Solubility in Water:SLIGHT IN WATER
Appearan

ce and Odor:LIQUID, SOLVENT ODOR

Percent Volatiles by Volume:77 %

Corrosion Rate:NA

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG ACIDS OR ALKALINE MATERIALS, OXIDIZING MATERIALS, ACCELERATORS.

Stability Condition to Avoid:AVOID EXCESSIVE HEAT (>115 F (46C) AND
SOURCES OF IGNITION.

Hazardous Decomposition Products:BURNING, INCLUDING WHEN HEATED BY
WELDING OR CUTTING, WILL PRODUCE SMOKE, CARBON MONOXIDE AND CARBON
DIOXIDE.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE IN ACCORDANCE W/FEDERAL-STATE-LOCAL LAWS
AND REGULATIONS. INCINERATE ONLY IN EPA FACILITY-DO NOT INCINERATE
CLSD CONTAINERS. OBSERVE PRECAUTIONS FOR DISPOAL OF FLAMM MATL.
CONTAM ABSORB MAY BE DISPOSED IN A HAZARDOUS WASTE
LANDFILL.RCRA-D001.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of
the Department

of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.