PACIFIC ANCHOR CHEMICAL, PERFORMANCE CHEMICALS DIV -- ANCAMINE K61B, HK61BU -- 8030-00-875-2631

Product ID: ANCAMINE K61B, HK61BU MSDS Date:05/01/1991 FSC:8030 NIIN:00-875-2631 **MSDS Number: BQWDC** === Responsible Party === Company Name: PACIFIC ANCHOR CHEMICAL, PERFORMANCE CHEMICALS DIV Address:7201 HAMILTON BOULEVARD **City:ALLENTOWN** State:PA ZIP:18195-1501 Country:US Info Phone Num:215-481-6933/ 800-PAC-EPOXY **Emergency Phone Num** :215-481-6933/ 800-523-9374 CAGE:0EMU2 === Contractor Identification === Company Name: PACIFIC ANCHOR CHEMICAL, PERFORMANCE CHEMICALS DIV Address:7201 HAMILTON BOULEVARD Box:City:ALLENTOWN State:PA ZIP:18195-1501 Country:US Phone:215-481-6933/800-PAC-EPOXY CAGE:0EMU2

Ingred Name:2,4,6-TRISDIMETHYLANIMOMETHYLPHENOL ESTER OF 2EHA CAS:51365-70-9 Fraction by Wt: 100% Other REC Limits:NONE SPECIFIED

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Health Hazards Acute and Chronic:ACUTE; IRRITATING TO EYES AND SKIN.
RISK OF EXPOSURE TO HAZARDOUS CONCENTRATIONS OF VAPOR UNDER NORMAL WORKING CONDITIONS IN WELL VENTILATED SPACE IS MINIMAL. HOWEVER,
CONDITIONS SUCH AS SPRAYING OR S UDDEN RELEASE OF HOT LIQUID, WHICH GENERATE AN AEROSOL, MISTS OR FOG SHOULD BE AVOIDED.
Effects of Overexposure:CHRONIC; REPEATED/PROLONGED EXPOSURE MAY

RESULT

IN ADVERSE SKIN EFFECTS (SUCH AS DEFATTING, RASH, IRRITATION OR CORROSION). ADVERSE EYE EFFECTS (SUCH AS CONJUNCTIVITIS OR CORNEAL DAMAGE). ADVERSE RESP IRATORY EFFECTS (SUCH AS COUGH, TIGHTNESS OF CHEST OR SHORTNESS OF BREATH).

Medical Cond Aggravated by Exposure:EYE DISEASE, SKIN DISORDERS AND ALLERGIES

First Aid:EYE: HOLD EYELID APART & IMMED FLUSH EYES W/WATER 15 MIN. CALL DR. SKIN: REMOVE P

RODUCT & IMMED FLUSH W/WATER 15 MIN. REMOVE

CONTAM CLOTHING & SHOES. WASH BEFORE REUSE. CALL DR. INHALE: MOVE TO FRESH AIR. IF BREATH STOPPD/LABORD, ASSISTD RESPIRATN (MOUTH TO MOUTH), OXYGEN MAY BE NEEDED. CALL DR. INGEST: CALL DR IMMED. INDUCE VOMIT OR EVAC STOMACH. NEVER GIVE ANYTHING BY MOUTH TO UNCONSCIOUS PERSON

Flash Point Method:PMCC
Flash Point:275F,135C
Extinguishing Media:IGNITION WILL GIVE RIS
E TO CLASS B FIRE. USE WATER
SPRAY. CARBON DIOXIDE, DRY CHEMICAL, ALCOHOL FOAM.
Fire Fighting Procedures:DONT BREATHE FUMES;USE WATER SPRAY TO REDUCE VAPOR. IF WATER POLLUTN OCCUR,NOTIFY AUTHORITIES.WEAR SCBA W/AIR SUPPLY.CONTAIN RUNOFF WATER.PREVENT STREAM CONTAM.
Unusual Fire/Explosion Hazard:MAY GENERATE CO GAS. MAY GENERATE TOXIC NITROGEN OXIDE GASES. SUDDEN REACTION AND FIRE MAY RESULT IF PRODUCT IS MIXED WITH AN OXIDIZING AGENT.

========= Accidental Release M

easures =================

Spill Release Procedures:STOP LEAK, IF POSSIBLE. VENTILATE SPACE INVOLVED. REDUCE VAPOR SPREADING WITH WATER SPRAY. SHUT OFF/REMOVE IGNITION SOURCES. CONSTRUCT DIKE TO PREVENT SPREADING. COLLECT RUNOFF WATER & TANSFER TO DRUM S OR TANKS. PROTECT WORKER WITH WATER SPRAY.

Handling and Storage Precautions: KEEP CONTAINER CLOSED, IN WELL VENTED PLACE. KEEP AWAY FROM FOOD, DRINK & ANI

MAL FOOD STUFFS. KEEP AWAY FROM IGNITION SOURCES. NO SMOKING. Other Precautions: KEEP AWAY FROM OXIDIZERS, HEAT OR FLAMES. AVOID CONTACT WITH SKIN OR EYES. HANDLE IN WELL VENTILATED WORK SPACE. REMOVE ALL EQUIPMENT WHICH MAY BE A IGNITION SOURCE FROM VICINITY WHILE HANDLING. Respiratory Protection:NOT REQUIRED UNDER NORMAL CONDITIONS. FOR EMERGENCY SITUATIONS USE SELF-CONTAINED BREATHING APPARATUS WITH Ρ **RESSURE DEMAND MODE.** Ventilation: ADEQUATE GENERAL AND LOCAL EXHAUST. Protective Gloves:SUITABL GLOVES, IMPERMEABLE GLOVES W/CUFF Eye Protection: SPLASHPROOF GOGGLES, GOGGLES W/FACESHIELD Other Protective Equipment: WEAR SUITABLE PROTECTIVE CLOTHING. LONG SLEEVED CLOTHING. RUBBER APRON. RUBBER BOOTS. Work Hygienic Practices: PROVIDE ACCESSIBLE EYE WASH STATIONS, SAFETY SHOWER. WASH AT END OF SHIFT, BEFORE EATING, SMOKING, USING TOILET. Supplemental Safety and Health ======= Physic Spec Gravity:0.96 (WATER=1) Appearance and Odor: AMBER MOBILE LIQUID, WITH AMMONIACAL ODOR. Stability Indicator/Materials to Avoid:YES MINERAL ACIDS (SULFURIC, PHOSPHORIC, ETC), AIR. Stability Condition to Avoid:MOISTURE Hazardous Decomposition Products: CARBON MONOXIDE, CARBON DIOXIDE, AND NITROGEN OXIDES IN A FIRE. IRRITATING & TOXIC FUMES AT ELEVATED TEMPERATURES. \_\_\_\_\_

Waste Disposal Methods:PLACE IN METAL CONTAINERS FOR RECOVERY OR DISPOSAL. ABSORB RESIDUAL MAT'L ON VERMICULITE. SCOOP UP. FLUSH AREA W/WATER SPRAY. CLEAN-UP PERSONNEL MUST BE EQUIPPED WITH SELF CONTAINED BREATHING APPARATU S AND BUTYL RUBBER PROTECTIVE CLOTHING.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.