

R.H. CARLSON COMPANY, INC. -- NORSIL RTV 140 -- 8040-01-009-1562

===== Product Identification =====

Product ID:NORSIL RTV 140

MSDS Date:02/13/1992

FSC:8040

NIIN:01-009-1562

Kit Part:Y

MSDS Number: BQWFJ

=== Responsible Party ===

Company Name:R.H. CARLSON COMPANY, INC.

Address:41 CHESTNUT STREET

City:GREENWICH

State:CT

ZIP:06830

Country:US

Info Phone Num:203-531-5500

Emergency Phone Num:800-424-9300 CHEMTREC/203-531-5500

Preparer's Name:W.J. BUCHLER

CAGE:MO500

=== Contractor Identification ===

Company Name:R.H. CARLSON COMPANY, INC.

Address:41 CHESTNUT STREET

City:GREENWICH

State:CT

ZIP:06830

Country:US

Phone:203-531-5500

CAGE:MO500

Company Name:R.H.CARLSON COMPANY,INC.

Address:41-CHESTNUT STREET

Box:1687

City:GREENWICH

State:CT

ZIP:06830-5921

Country:US

Phone:203-531-5500

CAGE:33530

===== Composition/Information on Ingredients =====

Ingred Name:NON-HAZARDOUS INGREDIENTS

Other REC Limits:NONE SPECIFIED

===== Hazar

ds Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Health Hazards Acute and Chronic:WARNING! MAY CAUSE IRRITATION. AVOID CONTACT WITH SKIN, EYES, AND CLOTHING, DIRECT CONTACT WITH UNCURED PRODUCT OR VAPOR MAY CAUSE SLIGHT IRRITATION. INHALATION OF VAPORS MAY PRODUCE RESPIRATORY IRRITATION. INGESTION OF MAT'L MAY PRODUCE ABDOMINAL PAIN AND DIARRHEA.

===== First Aid Measures =====

First Aid:ING

EST:DONT INDUCE VOMIT, IF OCCURS, GIVE FLUID. CALL DR.

DONT GIVE LIQ IF UNCONSCIOUS. SKIN: FLUSH W/WATER 15 MIN. REMOVE CONTAM CLOTH/SHOES. GET MED AID IF IRRIT. EYE: IMMEDIATELY FLUSH W/WATER 15 MIN, HOLD EYELIDS APART. DONT NEUTRALIZE. GET MED AID ASAP. FLUSH 15 MIN MORE IF NO MED AID. INHAL: REMOVE FROM AREA. GET MED AID IF BREATH DIFFICULT. OXYGEN IF DR'S ADVICE. NOT BREATH, GIVE ARTIFICIAL RESPIRATION

===== Fire Fighting Measures =====

Fire Fighting

ing Procedures:EVACUATE NON-ESSENTIAL PERSONNEL. FIREFIGHTERS SHOULD WEAR FULL FACE SCBA & IMPERVIOUS PROTECTIVE CLOTHING. USE STANDARD FIREFIGHTING TECHNIQUES.

===== Accidental Release Measures =====

Spill Release Procedures:FOLLOW GOOD INDUSTRIAL HYGIENE. WEAR PROTECTIVE CLOTHING, SPLASH GOGGLES, SOAK UP W/ABSORBENT (SAWDUST,CLAY,OIL ABSORBENT). SWEEP UP ABSORBENT. PLACE IN DRUM. WASH UP WITH DETERGENT & WATER. FLUSH WITH WATER. LARGE SPILL: DIKE & PUMP TO DRUM.

===== Handling and Storage =====

Handling and Storage Precautions:AVOID CONTACT WITH SKIN AND EYES, USE ONLY IN A WELL VENTILATED AREA. CONTACT LENS WEARERS TAKE APPROPRIATE PRECAUTION.

Other Precautions:STORE IN COOL PLACE AND KEEP AWAY FROM HEAT, SPARKS, AND FLAME. PRODUCT EVOLVES SLIGHT AMOUNTS OF ACETONE WHEN EXPOSED TO WATER OR HUMID AIR. OBSERVE LIMITS FOR ACETONE FORMED ON EXPOSURE TO WATER OR HUMID AIR OSHA PEL

EL & ACGIH TLV 750 PPM.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF CONDITIONS GENERATE VAPOR, HANDLE MAT'L IN
OPEN OR WELL-VENTED AREA. WHERE ADEQUATE VENT IS NOT AVAILABLE, USE
NIOSH APPROVED ORGANIC VAPOR RESPIRATORS. WHERE HIGHER EXPOSURES,
RECOMMEND POSITIVE P RESSURE AIR SUPPLY RESPIRATOR.

Ventilation:LOCAL EXHAUST IS REQUIRED & GENERAL MECHANICAL VENTILATION
IS SUGGESTED IN A CLOSED AREA.

Protective Gloves:PLASTIC FILM OR
RUBBER GLOVES SUGGESTED

Eye Protection:SAFETY GLASSES

Other Protective Equipment:PROTECTIVE APRON OR COVERALLS

Work Hygienic Practices:KEEP AWAY FORM HEAT, SPARKS, AND FLAME. AVOID
PROLONGED VAPOR BREATHING AND CONTACT WITH SKIN AND EYES.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

Vapor Pres:NEGLIGIBLE

Vapor Density:>1

Spec Gravity:1.05

Viscosity:>50,000 CPS

Evaporation Rate & Reference: