

RACAL COMMUNICATIONS INC -- NI-CAD BATTERY PACK (13.2 V), 3600064-1,MA --
6140-01-220-5343

===== Product Identification =====

Product ID:NI-CAD BATTERY PACK (13.2 V), 3600064-1,MA

MSDS Date:05/11/1993

FSC:6140

NIIN:01-220-5343

MSDS Number: BQWHP

=== Responsible Party ===

Company Name:RACAL COMMUNICATIONS INC

Address:5 RESEARCH PL

City:ROCKVILLE

State:MD

ZIP:20850-3213

Country:US

Info Phone Num:301

-948-4420

Emergency Phone Num:301-948-4420

CAGE:23386

=== Contractor Identification ===

Company Name:RACAL COMMUNICATIONS INC

Address:5 RESEARCH PL

Box:City:ROCKVILLE

State:MD

ZIP:20850-3213

Country:US

Phone:301-948-4420

CAGE:23386

===== Composition/Information on Ingredients =====

Ingred Name:CADMIUM (SARA III), PERCENTAGE OF INGREDIENTS 1 & 2: 13-15
AS CADMIUM.

CAS:7440-43-9

RTECS #:EU9800000

Other REC Limits:NONE RECOMMENDED

OSHA PEL:SEE 1910.1027

ACGIH TLV:0.01 MG/M3

DUST;9394
EPA Rpt Qty:10 LBS
DOT Rpt Qty:10 LBS

Ingred Name:CADMIUM HYDROXIDE
CAS:21041-95-2
Other REC Limits:NONE RECOMMENDED
OSHA PEL:NOT ESTABLISHED.
ACGIH TLV:NOT ESTABLISHED.

Ingred Name:NICKEL (SARA III), PERCENTAGE OF INGREDIENTS 3 & 4: 20-30
AS NICKEL
CAS:7440-02-0
RTECS #:QR5950000
Other REC Limits:NONE RECOMMENDED
OSHA PEL:1 MG/M3
ACGIH TLV:1 MG/M3; 9293

Ingred Name:NICKEL HYDROXIDE (SARA III)
CAS:12054-48-7
RTECS #:QR7040000
Other REC Limits:NONE RECOMMENDED
OSHA PEL:1 MG NI
/M3
ACGIH TLV:0.1 MG NI/M3; 9293
EPA Rpt Qty:10 LBS
DOT Rpt Qty:10 LBS

Ingred Name:POTASSIUM HYDROXIDE (SARA III)
CAS:1310-58-3
RTECS #:TT2100000
Fraction by Wt: 2-4% DRY
Other REC Limits:NONE RECOMMENDED
OSHA PEL:C, 2 MG/M3
ACGIH TLV:C 2 MG/M3; 9293
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:COBALT (SARA III), PERCENTAGE OF INGREDIENTS 6 & 7: 1-2 AS
COBALT
CAS:7440-48-4
RTECS #:GF8750000
Other REC Limits:NONE RECOMMENDED
OSHA PEL:0.1 MG/M3;AS CO
ACGIH TLV:0.05 MG/M3;DUST 9293

Ingred Name:COBALT HYDROXIDE
CAS:1307-86-4
RTECS #:GG0904000
Other REC Limits:NONE RECOMMENDED
OSHA PEL:0.05 MG/M3(COBALT)
ACGIH TLV:0.1 MG/M3

===== Hazards Identification =====

LD50 LC50 Mixture:NOT RELEVANT
Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:YES
Health Hazards Acute and Chronic:ACUTE AND CHRONIC- ELECTROLYTE
(POTASSIUM HYDROXIDE) FROM LEAKER IS CAUSTIC. CONTACT WITH EYES OR
SKI
N CAN CAUSE IRRITATION AND BURNS. FUMES ARE TOXIC AND HARMFUL IF
INHALED.
Explanation of Carcinogenicity:CONTAINS CADMIUM [7440-43-9] WHICH IS
LISTED BY NTP AND IARC AND REGULATED BY OSHA AS A CARCINOGEN. ALSO
NICKEL.
Effects of Overexposure:ELECTROLYTE (POTASSIUM HYDROXIDE) FROM LEAKER
IS CAUSTIC. CONTACT WITH EYES OR SKIN CAN CAUSE IRRITATION AND
BURNS. FUMES ARE TOXIC AND HARMFUL IF INHALED.
Medical Cond Aggravated by Exposure:PERSONS WITH PRE-EXISTING SKIN
DISORDERS O
R EYE PROBLEMS OR IMPAIRED RESPIRATORY FUNCTION MAY BE
MORE SUSCEPTIBLE TO THE EFFECTS OF THE PRODUCT'S DUSTS, VAPORS OR
FUMES.

===== First Aid Measures =====

First Aid:GET MEDICAL ATTENTION IMMEDIATELY. EYE/SKIN:IMMEDIATELY FLUSH
WITH WATER FOR AT LEAST 15 MINUTES. HOLD EYELIDS OPEN.
INHALED:REMOVE TO FRESH AIR & PROVIDE OXYGEN/CPR IF NEEDED.
ORAL:UNLIKELY.

===== Fire Fighting Measures =====

Flash Po

int:NONE

Extinguishing Media:WATER SPRAY, CARBON DIOXIDE, FOAM OR DRY CHEMICAL FOR SURROUNDING FIRE. USE WATER SPRAY TO COOL FIRE EXPOSED CONTAINERS.

Fire Fighting Procedures:WEAR NIOSH-APPROVED SELF-CONTAINED BREATHING APPARATUS OPERATED IN THE POSITIVE PRESSURE MODE.

Unusual Fire/Explosion Hazard:MAY BURST WHEN SUBJECT TO EXTREME HEAT OR FIRE, RELEASING CADMIUM FUME WHICH IS TOXIC AND CAN CAUSE DEATH.

===== Accidental Release Measures =====

Spill R

Release Procedures:BATTERY AND CELL CASES WILL NORMALLY CONTAIN MATERIALS OF CONCERN. USE INDUSTRIAL ABSORBENT TO COLLECT LIQUID POTASSIUM HYDROXIDE. AVOID SKIN AND EYE CONTACT.

Neutralizing Agent:WEAK ACID FOR POTASSIUM, NICKEL & CADMIUM HYDROXIDE

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL PLACE. DO NOT ELECTRICALLY SHORT CIRCUIT. USE PROPER BATTERY CHARGER. AVOID BREAKING, CRUSHING OR BURNING BATTERIES.

Other

Precautions:AVOID INCINERATION OR MUTILATION. DO NOT TOUCH BROKEN OR LEAKING BATTERIES. KEEP OUT OF REACH OF CHILDREN.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE NIOSH APPROVED MIST OR DUST MASK WHEN HANDLING BROKEN OR LEAKING BATTERIES. WEAR SELF-CONTAINED BREATHING APPARATUS IN EMERGENCIES.

Ventilation:ROOM VENTILATION

Protective Gloves:RUBBER WHEN HANDLING LEAKERS

Eye Protection:SAFETY GOGGLES RECOMMENDED

Other Protective E

quipment:EYE WASH STATION, QUICK DRENCH SHOWER

Work Hygienic Practices:OBSERVE GOOD PERSONAL HYGIENE PRACTICES AND RECOMMENDED PROCEDURES. DO NOT WEAR CONTAMINATED CLOTHING.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:Z5

Spec Gravity:NOT RELEVANT

Solubility in Water:NOT RELEVANT

Appearance and Odor:PLASTIC HOUSING, 9.45" X 2.09" X 3.59", MAXIMUM WEIGHT 4 LBS

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

NOT KNOWN

Stability Condition to Avoid: EXCESSIVE HEAT, FIRE

Hazardous Decomposition Products: TOXIC CADMIUM FUME

===== Disposal Considerations =====

Waste Disposal Methods: CELLS AND BATTERIES MAY BE RETURNED AT SENDERS EXPENSE TO A PERMITTED TREATMENT, STORAGE, DISPOSAL FACILITY (TSDF). DISPOSAL MUST BE MADE IN ACCORDANCE WITH ALL APPLICABLE FEDERAL, STATE AND LOCAL LAWS AND REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.