

ALOX CORP -- ALOX 2028C -- 8030-00-938-1947

===== Product Identification =====

Product ID:ALOX 2028C

MSDS Date:12/09/1988

FSC:8030

NIIN:00-938-1947

MSDS Number: BQXVH

=== Responsible Party ===

Company Name:ALOX CORP

Address:3943 BUFFALO AVE

Box:517

City:NIAGARA FALLS

State:NY

ZIP:14302

Country:US

Info Phone Num:716-282-1295

Emergency Phone Num:716-282-1295

CAGE:60773

=== Contractor Identification ===

Company Name:ALOX CORP

Address:3943 BUFFALO AVE

Box:517

City

:NIAGARA FALLS

State:NY

ZIP:14302

Country:US

Phone:716-282-1295

CAGE:60773

===== Composition/Information on Ingredients =====

Ingred Name:ALIPHATIC MINERAL SPIRITS (140F MINIMUM FLASH POINT).

CAS:64475-85-0

RTECS #:PY8240000

Fraction by Wt: 50%

Other REC Limits:NONE SPECIFIED

ACGIH TLV:100 PPM

Ingred Name:\*(0% PROPRIETARY PRODUCT-AN OXYGENATED HYDROCARBON IN WHICH  
A PROTION OF FREE ORGANIC ACID PRODUCED BY OXIDATION IS \*\*

RTECS #:9999999ZZ

Other REC Limits:NONE SPECIFIED

Ingred Name:\*\*NEUTRALIZED W/BARIUM, THEN BLENDED W/BA SULFONATE &  
MINERAL SPIRITS. BARIUM COMPOUNDS (4% IN NON-MINERAL SPIRITS. \*\*\*  
RTECS #:9999999ZZ  
Other REC Limits:NONE SPECIFIED

Ingred Name:\*\*\*PORTION, 2% IN ALOX 2028C) ARE NOT WATER SOLUBLE).  
RTECS #:9999999ZZ  
Other REC Limits:NONE SPECIFIED

===== Hazards Identification =====

LD50 LC50 Mixture:LD: 3G/KG RATS; MINERAL SPIRITS  
Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:NONSOLVENT PORTIONS NONTOXIC FOR  
INHALATION SKIN & INGESTION. FOR SOLVENTS PORTION: HARMFUL IF  
INHALED. CAUSES IRRITATE. REPORTS ASSOCIATE REPEAT/PROLONG  
OCCUPATIONAL OVEREXPOSURE TO SOLVENT W/PERM BR AIN/NERVOUS SYSTEM  
DAMAGE. INTENTIONAL MISUSE BY CONCENTRATING/INHALING HARMFUL/FATAL.  
Effects of Overexposure:INHALE: NAUSEA/DIZZY/NOSE/THROAT IRRITATE/ EYE  
WATERING. SKIN: DEFAT/OIL ACNE/IRRITATE/ALLERGIC REAC  
TION, CONTACT  
W/ HEATED MAT'S-THERMAL BURNS. INGEST:  
IRRITATE/VOMIT/DIARRHEA/NAUSEA.

===== First Aid Measures =====

First Aid:INHALE: MOVE TO FRESH AIR, TREAT SYMPTOM- ADMINISTER OXYGEN  
IF BREATHING IS IMPAIRED. EYES: FLUSH W/WATER 15 MINUTES- CONSULT  
PHYSICIAN. SKIN: WASH W/SOAP/WATER-TREAT BURNS FROM HOT MATERIAL AS  
THERMAL BURNS. INGEST: DO NOT INDUCE VOMITING-CONSULT PHYSICIAN.

===== Fire Fighting Measures =====  
=====

Extinguishing Media:DRY CHEMICAL, CARBON DIOXIDE, WATER FOG  
Fire Fighting Procedures:HANDLE AS PETROLEUM PRODUCT (I.E: DO NOT USE  
WATER EXCEPT AS FOG OR TO COOL CONTAINERS OR TO FLUSH AWAY).  
Unusual Fire/Explosion Hazard:SAME AS PETROLEUM PRODUCTS (I.E: WATER  
STREAMS ON BURNING MATERIAL MAY SPREAD FIRE).

===== Accidental Release Measures =====

Spill Release Procedures:ATTEMPT TO RECOVER. KEEP PETROLEUM PRODUCTS  
OUT OF STREAMS AND WATERWAYS

YS.

===== Handling and Storage =====

Handling and Storage Precautions:AVOID PROLONGED/REPEATED CONTACT. KEEP CONTAINERS CLOSED WHEN NOT IN USE.

Other Precautions:IF INGESTION AND VOMITING OCCURS, MONITOR PATIENT FOR 48 HOURS FOR BREATHING DIFFICULTIES.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF VAPOR OR MIST ARE GENERATED USE APPROPRIATE MASK FOR VAPORS OR MIST.

Ventilation:LOCAL EXHAUST: PREFER RED IF VAPOR OR MIST ARE GENERATED.

Protective Gloves:OIL IMPERVIOUS

Eye Protection:SAFETY GLASSES

Other Protective Equipment:AS NEEDED TO PROTECT AGAINST HOT PRODUCT OR PROTECT FROM REPEATED OR PROLONGED CONTACT

Work Hygienic Practices:TO AVOID REPEATED/PROLONGED CONTACT. WASH BEFORE EATING/SMOKING/USING TOILET. LAUNDER SATURATED CLOTHING BEFORE REUSE.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:V2

Boiling Pt:B.P. Text:>1

50F,>66C

Vapor Pres:1

Spec Gravity:.86 @ 60F

Evaporation Rate & Reference: