

MINNESOTA MINING AND MFG CO -- SCOTCH-WELD (TM) EC-1945A METAL PRIMER --  
8040-00-065-6578

===== Product Identification =====

Product ID:SCOTCH-WELD (TM) EC-1945A METAL PRIMER

MSDS Date:04/22/1991

FSC:8040

NIIN:00-065-6578

Kit Part:Y

MSDS Number: BQXZX

=== Responsible Party ===

Company Name:MINNESOTA MINING AND MFG CO

Address:3M CTR

City:SAINT PAUL (FORMALLY IN DETROITT, MI)

State:MN

ZIP:55144-1000

Country:US

Info Phone Num:612-733-1341/612-733-1110

Emergency

Phone Num:612-733-1341

Preparer's Name:C.A. EISENHARD

CAGE:76381

=== Contractor Identification ===

Company Name:MINNESOTA MINING AND MFG CO, DBA 3M

Address:3M CENTER BLDG 224-5S-04

Box:City:SAINT PAUL

State:MN

ZIP:55144-1000

Country:US

Phone:866-556 5712 / 612-733-1110

CAGE:76381

===== Composition/Information on Ingredients =====

Ingred Name:ISOPROPYL ALCOHOL (SARA III)

CAS:67-63-0

RTECS #:NT8050000

Fraction by Wt: 40-50%

Other REC Limits:NONE SPECIFIED

OSHA PEL:400 PPM/STEL

500 PPM  
ACGIH TLV:400 PPM/STEL 500 PPM

Ingred Name:TOLUENE (SARA III)  
CAS:108-88-3  
RTECS #:XS5250000  
Fraction by Wt: 15-25%  
Other REC Limits:NONE SPECIFIED  
OSHA PEL:200 PPM/150 STEL  
ACGIH TLV:50 PPM; 9293  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

Ingred Name:METHYL ETHYL KETONE (SARA III)  
CAS:78-93-3  
RTECS #:EL6475000  
Fraction by Wt: 15-25%  
Other REC Limits:NONE SPECIFIED  
OSHA PEL:200 PPM/STEL 300 PPM  
ACGIH TLV:200 PPM/STEL 300 PPM  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

Ingred Name:XYLEN  
E (SARA III)  
CAS:1330-20-7  
RTECS #:ZE2100000  
Fraction by Wt: 5-15%  
Other REC Limits:NONE SPECIFIED  
OSHA PEL:100 PPM/STEL 150 PPM  
ACGIH TLV:100 PPM/STEL 150 PPM  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

Ingred Name:ALIPHATIC AMINE (VENDOR TRADE SECRET)  
Fraction by Wt: 1-10%  
Other REC Limits:NONE SPECIFIED

Ingred Name:MAXIMUM VOC: 733 GRAMS/LITER. MAXIMUM VOC MINUS WATER MINUS  
EXEMPT SOLVENTS: 733 GRAMS/LITER. (SCAQMD RULE 443.1)  
RTECS #:9999999VO  
Other REC Limits:NONE SPECIFIED

=====

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Health Hazards Acute and Chronic:ACUTE;EYE:IRRIT. SKIN: IRRIT, ALLERGIC REACTION (DRY, CRACK). INHALE:IRRIT, TEMPORARY NERV SYS IMPAIRMENT (LIGHT- HEADED). HEART, LIVER, KIDNEY, BLOOD CHANGES. INGEST:DIGEST SYS IRRIT, NERV SYS IMPAIR MENT (NAUSEA, VOMIT, ABDOM PAIN, MALAISE, DIZZY, UNCOORDINATION). SOLVENT ASPIRATION INTO LUNG MAY CAUSE DAMAGE OR DEATH

Effects o

f Overexposure:CHRONIC; INHALATION: REPEATED OR EXTREME

OVEREXPOSURE TO TOLUENE VAPORS MAY CAUSE NERVOUS SYSTEM DAMAGE.

===== First Aid Measures =====

First Aid:EYE: FLUSH EYES WITH LARGE AMOUNTS OF WATER FOR AT LEAST 10 MINUTES. CALL A PHYSICIAN. SKIN: THOROUGHLY WASH AFFECTED AREA WITH SOAP AND WATER. INHALATION: REMOVE PERSON TO UNCONTAMINATED AIR. CALL A PHYSICIAN. IF SWALLOWED: DO NOT INDUCE VOMITING. IMMEDIATELY CALL A PHYSICIAN OR POISON CONTROL CENTER.

===== Fire Fighting Measures =====

Flash Point:22.0F,-5.6C

Lower Limits:1.00

Upper Limits:12.00

Extinguishing Media:CO2, FOAM, DRY CHEMICALS

Fire Fighting Procedures:FIRE FIGHTERS SHOULD BE EQUIPPED WITH SELF-CONTAINED BREATHING APPARATUS WHEN FIGHTING FIRES INVOLVING THIS MATERIAL.

Unusual Fire/Explosion Hazard:FLAMMABLE. OVERHEATED, CLOSED CONTAINERS ADJACENT TO FIRE COULD EXPLODE DUE TO INTERNAL PRESSURE BUILDUP.

=====

===== Accidental Release Measures =====

Spill Release Procedures:EXTINGUISH IGNITION SOURCES. VENTILATE AREAS. OBSERVE PRECAUTIONS FROM OTHER SECTIONS. CONTAIN SPILL. COVER WITH ABSORBENT MATERIALS. COLLECT THE SPILLED MATERIAL USING NON-SPARKING TOOLS. PLACE IN DO T APPROVED METAL CONTAINER AND SEAL.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP AWAY FROM HEAT, IGNIT SOURCE. EASILY IGNITED

. USE W/VENT (KEEP BELOW TLV/PEL). AVOID BREATHING VAPOR DURING SPRAY. KEEP OUT OF REACH OF CHILDREN.  
Other Precautions:AVOID BREATHING VAPORS RELEASED DURING HEAT CURING. VENT CURING OVENS TO OUTDOORS OR EMISSION CONTROL DEVICE. KEEP CONTAINER CLOSED WHEN NOT IN USE. AVOID EYE AND SKIN CONTACT.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:FOR SPRAY APPLICATIONS USE AN OPERATING SPRAY BOOTH, AND WEAR A SUPPLIED AIR RESPIRATOR.

Ventilation:CURING OVENS SHOULD BE PROPERLY VENTED TO OUTDOORS OR SUITABLE EMISSION CONTROL DEVICE.

Protective Gloves:WEAR IMPERVIOUS GLOVES

Eye Protection:WEAR CHEMICAL SAFETY GOGGLES

Other Protective Equipment:WEAR EYE AND SKIN PROTECTIVE EQUIPMENT WHEN HANDLING THIS PRODUCT.

Work Hygienic Practices:WASH CONTAMINATED CLOTHING BEFORE REUSE.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:F2

Boiling Pt:B.P. Text:175F,79CMEK

Vapor Pres:

80.0000

Vapor Density:>2.00

Spec Gravity:0.820 (WATER=1)

Evaporation Rate & Reference:>3.00 (ETHER=1)

Solubility in Water:VERY SLIGHT

Appearance and Odor:CLEAR AMBER, LIQUID, SOLVENT ODOR

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

Hazardous Decomposition Products:CO, CO2, NITROGEN COMPOUNDS AND SMOKE PARTICLES WHEN SUBJECTED TO EXCESSIVE HEAT OR FLAME.

===== Disposal Considerations =====

=

Waste Disposal Methods:THIS PRODUCT CONTAINS TWO PARTS. FOR ACCELERATOR: INCINERATE ABSORBED & BULK PRODUCT AFTER MIXING W/FLAMM MAT'L IN LICENSED WASTE FACILITY. DISPOSAL SHOULD BE IN ACCORDANCE WITH REGULATIONS. US EPA HAZARDOUS WASTE NO: D001 (IGNITABLE).

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly

or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.