

ELDORADO CHEMICAL COMPANY, INC. -- PR-3400, PAINT REMOVER -- 8010-00-815-2970

=====
Product Identification
=====

Product ID:PR-3400, PAINT REMOVER

MSDS Date:07/26/1988

FSC:8010

NIIN:00-815-2970

MSDS Number: BRFQC

=== Responsible Party ===

Company Name:ELDORADO CHEMICAL COMPANY, INC.

Box:34837

City:SAN ANTONIO

State:TX

ZIP:78265

Country:US

Info Phone Num:512-653-9323

Emergency Phone Num:800-531-108

8

Preparer's Name:PAT E SMITH

CAGE:55208

=== Contractor Identification ===

Company Name:ELDORADO CHEMICAL COMPANY, INC.

Address:14350 LOOKOUT ROAD

Box:34837

City:SAN ANTONIO

State:TX

ZIP:78265-4837

Country:US

Phone:800-531-1088/ 210-653-2060

CAGE:55208

=====
Composition/Information on Ingredients
=====

Ingred Name:DICHLOROMETHANE (VAPOR HAZARD, MUTAGEN)

CAS:75-09-2

RTECS #:PA8050000

Fraction by Wt: 70%

Other REC Limits:NONE SPECIFIED

OSHA PEL:500 PPM

ACGIH TLV:50 PPM

EPA Rpt

Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:TOLUENE (VAPOR HAZARD, FLAMMABLE)
CAS:108-88-3
RTECS #:XS5250000
Fraction by Wt: 4%
Other REC Limits:NONE SPECIFIED
OSHA PEL:200 PPM/150 STEL
ACGIH TLV:50 PPM; 9293
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:METHANOL (VAPOR HAZARD, FLAMMABLE)
CAS:67-56-1
RTECS #:PC1400000
Fraction by Wt: 1%
Other REC Limits:NONE SPECIFIED
OSHA PEL:S,200PPM/250STEL
ACGIH TLV:S,200PPM/250STEL; 93
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:ETHY
L ALCOHOL (VAPOR HAZARD, FLAMMABLE)
CAS:64-17-5
RTECS #:KQ6300000
Fraction by Wt: 8%
Other REC Limits:NONE SPECIFIED
OSHA PEL:1000 PPM
ACGIH TLV:1000 PPM

Ingred Name:SODIUM CHROMATE (OXIDIZER, SUSPECTED CARCINOGEN)
CAS:7775-11-3
RTECS #:GB2955000
Fraction by Wt: .7%
Other REC Limits:NONE SPECIFIED
ACGIH TLV:.5 PPM
EPA Rpt Qty:10 LBS
DOT Rpt Qty:10 LBS

Ingred Name:AMMONIUM HYDROXIDE SOLUTION (VAPOR HAZARD, CORROSIVE)
CAS:1336-21-6
RTECS #:BQ9625000
Fraction by Wt: 4%
Other REC Limits:NONE SPECI

FIED
ACGIH TLV:25 PPM
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:INHAL: ACUTE-HIGH, ABSORBED IN LUNGS.
CHRONIC-LOW, NO CUMULATIVE EFFECT. SKIN: ACUTE-HIGH, CORROSIVE TO
SKIN. CHRONIC-LOW, NO LONG TERM. SKIN ABSORPTION: ACUTE-SLIGHT PAIN
AND DISCOMFORT IS SAFETY FAC TOR. CHRO
NIC-SLIGHT. EYE: ACUTE-HIGH,
CORROSIVE TO EYES. CHRONIC-LOW, NO LONG TERM.
Effects of Overexposure:INHALATION: INDUCES NARCOSIS, DIZZINESS,
NAUSEA. NO LONG TERM HAZARD. SKIN: CORROSIVE TO SKIN, WILL CAUSE
SCARRING WHICH DISAPPERS IN 1-2 YEARS. USE METHOD PRECLUDES LONG
ENOUGH EXPOSURE TO CAUSE ABSO RPTION. EYE: CORROSIVE TO EYES ON
CONTACT, SHORT EXPOSURE WILL CAUSE HAZY VISION, WHICH RETURNS TO
NORMAL.

=====
===== First Aid Measures =====

First Aid:EYES: FLUSH WITH WATER FOR 15 MINUTES. SEEK MEDICAL
ATTENTION. SKIN: FLUSH WITH WATER FOR 10 MINUTES. WASH WITH SOAP
AND WATER. INHALATION: REMOVE TO FRESH AIR, IF UNCONSCIOUS, GIVE
OXYGEN AND SEEK ME DICAL ATTENTION.

=====
===== Fire Fighting Measures =====

Fire Fighting Procedures:SELF-CONTAINED BREATHING APPARATUS REQUIRED
Unusual Fire/Explosion Hazard:CONTACT WITH FLAME MAY PRODUCE TOXIC
CHLORIDE FUMES AND/OR PHOSGENE GAS

=====
===== Accidental Release Measures =====

Spill Release Procedures:ALLOW TO EVAPORATE, SWEEP UP RESIDUE WITH
SAWDUST OR SWEEPING COMPOUND.

=====
===== Exposure Controls/Personal Protection =====

Ventilation:RESPIRATORY. 100 FT/MIN. SCBA REQUIRED IF LIMTIS EXCEEDED
Protective Gloves:POLYETHYLENE
Eye Protection:FACE SHIELD OR GOGGLES
Other Protective Equipment:FULL WASHRACK GEAR
Work Hygienic Practices:DO NOT USE IN CONFINED SPACES. AVOID ALL SKIN
CONTACT. DO

NOT HEAT

Supplemental Safety and Health

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:115F,46C

Vapor Pres:200 MM HG

Vapor Density:2

Spec Gravity:(H2O=1) 1.2

pH:12

Evaporation Rate & Reference:(WATER = 1) 1

Solubility in Water:INSOL (DISPERSABLE)

Appearance and Odor:VISCOUS, PUNGENT LIQUID

Percent Volatiles by Volume:90

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG ALKALIS,

STRONG ACIDS, STRONG OXIDIZERS, REACTIVE METALS

===== Disposal Considerations =====

Waste Disposal Methods:USEPA HAZARDOUS WASTE NO 3, U080, D007, U154,
U220. CONSULT FEDERAL, STATE AND LOCAL REGULATORY AGENCIES FOR
PROPER DISPOSAL

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.