View NSN Online: https://aerobasegroup.es/nsn/6750-00-250-8581

SIMON H R CO,INC. -- CHEMBLEND FIXER PART 2 -- 6750-00-250-8581

Product ID:CHEMBLEND FIXER PART 2 MSDS Date:06/01/1993 FSC:6750 NIIN:00-250-8581 Kit Part:Y MSDS Number: BRGHV === Responsible Party === Company Name: SIMON H R CO, INC. Address:3515 MARMENCO COURT City:BALTIMORE State:MD ZIP:21230-3411 Country:US Info Phone Num:301-636-5555 Emergency Phone Num:301-636 -5555 CAGE:27912 === Contractor Identification === Company Name: SIMON H R CO, INC. Address:3515 MARMENCO COURT Box:City:BALTIMORE State:MD ZIP:21230-3411 Country:US Phone:410-636-5555 CAGE:27912 Ingred Name: ALUMINUM SULFATE (SARA III) CAS:10043-01-3 RTECS #:BD1700000 Other REC Limits:NONE RECOMMENDED OSHA PEL:2 MG/M3 ACGIH TLV:2 MG/M3; 9293 EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

================== Hazards Identificati

LD50 LC50 Mixture: NONE SPECIFIED BY MANUFACTURER. Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:SKIN AND EYE IRRITATION UNDER PROLONGED CONTACT. INGESTION MAY CAUSE NAUSEA, VOMITING, OR PURGING. Explanation of Carcinogenicity:NO INFORMATION GIVEN ON MSDS BY SUPPLIER Effects of Overexposure: INHALATION OF VAPORS ABOVE TLV MAY IRRITATE THE **RESPIRATORY TRACT. MAY IR** RITATE OR BURN EYES. MAY IRRITATE SKIN. MAY IRRITATE THE GASTROINTESTINAL TRACT. NO UNUSUAL CHRONIC TOXICITY. Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER. First Aid: EYES: IMMEDIATELY FLUSH WITH LARGE AMOUNTS OF WATER FOR 15 MINUTES AND GET MEDICAL ATTENTION. SKIN: REMOVE CONTAMINATED CLOTHING. FLUSH SKIN FOR 15 MINUTES. IF SYMPTOMS PERSIST, SEEK MEDICAL HELP. INH ALATION: REMOVE SUBJ ECT TO FRESH AIR. IF SYMPTOMS PERSIST, SEEK MEDICAL HELP. INGESTION: CONSCIOUS SUBJECT-IMMEDIATE GIVE LARGE AMOUNTS OF WATER AND INDUCE VOMITING. CALL FOR MEDICAL HELP. Flash Point:NONE Extinguishing Media: USE APPROPRIATE AGENT FOR SURROUNDING FIRE Fire Fighting Procedures:NONE SPECIFIED BY MANUFACTURER. Unusual Fire/Explosion Hazard:NONE SPECIFIED BY MANUFACTURER. ================== Accidental Release Measures _____ Spill Release Procedures: SOAK SPILL WITH SAW DUST, SAND, OIL DRY, OR OTHER ABSORBENT MATERIAL. Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER. Handling and Storage Precautions: STORE AS NORMAL. Other Precautions:NONE Respiratory Protection: NIOSH APPROVED RESPIRATOR FOR MISTS. Ventilation: NO SPECIAL VENTILATION IS NECESSARY, EXCEPT

IN SMALL ENCLOSED AREAS WHERE A LOCAL EXHAUST FAN SHOULD BE USED. Protective Gloves:LATEX OR NEOPRENE Eye Protection:SAFETY GLASSES WITH SIDE SHIELDS. Other Protective Equipment:CHEMICAL RESISTANT APRON. Work Hygienic Practices:NONE SPECIFIED BY MANUFACTURER. Supplemental Safety and Health KEY 1=HCC IS C3. THIS ITEM IS PART 2 OF A 2 PART KIT. SEE THIS NSN AND CAGE UNDER PN/IND A FOR INFORMATION OF PART 1 OF THIS PRODUCT.

HCC:C3 Boiling Pt:B.P. Text:>212F/100C Spec Gravity:1.3000 @15.6C pH:2.21 Solubility in Water:COMPLETE Appearance and Odor:COLORLESS, VINEGAR ODOR

Stability Indicator/Materials to Avoid:YES STRONG ALKALINE MATERIALS Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER. Hazardous Decomposition Products:NONE SPECIFIED BY MANUFACTURER.

Waste Disposa

I Methods:CONSULT FEDERAL, STATE, AND LOCAL REGULATIONS FOR LEGAL DISPOSAL METHODS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and a ssume responsibility for the suitability of this information to their particular situation.