

DOW CORNING CORP -- DOW CORNING (R) 3-7132 RTV ADHESIVE SEALANT -- 8030-00-180-6339

===== Product Identification =====

Product ID:DOW CORNING (R) 3-7132 RTV ADHESIVE SEALANT

MSDS Date:11/11/1992

FSC:8030

NIIN:00-180-6339

MSDS Number: BRGRT

=== Responsible Party ===

Company Name:DOW CORNING CORP

Address:SOUTH SAGINAW ROAD

City:MIDLAND

State:MI

ZIP:48686

Country:US

Info Phone Num:517-496-6000

Emerge

ncy Phone Num:517-496-5900

Preparer's Name:JACK L SHENEGER

CAGE:5D028

=== Contractor Identification ===

Company Name:DOW CORNING CORP

Address:3901 S SAGINAW RD

Box:997

City:MIDLAND

State:MI

ZIP:48686-0997

Country:US

Phone:517-496-6000/517-496-6315

CAGE:5D028

Company Name:DOW CORNING CORP

Address:2200 W SALZBURG RD

Box:City:AUBURN

State:MI

ZIP:48611

Country:US

Phone:517-496-4388

CAGE:71984

Company Name:INLAND PACKAGING INC

Address:209 PETERSON DR

Box:644

City:ELIZABETHTOWN

State:KY

ZIP:42701-9

804
Country:US
Phone:502-737-6757
CAGE:66172

===== Composition/Information on Ingredients =====

Ingred Name:METHYLTRIACETOXYSILANE (LIMITS ARE FOR ACETIC ACID, FORMED DURING CURING ON EXPOSURE TO WATER OR HUMID AIR)

CAS:4253-34-3
RTECS #:VV4500000
Fraction by Wt: 2%
Other REC Limits:NONE SPECIFIED
OSHA PEL:10 PPM
ACGIH TLV:10 PPM/STEL 15 PPM

Ingred Name:ETHYLTRIACETOXYSILANE (LIMITS ARE FOR ACETIC ACID, FORMED DURING CURING ON EXPOSURE TO WATER OR HUMID AIR)

CAS:1768
9-77-9
Fraction by Wt: 2%
Other REC Limits:NONE SPECIFIED
OSHA PEL:10 PPM
ACGIH TLV:10 PPM/STEL 15 PPM

Ingred Name:SILICA, AMORPHOUS

CAS:112945-52-5
RTECS #:VV7310000
Fraction by Wt: 10%
Other REC Limits:NONE SPECIFIED
OSHA PEL:6 MG/M3
ACGIH TLV:10 MG/M3 TOTAL DUST

===== Hazards Identification =====

Health Hazards Acute and Chronic:ACUTE; EYE: IRRITATES SLIGHTLY WITH REDNESS & SWELLING. SKIN: SINGLE SHORT EXPOSURE (300F.DONT EAT.AVOID BREATHING, SKIN/EYE CONTACT.

Other Precautions:REVIEW OSHA FORMALDEHYDE REGS FOR INFO-SAFE HANDLING REQUIREMNTS. PRODUCT FORMS ACETIC ACID (HOAC) W/EXPOSURE TO WATER/HUMID AIR. VENT TO CONTROL HOAC EXPOSURE W/IN 10 PPM (CURRENT TLV) OR USE RESPIRATORY PROTECTN. VENT TO CONTROL EXPOSURE.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE RESPIRATORY PROTECTION UNLESS LOCAL EXHAUST VENTILATION IS ADEQUATE OR AIR SAMPLING DATA SHOW EXPOSURES ARE WITHIN

TLV & PEL GUIDELINES. SUITABLE RESPIRATOR: ORGANIC VAPOR TYPE.

Ventilation:LOCAL EXHAUST: RECOMMENDED. MECHANICAL (GENERAL): RECOMMENDED.

Protective Gloves:RUBBER OR PLASTIC GLOVES ARE RECOMMENDED

Eye Protection:SAFETY GLASSES AS A MINIMUM

Other Protective Equipment:WASHING AT MEALTIME & END OF SHIFT IS ADEQUATE. REMOVE CONTAMINATED CLOTHING & SHOES ASAP & CLEAN BEFORE REUSE.

Work Hygienic Practices:GOOD PRACTICE REQUIRES THAT GROSS AMOUNT OF ANY CHEM BE REMOVED FROM SKIN AS AP, ESPECIALLY BEFORE EATING OR SMOKING.

Supplemental Safety and Health

THESE PRECAUTIONS ARE FOR ROOM TEMPERATURES HANDLING; USE AT ELEVATED TEMPERATUERS OR AEROSOL/SPRAY APPLICATION, MAY REQUIRED ADDED PRECAUTIONS.

===== Physical/Chemical Properties =====

HCC:V7

Vapor Pres: