

DEFT INC -- COMP A, PN 44GN007 -- 8010-01-218-0857

=====  
===== Product Identification =====

Product ID:COMP A, PN 44GN007

MSDS Date:06/30/1992

FSC:8010

NIIN:01-218-0857

Kit Part:Y

MSDS Number: BRHCF

=== Responsible Party ===

Company Name:DEFT INC

Address:17451 VON KARMAN AVENUE

City:IRVINE

State:CA

ZIP:92714

Country:US

Info Phone Num:714-474-0400

Emergency Phone Num:714-474-0400 800-424-9300(CHEMTREC)

P

reparer's Name:NORM GAUL

CAGE:33458

=== Contractor Identification ===

Company Name:DEFT INC

Address:17451 VON KARMAN AVE

City:IRVINE

State:CA

ZIP:92714-6205

Country:US

Phone:800 424-9300

CAGE:33458

Company Name:DEFT, INC.

Address:17451 VON KARMAN AVE

City:IRVINE

State:CA

ZIP:92614

Country:US

Phone:949-474-0400

CAGE:33461

=====  
===== Composition/Information on Ingredients =====

Ingred Name:2-BUTOXYETHANOL (SARA 313) (VAPOR PRESSURE 9 MM HG @ 77F)

CAS:111-76-2

RTECS #:KJ8575000

Frac

tion by Wt: 15%  
Other REC Limits:NONE SPECIFIED  
OSHA PEL:S, 50 PPM  
ACGIH TLV:S, 25 PPM; 9293

Ingred Name:C8&10 AROMATIC HYDROCARBON (VAPOR PRESSURE 3 MM HG @ 68 F)  
CAS:64742-95-6  
Fraction by Wt: 15%  
Other REC Limits:NONE SPECIFIED

Ingred Name:DISPERSION AGENT  
Fraction by Wt: < 1%  
Other REC Limits:NONE SPECIFIED

Ingred Name:BARIUM CHROMATE (SARA 313)  
CAS:10294-40-3  
Fraction by Wt: 25%  
Other REC Limits:NONE SPECIFIED  
OSHA PEL:.1 MP/F3  
ACGIH TLV:.05 MP/F3

Ingred Name:VOC: 391 G/L  
RTECS #:999999  
9VO  
Other REC Limits:NONE SPECIFIED

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO  
Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:YES  
Health Hazards Acute and Chronic:ACUTE: VAPORS IRRITATING TO EYES,  
NOSE, THROAT. INHALATION CAUSE HEADACHES, DIFFICULT BREATHING &  
LOSS OF CONSCIOUSNESS. CHRONIC: SKIN SENSITIZATION, ASTHMA, OTHER  
ALLERGIC RESPONSES. POSSIBLE KIDNEY & LIVER DAMAGE. DELAYED  
EFFEC  
TS INVOLVING THE BLOOD, GASTROINTESTINAL, NERVOUS &  
REPRODCTIVE SYSTEMS.ECZEMA, DERMATITIS.  
Explanation of Carcinogenicity:PROP 65-CARCENOGENIC. BARIUM  
CHROMATE,2-BUTOXYETHANOL,THESE PRODUCT CONTAINS CHEMICAL(S) KNOWN  
TO CALIF. TO CAUSE CANCER  
Effects of Overexposure:INHALATION: HEADACHE, DIZZINESS, STAGGERING  
GAIT, CONFUSION, UNCONSCIOUSNESS OR COMA. SKIN/EYE: IRRITATION.  
SWELLING, REDNESS, & RASH. EYES: LIQUID, AREOSOLS, VAPORS ARE  
IRRITATING. MAY CAUSE TEARING, REDNES

S, SWELLING, & STINGING

SENSATION. INGESTION: IRRITATION & CORROSIVE ACTION TO MOUTH, STOMACH, DIGESTIVE TRACT.

Medical Cond Aggravated by Exposure:INGESTION: VOMITING MAY CAUSE ASPIRATION OF THE SOLVENT, RESULTING IN CHEMICAL PNEUMONITIS. SKIN ABSORPTION: PROLONGED CONTACT WILL CAUSE DRYING & CRACKING OF THE SKIN, DUE TO DEFATTING ACTION.

=====  
===== First Aid Measures =====

First Aid:INHALATION: REMOVE TO FRESH AIR. RESTORE BREATHING. ASTHMATIC

TYPE SYMPTOMS MAY DEVELOP & MAY BE IMMEDIATE/DELAYED. GET MEDICAL ATTENTION. SKIN: WASH AFFECTED AREAS W/SOAP & WATER. EYES: FLUSH W/CLEAN LUKEWARM WATER (LOW PRESSURE) FOR AT LEAST 15 MINUTES, OCCASIONALLY LIFTING EYELIDS. GET MEDICAL ATTENTION. INGESTION: DO NOT INDUCE VOMITING. DON'T GIVE ANYTHING TO UNCONSCIOUS PERSON. GET MED ATTN.

=====  
===== Fire Fighting Measures =====

Flash Point Method:TCC

Flash Point:116F,47C

Lower Limits:1.0

0 %

Upper Limits:10.60 %

Extinguishing Media:FOAM, ALCOHOL FOAM, CO2, DRY CHEMICAL, WATER FOG.

Fire Fighting Procedures:FULL FIRE FIGHTING EQUIPMENT W/SELF-CONTAINED BREATHING APPARATUS. WATER USED TO COOL CLOSED CONTAINERS TO PREVENT PRESSURE BUILDUP, AUTO IGNITION OR EXPLOSION.

Unusual Fire/Explosion Hazard:ISOLATE FROM HEAT, SPARKS, & OPEN FLAME. CLOSED CONTAINERS EXPLODE EXPOSED TO EXTREME HEAT. OVEREXP TO DECOMP PROD CAUSE HEALTH HAZARD.SYMPT.NOT IMMED APPARENT.

=====  
===== Accidental Release Measures =====

Spill Release Procedures:EVACUATE ALL NON-ESSENTIAL PERSONNEL. REMOVE ALL SOURCES OF IGNITION (FLAME, SPARK SOURCES, HOT SURFACES). VENTILATE AREA CONTAIN AND REMOVE WITH INERT ABSORBENT AND NON-SPARKING TOOLS.

=====  
===== Handling and Storage =====

Handling and Storage Precautions:STORE IN BUILDINGS DESIGNED TO COMPLY W/OSHA 1910.106 AVOID STORING NEAR HIGH TEMP.,FIRE,OPEN FLAME,SPARK SO

URCES. STORE IN TIGHTLY CLOSED CONTAINERS.

Other Precautions:KEEP UPRIGHT/TIGHT TO PREVENT LEAKAGE. DON'T BREATH VAPORS, SPRAY MISTS. AVOID CONTACT WITH SKIN, EYES. DON'T INGEST. DO NOT HANDLE UNTIL THE MANUFACTURERS SAFETY PRECAUTIONS HAVE BEEN READ & UNDERSTOOD. SMOKE IN DESIGNATED AREAS ONLY.

=====  
===== Exposure Controls/Personal Protection =====

Respiratory Protection:RESPIRATOR THAT IS RECOMMENDED/APPROVED FOR USE IN AN ORGANIC VAPOR ENVIRONMENT (AIR PURIFYING OR FRESH AIR SUPPLIED) IS NECESSARY. OBSERVE OSHA REGULATIONS FOR RESPIRATOR USE.

Ventilation:EXHAUST VENTILATION SUFFICIENT TO KEEP THE AIRBORNE CONCENTRATIONS OF SOLVENT VAPORS OR MISTS BELOW THEIR RESPECTIVE TLV'S

Protective Gloves:COTTON, NEOPRENE, RUBBER, POLYETHYLENE.

Eye Protection:CHEMICAL GOGGLES, FULL-FACE SHIELD.

Other Protective Equipment:THE USE OF LONG SLEEVE & LONG LEG CLOTHING IS RECOMMENDED. REMOVE & WASH CONTAMINATED CLOTHING BEFORE REUSE.

Work Hygienic Practices:WASH HANDS BEFORE EATING, SMOKING, OR USING WASHROOM.

Supplemental Safety and Health

=====  
===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:308 TO 343F

Vapor Density:> AIR

Spec Gravity:1.51741

Evaporation Rate & Reference:0.44 X N-BUTYL ACETATE

Solubility in Water:INSOLUBLE

Appearance and Odor:GREEN LIQUID WITH SOLVENT ODOR

Percent Volatiles by Volume:44.6

=====  
===== Stability and Reactivity Data =====

Stability Indicator

Materials to Avoid:YES

OXIDIZING MATERIALS AND STRONG ACIDS. EPOXY RESINS UNDER UNCONTROLLED CONDITIONS.

Stability Condition to Avoid:HIGH TEMPERATURES. EPOXY RESINS UNDER UNCONTROLLED CONDITIONS.

Hazardous Decomposition Products:BY HIGH HEAT/TEMPERATURE: CARBON MONOXIDE, CARBON DIOXIDE, AND OXIDES OF NITROGEN. CHROMIUM OXIDES WHEN BURNED.

=====  
===== Disposal Considerations =====

Waste Disposal Methods:WASTE MUST BE DISPOSED OF IN ACCORDANCE WITH

LOCAL, STATE & FEDERAL ENVIRONMENTAL CONTROL REGULATIONS. EMPTY CONTAINERS MUST BE HANDLED WITH CARE, DUE TO PRODUCT RESIDUE AND FLAMMABLE VAPOR DO NOT INC INERATE CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.