

View NSN Online: <https://aerobasegroup.es/nsn/6850-01-313-1178>

THE DEXTER CORP,AUTOMOTIVE MATLS DIV (HYSOL DIV) -- AC4368 AEROSOL,PRODUCT
CODE:FK4368-AEROSOL -- 6850-01-313-1178

===== Product Identification =====

Product ID:AC4368 AEROSOL,PRODUCT CODE:FK4368-AEROSOL

MSDS Date:09/24/1992

FSC:6850

NIIN:01-313-1178

MSDS Number: BRHDJ

=== Responsible Party ===

Company Name:THE DEXTER CORP,AUTOMOTIVE MATLS DIV (HYSOL DIV)

Address:ONE DEXTER DRIVE

City:SEABROOK

Sta

te:NH

ZIP:03874

Country:US

Info Phone Num:603-474-5541

Emergency Phone Num:603-474-5541,800-424-9300(CHEMTREC)

Preparer's Name:KEN DECOSTA

CAGE:DO688

=== Contractor Identification ===

Company Name:DEXTER CORP THE HYSOL DIV

Address:1 DEXTER DR

Box:City:SEABROOK

State:NH

ZIP:03874

Country:US

Phone:603-474-5541/FAX: 603-474-5545

CAGE:1JB33

Company Name:RUDOLPH BROS AND COMPANY

Address:960 WALNUT STREET

Box:425

City:CANAL WINCHESTER

State:OH

ZIP:43110

Country:US

Phone:614-833-0707

CAGE:6S222

Company

Name:THE DEXTER CORP, HYSOL DIVISION
Address:15051 DON JULIAN ROAD
Box:1282
City:INDUSTRY
State:CA
ZIP:91749
Phone:(716) 372-6309
CAGE:DO688

===== Composition/Information on Ingredients =====

Ingred Name:STODDARD SOLVENT (BOILING POINT 308F-388F) (VM&P NAPHTHA)
CAS:8032-32-4
RTECS #:OI6180000
Fraction by Wt: 1.2%
Other REC Limits:NONE SPECIFIED
OSHA PEL:100 PPM
ACGIH TLV:100 PPM; 9293

Ingred Name:HEXANE (N-HEXANE)
CAS:110-54-3
RTECS #:MN9275000
Fraction by Wt: 43-45%
Other
REC Limits:NONE SPECIFIED
OSHA PEL:500 PPM
ACGIH TLV:50 PPM; 9293
EPA Rpt Qty:1 LB
DOT Rpt Qty:1 LB

Ingred Name:CHLORODIFLUOROMETHANE
CAS:75-45-6
RTECS #:PA6390000
Fraction by Wt: 37.4%
Other REC Limits:NONE SPECIFIED
OSHA PEL:1000 PPM
ACGIH TLV:1000PPM; 9293
Ozone Depleting Chemical:2

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III)
CAS:1330-20-7
RTECS #:ZE2100000
Fraction by Wt: 0.4%
Other REC Limits:NONE SPECIFIED
OSHA PEL:100 PPM/150 STEL
ACGIH TLV:100 PPM/150STEL;9293
EPA Rpt Qty:1000 LB

S
DOT Rpt Qty:1000 LBS

Ingred Name:ACETONE (SARA III)
CAS:67-64-1
RTECS #:AL3150000
Fraction by Wt: 12.6%
Other REC Limits:NONE SPECIFIED
OSHA PEL:1000PPM
ACGIH TLV:750PPM/1000STEL;9293
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:SILICONE BLEND
Fraction by Wt: >5%
Other REC Limits:NONE SPECIFIED

===== Hazards Identification =====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Ca

rcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:EYES: IRRITATION. SKIN: IRRITATION.

INHALATION/INGESTION: RESPIRATORY SYSTEM IRRITATION, DIZZINESS,
NAUSEA, HEADACHES, OTHER CNS EFFECTS, MAY IMPAIR CARDIOVASCULAR
FUNCTIONS. EXCESSIVE EXPOSURE CAN CAUSE LIVER, KIDNEY, AND BLOOD
SYSTEM DAMAGE, GI IRRITATION, NAUSEA, VOMITING, DIARRHEA, HEART
TISSUE SENSITIZATION.

Explanation of Carcinogenicity:THIS COMPOUND CONTAINS NO INGREDIENTS AT
CONCENTRATIONS

OF 0.1% OR GREATER THAT ARE CARCINOGENS OR SUSPECT
CARCINOGENS.

Effects of Overexposure:EYES: IRRITATION. SKIN: IRRITATION.

INHALATION/INGESTION: RESPIRATORY SYSTEM IRRITATION, DIZZINESS,
NAUSEA, HEADACHES, OTHER CNS EFFECTS. MAY IMPAIR CARDIOVASCULAR
FUNCTIONS. CAUSE LIVER, KIDNEY, AND BLOODSYSTEM DAMAGE, GI
IRRITATION, NAUSEA, VOMITING, DIARRHEA, HEART TISSUE SENSITIZATION.

Medical Cond Aggravated by Exposure:PERSONS WITH A HISTORY OF AILMENTS
OR WITH A PRE-EXISTING DI

SEASE INVOLVING THE EYES, SKIN, OR
RESPIRATORY TRACT MAY BE AT INCREASED RISK FROM EXPOSURE.

===== First Aid Measures =====

First Aid:EYES: FLUSH WITH LARGE AMOUNTS OF WATER. GET MEDICAL
ATTENTION. SKIN: REMOVE CONTAMINATED CLOTHING. WASH AREA WITH SOAP
AND WATER. INHALATION: MOVE TO FRESH AIR. IF NOT BREATHING GIVE
CPR. IF BREATHIN G DIFFICULT GIVE OXYGEN. DO NOT GIVE EPINEPHRINE
OR SIMILAR DRUGS. GET MEDICAL ATTENTION. INGESTION: DO N
OT INDUCE
VOMITING. GET MEDICAL ATTENTION.

===== Fire Fighting Measures =====

Flash Point:FLAMMABLE AEROS.
Extinguishing Media:CARBON DIOXIDE, FOAM, DRY CHEMICAL.
Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A
FULL FACED SELF CONTAINED BREATHING APPARATUS. COOL FIRE EXPOSED
CONTAINERS WITH WATER SPRAY.
Unusual Fire/Explosion Hazard:AVOID EXTREME HEAT, CONTAINERS MAY BURST.
COMBUSTION OR HEAT OF FIRE MAY PRODUCE HAZARDOUS
DECOMPOSITION
PRODUCTS AND VAPORS. KEEP AWAY FROM HOT SURFACES.

===== Accidental Release Measures =====

Spill Release Procedures:USE PROPER PERSONAL PROTECTION. REMOVE ALL
IGNITION SOURCES.PROVIDE ADEQUATE VENTILATION. COLLECT WITH
ABSORBENT AND PREVENT RUN-OFF. COLLECT ABSORBED WASTE FOR PROPER
DISPOSAL IN AN APPROVED CONTAINER.
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:STORE AWAY FROM HEAT AND FLAME. USE
WITH ADEQUATE VENTILATION. PROTECT CONTAINERS FROM PHYSICAL DAMAGE.
Other Precautions:AVOID PROLONGED OR REPEATED BREATHING OF VAPOR. AVOID
CONTACT WITH EYES. USE WITH ADEQUATE VENTILATION. VAPORS MAY BE
HEAVIER THAN AIR AND MAY COLLECT IN LOW AREAS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF USE CONDITIONS GENERATE AIRBORNE
CONTAMINATION, USE NIOSH/MSHA APPR

OVERED RESPIRATOR APPROPRIATE FOR
THE AIRBORNE LEVELS GENERATED.

Ventilation:LOCAL/GENERAL AS REQUIRED TO MAINTAIN PEL/TLV.

Protective Gloves:SOLVENT RESISTANT.

Eye Protection:CHEMICAL SPLASH GOGGLES.

Other Protective Equipment:EYE WASH STATION AND SAFETY SHOWER.

IMPERVIOUS WORK CLOTHING AND APRON AS NECESSARY TO AVOID SKIN
CONTACT.

Work Hygienic Practices:WASH AFTER HANDLING AND BEFORE EATING,
DRINKING, OR SMOKING. LAUNDRY CONTAMINATED CLOTHING BEFORE REUSE.

Supplemental Safety and
Health

===== Physical/Chemical Properties =====

HCC:V3

Boiling Pt:B.P. Text:AEROSOL

Vapor Pres:50 PSI

Vapor Density:2.82;AIR=1

Spec Gravity:0.819 +/-0.015

Evaporation Rate & Reference:8 (N-BUTYL ACETATE = 1)

Solubility in Water:INSOLUBLE

Appearance and Odor:CLEAR, COLORLESS. HEXANE ODOR.

Percent Volatiles by Volume:96.1

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

ALKALI OR ALKALINE EARTH METALS;

POWDERED ALUMINUM, ZINC, BERYLLIUM,
ETC.

Stability Condition to Avoid:HIGH TEMPERATURES, OPEN FLAMES AND OTHER
SOURCES OF IGNITION.

Hazardous Decomposition Products:PHOSGENE, HYDROGEN CHLORIDE, HYDROGEN
FLUORIDE.

Conditions to Avoid Polymerization:WILL NOT OCCUR.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF WASTE IN ACCORDANCE WITH LOCAL, STATE
AND FEDERAL REGULATIONS. CANS ARE UNDER PRESSURE. DO NOT PUNCTURE
OR I

NCINERATE.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.