

ACCRABOND, INC. -- SEALING COMPOUND -- 8030-01-158-6070

===== Product Identification =====

Product ID:SEALING COMPOUND

MSDS Date:03/20/1991

FSC:8030

NIIN:01-158-6070

MSDS Number: BRKKK

=== Responsible Party ===

Company Name:ACCRABOND, INC.

Address:8848 HACKS CROSS ROAD

City:OLIVE BRANCH

State:MS

ZIP:38654

Country:US

Info Phone Num:601-895-4480

Emergency Phone Num:601-895-4480 800-424-9300(CHEMTREC
)

CAGE:5V071

=== Contractor Identification ===

Company Name:ACCRABOND INC

Address:8848 HACKS CROSS RD

Box:City:OLIVE BRANCH

State:MS

ZIP:38654-3884

Country:US

Phone:601-895-4480

CAGE:5V071

===== Composition/Information on Ingredients =====

Ingred Name:DIETHYLENE GLYCOL DIMETHACRYLATE

CAS:23588-41-1

Fraction by Wt: < 95%

Other REC Limits:NONE SPECIFIED

Ingred Name:DIBUTYL MALEATE

CAS:105-76-0

RTECS #:ON0875000

Fraction by Wt: < 20%

Other REC Limits:NONE SPECIFIED

Ingred Name

:CUMENE HYDROPEROXIDE (SARA 313)

CAS:80-15-9

RTECS #:MX2450000

Fraction by Wt: 2%

Other REC Limits:NONE SPECIFIED

ACGIH TLV:50 PPM

EPA Rpt Qty:10 LBS

DOT Rpt Qty:10 LBS

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:POSSIBLE SKIN AND EYE IRRITATION / MAY
CAUSE SENSITIZATION IN SOME INDIVIDUALS.

Effects of Overexposure:SKIN AND
EYE IRRITATION.

===== First Aid Measures =====

First Aid:EYES: FLUSH WITH WATER AND CONSULT A PHYSICIAN. MAY IRRITATE
OR DAMAGE EYE TISSUE. SKIN: WASH AREA THOROUGHLY WITH SOAP AND
WATER. MAY CAUSE MILD SKIN IRRITATION. INHALATION: REMOVE TO FRESH
AIR. MA Y CAUSE SLIGHT IRRITATION TO RESPIRATORY SYSTEM.
INGESTION: INDUCE VOMITING. CONSULT A PHYSICIAN. MAY BE SLIGHTLY
TOXIC TO HUMANS.

===== Fire Fighting Measures ==
=====

Flash Point Method:PMCC

Flash Point:151F,66C

Extinguishing Media:DRY CHEMICAL, FOAM, CO2, WATER FOG.

Fire Fighting Procedures:SELF-CONTAINED BREATHING APPARATUS SHOULD BE
WORN

Unusual Fire/Explosion Hazard:EXTREME HEAT MAY CAUSE VIOLENT
POLYMERIZATION

===== Accidental Release Measures =====

Spill Release Procedures:ABSORB WITH INERT MATERIAL AND PLACE IN
CONTAINER FOR DISPOSAL.

===== Handling and Storage =====

=====

Handling and Storage Precautions:STORE IN COOL DARK PLACE BELOW 85F AND ABOVE 50F
Other Precautions:NONE

===== Exposure Controls/Personal Protection =====

Respiratory Protection:AT HIGH VAPOR CONCENTRATIONS, NIOSH APPROVED FOR ORGANIC VAPORS
Ventilation:LOCAL EXHAUST PREFERRED, GENERAL MECHANICAL ADEQUATE.
Protective Gloves:RUBBER
Eye Protection:CHEMICAL SPLASH GOGGLES
Other Protective Equipment:EYE WASH STAND
Work Hygienic Practices:WASH HANDS THOROUGHLY AFTER USE
Supplemental Safety and Health

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:>392F,>200C
Spec Gravity:1.056
Solubility in Water:SLIGHT
Appearance and Odor:VARIOUS COLORS; MILD PLEASANT ODOR

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZING AND REDUCING AGENTS
Stability Condition to Avoid:HEAT
Hazardous Decomposition Products:MAY PRODUCE ACIDS AND NOXIOUS GASES
Conditions to Avoid Polymerization:HEAT, LIGHT AND OXIDIZING AGENTS.
WATER MAY CAUSE POLYMERIZATION.

===== Disposal Considerations =====

Waste Disposal Methods:INCINERATE OR DISPOSE IN APPROVED LANDFILL.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this informati

on to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.