

CON-LUX COATINGS, INC. -- PRIMER, ENAMEL-UNDERCOAT, ODORLESS, INTERIO --
8010-00-269-2536

=====
Product Identification
=====

Product ID:PRIMER, ENAMEL-UNDERCOAT, ODORLESS, INTERIO

MSDS Date:05/01/1993

FSC:8010

NIIN:00-269-2536

MSDS Number: BRNKT

=== Responsible Party ===

Company Name:CON-LUX COATINGS, INC.

Address:226 TALMADGE ROAD

City:EDISON

State:NJ

ZIP:08818-0847

Country:US

Info Phone Num:201-

287-4000

Emergency Phone Num:800-424-9300 CHEMTREC

Preparer's Name:ED DOENGES

CAGE:60189

=== Contractor Identification ===

Company Name:CON-LUX COATINGS INC

Address:226 TALMADGE RD

Box:847

City:EDISON

State:NJ

ZIP:08818-0847

Country:US

Phone:732-287-4000

CAGE:60189

=====
Composition/Information on Ingredients
=====

Ingred Name:MINERAL SPIRITS (STODDARD SOLVENT)

CAS:64741-65-7

Fraction by Wt: 22.4%

Other REC Limits:NONE SPECIFIED

OSHA PEL:100 PPM

ACGIH TLV:100 PPM

Ingred Name

:TITANIUM DIOXIDE (TITANIUM OXIDE)

CAS:13463-67-7

RTECS #:XR2275000

Fraction by Wt: 19.8%

Other REC Limits:NONE SPECIFIED

OSHA PEL:15 MG/M3 TDUST

ACGIH TLV:10 MG/M3 TDUST; 9293

Ingred Name:CALCIUM CARBONATE (LIMESTONE)

CAS:1317-65-3

RTECS #:EV9580000

Fraction by Wt: 39.5%

Other REC Limits:NONE SPECIFIED

OSHA PEL:10 MG/M3

ACGIH TLV:10 MG/M3

=====
===== Hazards Identification =====

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:

ACUTE: IRRITATION OF EYES AND SKIN MAY

OCCUR WITH OVEREXPOSURE. CONTINUED BREATHING OF VAPORS MAY IRRITATE
RESPIRATORY TRACT.

CHRONIC: REPORTS HAVE ASSOCIATED PROLONGED
OCCUPATIONAL OVEREXPOSURE TO SOLVENTS WITH PERMANENT BRAIN &
NERVOUS SYSTEM DAMAGE.

Effects of Overexposure:HEADACHE, NAUSEA, AND DIZZINESS.

=====
===== First Aid Measures =====

First Aid:INHALATION: REMOVE VICTIM TO FRESH AIR. RESTORE RESPIRATION,
IF NE

CESSARY, TREAT SYMPTOMATICALLY. EYE CONTACT: FLUSH IMMEDIATELY
WITH COPIOUS AMOUNTS OF WATER FOR 15 MINUTES. CONSULT A PHYSICIAN.

SKIN CONTACT: WASH AFFECTED AREA WITH SOAP AND WATER. REMOVE
CONTAMINATED CLOTHING. INGESTION: DO NOT INDUCE VOMITING. CONTACT
PHYSICIAN IMMEDIATELY.

=====
===== Fire Fighting Measures =====

Flash Point:120F,49C

Lower Limits:1.0

Upper Limits:6.0

Extinguishing Media:CO2, DRY CHEMICAL

Fire Fighting Procedures:USE SCBA. WATE

R SPRAY MAY BE USEFUL IN
MINIMIZING VAPORS & COOLING CONTAINERS EXPOSED TO HEAT AND FLAMES.
Unusual Fire/Explosion Hazard:NO INFORMATION FOUND.

===== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE ALL IGNITION SOURCES. WEAR
APPROPRIATE PERSONAL PROTECTION EQUIPMENT AND APPROVED RESPIRATOR.
CONTAIN SPILL & PUT IN VAPOR TIGHT CONTAINERS.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN AREAS TO COMPLY WITH
ANSI-NFPA 30 FLAMMABLE AND COMBUSTIBLE LIQUIDS CODE.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE APPROVED NIOSH/MSHA ORGANIC VAPOR
RESPIRATOR.
Ventilation:SUFFICIENT VENT TO KEEP HAZARDOUS MATERIALS BELOW
APPLICABLE EXPOSURE LEVELS.
Protective Gloves:NEOPRENE
Eye Protection:SPLASH SHIELDS
Work Hygienic Practices:WASH HANDS PROPERLY BEFORE EATING, DRINKING, OR
USING WASHROOM FACILITIES.
Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:F4
Boiling Pt:B.P. Text:346F,174C
Vapor Pres:2
Vapor Density:>1
Spec Gravity:1.512
Viscosity:72 - 89 KU
Evaporation Rate & Reference: