DEVOE COATINGS CO -- DEVFLEX 601 595A 27880 SOFT WHITE -- 8010-01-206-1776 Product ID:DEVFLEX 601 595A 27880 SOFT WHITE MSDS Date: 10/02/1990 FSC:8010 NIIN:01-206-1776 MSDS Number: BRPJX === Responsible Party === Company Name: DEVOE COATINGS CO Address:4000 DUPONT CIRCLE City:LOUISVILLE State:KY ZIP:40207 Country:US Info Phone Num:502-897-9861 Emergency Phone Num:800-424-9300 (CHEMTREC) CAGE:1HK86 === Contractor Identification Company Name: DEVOE COATINGS CO Address:4000 DUPONT CIRCLE Box:7600 City:LOUISVILLE State:KY ZIP:40207-4802 Country:US Phone:502-897-9861 CAGE:1HK86 ======= Composition/Information on Ingredients ======== Ingred Name: NO INGREDIENT FOR THIS FORMULATION_INGREDIENT =========== Hazards Identification ========================== LD50 LC50 Mixture: NONE SPECIFIED BY MANUFACTURER. Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC :YES OSHA:NO Health Hazards Acute and Chronic:ACUTE:INHAL:IRRITATION OF RESPIRATORY TRACT; HEADACHE, NAUSEA, DIZZINESS. SKIN OR EYE CONTACT: PRIMARY IRRITATION. CHRONIC:PROLONGED OR REPEATED BREATHING OF SPRAY MIST &/OR SANDING DUST OVER A PERIOD OF YEARS MAY CAUSE DUST DISEASE OF THE LUNGS. Explanation of Carcinogenicity: ANTIMONY TRIOXIDE: GROUP 2B(IARC). Effects of Overexposure: SEE HEALTH HAZARDS. Medical Cond Aggravated by Exposure: NONE WHEN USED I/A/W SAFE HANDLING & USE

======================================
First Aid:INHAL:REMOVE TO FRESH AIR. EYES:FLUSH IMMEDIATELY W/LARGE AMOUNTS OF WATER FOR AT LEAST 15 MINUTES. CALL MD FOR MEDICAL TREATMENT. SKIN:REMOVE W/SOAP & WATER. REMOVE SOILED CLOTHING. INGEST:DRINK 1 OR 2 GLASSES OF WATER TO DILUTE. DO NOT INDUCE VOMITING. CALL MD IMMEDIATELY. TREAT SYMPTOMATICALLY.
======================================
Flash Point:NONE Lo wer Limits:1.1% Extinguishing Media:IN CASE OF FIRE USE CO2, DRY CHEM, FOAM OR OTHER
NPFA APPROVED METHOD FOR TREATING A CLASS B FIRE. Fire Fighting Procedures:WEAR NIOSH/MSHA APPRVD SCBA & FULL PROT EQUIP . SUMMON PROFESSIONAL FIREFIGHTERS. H2O SPRAY MAY BE INEFT. IF H2O IS USED, FOG NOZZ ARE PREF. IF(SUPDAT) Unusual Fire/Explosion Hazard:DUE TO PRESS BUILD-UP, CLSD CNTNRS EXPOSED TO EXTREME HEAT MAY EXPLODE. DURING EMER CNDTNS, OVEREXP TO DECOMP PRODS MAY CAUSE HLTH HAZ. SY
MPS MAY NOT BE(SUPDAT)
=========== Accidental Release Measures ===========
Spill Release Procedures:WASH W/WATER. CONTAIN SPILLED MATERIAL & REMOVE W/INERT ABSORBENT. STORE IN CLOSED CONTAINER UNTIL PROPERLY DISPOSED OF. Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.
============= Handling and Storage ==============
Handling and Storage Precautions:STORE BELOW 110F & KEEP FROM FREEZING. KEEP CONTAINER CLOSED WHEN NOT IN USE. DO NOT REUSE EMTP Y
CONTAINERS. KEEP OUT OF REACH OF CHILDREN. Other Precautions:DO NOT TRANSFER CONTENTS TO BOTTLES OR OTHER UNLABELLED CONTAINERS. DO NOT GET IN EYES.
====== Exposure Controls/Personal Protection ========
Respiratory Protection:DO NOT BREATHE VAPS, SPRAY MIST/SANDING DUST. WHEN SPRAY APPLIED IN OUTDOOR/OPEN AREAS W/UNRESTRICTED VENT & DURING SANDING/ GRINDING OPERATIONS, USE NIOSH/MSHA APPRVD MECH

INFORMATION.

FILTER RESP TO REMOVE SOLID AIRBORNE PARTICLES OF OVERSPRAY

(SUPDAT

Ventilation: USE ONLY W/ADEQ VENT. PROVIDE GEN DILUTION/LOC EXHST VENT IN VOL & PATTERN TO KEEP AIR CONTAM CONC BELOW CURRENT(ING 11)

Protective Gloves: IMPERVIOUS GLOVES.

Eye Protection: CHEMICAL WORKERS GOGGLES .

Other Protective Equipment: NONE REQUIRED.

Work Hygienic Practices: REMOVE & WASH SOILED CLOTHING BEFORE REUSE. WASH HANDS BEFORE EATING, SMOKING OR USING THE WASHROOM.

Supplemental Safety and Health

FIRE FIGHT PROC:EXPOSED TO FIRE/EXTREME HEAT, H2O SHOULD BE USED TO

COOL CLSD CNTNRS & PVNT PRESS BUILD-UP/POSS AUTO-IGNIT. EXPLO HAZ:IMMED APPARENT. GET MD. HAZ DECOMP PROD:OF ANTIMONY. RESP PROT:& S ANDING DUST. WHEN USED IN RESTRICTED VENT AREAS, WEAR NIOSH/ MSHA APPRVD CHEM/MECH FILTERS DESIGNED TO REMOVE (ING 8)

NIOSH/ MSHA APPRVD CHEM/MECH FILTERS DESIGNED TO REMOVE (IN

HCC:N1

Boiling Pt:B.P. Text:212F,100C

Vapor Pres:SEE INGS Vapor Density:SEE INGS

Evaporation Rate & Evaporation R

Appearance and Odor: NONE SPECIFIE

D BY MANUFACTURER.

Percent Volatiles by Volume:59.88

======== Stability and Reactivity Data =========

Stability Indicator/Materials to Avoid:YES

NONE SPECIFIED BY MANUFACTURER.

Stability Condition to Avoid: NONE SPECIFIED BY MANUFACTURER.

Hazardous Decomposition Products:MAY CAUSE HAZ FUMES WHEN HEATED TO DECOMP. FUMES MAY CONTAIN CO, CO2, NOX, CHLORINE, HCL, OXIDES & CHLORIDES (SUPDAT)

====== Disposal Considerations ===========

Waste Dispos

al Methods:DISPOSE OF I/A/W LOCAL, STATE & FEDERAL REGULATIONS. INCINERATE ONLY IN APPROVED FACILITY. DO NOT INCINERATE CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document

should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.