Product ID:S14085 TTP91, BROWN 10076

MSDS Date:04/07/1993

FSC:8010

NIIN:00-597-8199

MSDS Number: BRQPH === Responsible Party ===

Company Name: WARREN PAINT AND COLOR COMPANY

Address:700 WEDGEWOOD AVE

City:NASHVILLE

State:TN ZIP:37203 Country:US

Info Phone Num:615-292-6655

Emergency Phone Num:615-292-6655

CAGE:1J302

=== Contractor Identification ===

Company Name: WARREN PAINT AND COLOR COMPANY

Box:City:NASHVILLE

State:TN

ZIP:37203-5526 Country:US

Phone:615-292-6655

CAGE:1J302

======= Composition/Information on Ingredients ========

Ingred Name: VM&P NAPHTHA (VAPOR PRESSURE 26.9 MM HG @ 100F)

CAS:8030-30-6

RTECS #:DE3030000 Fraction by Wt: 26.09%

Other REC Limits:300.00 PPM

Ingred Name: TOLUENE (SARA III) (VAPOR PRESSURE 55.9 MM HG @ 100F)

CAS:108-88-3

RTECS #:XS5250000 Fraction by Wt: 9.27%

Other REC Limits:200.00 PPM

OSHA PEL

:200 PPM/150 STEL ACGIH TLV:50 PPM; 9293 EPA Rpt Qty:1000 LBS

EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS

Ingred Name: METHYL ETHYL KETONE (SARA III) (VAPOR PRESSURE 155.1 MM HG

@ 100F) CAS:78-93-3

RTECS #:EL6475000 Fraction by Wt: 8.69%

Other REC Limits:200.00 PPM

EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Ingred Name: METHYL N-AMYL KETONE (VAPOR PRESSURE 2.1 MM HG @ 20C)

CAS:110-43-0

RTECS #:MJ5075000 Fraction by Wt: 7.02%

Other REC Limits: NONE SPECIFIED

Ingred Name:XYLENE (SARA III) (VAPOR PRESSURE 21.2 MM HG @

100F)

CAS:1330-20-7

RTECS #:ZE2100000 Fraction by Wt: 1.87%

Other REC Limits:100.00 PPM

EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS

Ingred Name: MINERAL SPIRITS (VAPOR PRESSURE 6.2 MM HG @ 100F)

CAS:64475-85-0 RTECS #:PY8240000 Fraction by Wt: 0.34%

Other REC Limits:500.00 PPM

Ingred Name: VOLATILE ORGANIC COMPOUNDS: 4.68?

RTECS #:9999999VO

Other REC Limits: NONE SPECIFIED

========= Hazards Identification ==============

Routes of Entry: Inhalation:YES Skin:YES Ingestion:Y

Health Hazards Acute and Chronic:INHALATION: DIZZINESS, BREATHING DIFFICULTY, HEADACHE, AND LOSS OF COORDINATION. EYE CONTACT: SEVERE IRRITATION, TEARING, REDNESS, AND BLURRED VISION. SKIN CONTACT: CAN DRY AND DEFAT SKIN CAUSING CRAC KS, IRRITATION, AND DERMATITIS. INGESTION: CAN CAUSE GASTROINTESTINAL IRRITATION, VOMITING, NAUSEA, AND DIARRHEA.

Medical Cond Aggravated by Exposure: ANESTHESIA, RESPIRATORY TRACT IRRITATION, DERMATITIS, NAUSEA, VOMITING.

	=======	
======	First Aid Measures	

First Aid:INHALATION OVEREXPOSURE: MOVE PERSON TO FRESH AIR. IF BREATHING STOPS, APPLY ARTIFICAIL RESPIRATION AND SEEK IMMEDIATE MEDICAL ATTENTION. EYE CONTACT: FLUSH WITH LARGE QUANTITIES OF WATER FOR 15 MINUT ES. SKIN CONTACT: WASH THOROUGHLY WITH SOAP AND WATER AND SEE A DOCTOR. INGESTION: DO NOT INDUCE VOMITING, CAN CAUSE CHEMICAL PNEUMONITIS AND PULMONARY EDEMA. CONTACT PHYSICIAN IMMEDIATELY.

= Fire Fighting Measures =========

Flash Point Method:TCC Flash Point:28.0F,-2.2C

Extinguishing Media: FOAM, ALCOHOL FOAM, CO2, DRY CHEMICAL, WATER FOG, OTHER

Fire Fighting Procedures: RESPIRATORY EQUIPMENT SHOULD BE WORN TO AVOID INHALATION OF CONCENTRATED VAPORS. WATER SHOULD NOT BE USED EXCEPT AS FOG TO KEEP NEARBY CONTAINERS COOL.

Unusual Fire/Explosion Hazard: HANDLE AS COMBUSTIBLE MATERIAL. VAPOR FORM EXPLOSIVE MIX IN AIR BETWEEN VAPOR & LOWER EXPLOSION LIMITS

WHICH CAN BE IGNITED BY IGNITION SOURCES.

A ' 1 (1 D) A4	
 Accidental Release Measures	

Spill Release Procedures:ELIMINATE IGNITION SOURCES. PROVIDE GOOD VENTILATION. DIKE SPILL AREA AND ADD ABSORBENT EARTH OR SAWDUST TO APPLIED LIQUID

=========== Handling and Storage ==============

Handling and Storage Precautions: USE NON-SPARKING UTENSILS WHEN HANDLING THIS MATERIAL. AVOID HOT METAL SURFACES. USE IN COOL, WELL-VENTED AREA. KEEP C

ONTAINER CLOSED WHEN NOT IN USE. Other Precautions: KEEP AWAY FROM EXCESSIVE HEAT AND OPEN FLAMES. SMOKING IN AREAS WHERE THIS MATERIAL IS USED SHOULD BE STRICTLY PROHIBITED. ===== Exposure Controls/Personal Protection ======== Respiratory Protection: WHEN SPRAYING, USE NIOSH CARTRIDGE RESPIRATOR/GAS MASK SUITABLE TO KEEP AIRBORNE MIST/VAPOR CONCENTRATIONS BELOW LIMITS. WHEN USING IN POORLY VENTED & CONFINED AREA, USE FRESH AIR SUPPLYING RESPIRATOR OR SELF-CON **TAINED** BREATHING APPARATUS. Ventilation: USE GENERAL MECHANICAL VENT/LOCAL EXHAUST TO KEEP CONCENTRATIONS BELOW TLV. USE EXPLOSION PROOF VENT EQUIPMENT. Protective Gloves: IMPERMEABLE CHEMICAL HANDLING GLOVES Eye Protection: CHEM SAFETY GLASSES, GOGGLES, FACESHIELD Other Protective Equipment: USE IMPERMEABLE APRONS AND PROTECTIVE CLOHTING WHENEVER POSSIBLE TO PREVENT SKIN CONTACT. USE HEADCAPS WHEN POSSIBLE Work Hygienic Practices: EYE WASHES AND SAFETY SHOWERS IN THE WORKPLACE IS RECOMMENDED. Supplemental Safety and Health ======== Physical/Chemical Properties =========== HCC:F2 Boiling Pt:B.P. Text:172 TO 307F Vapor Density:> AIR Evaporation Rate & Evaporation R Percent Volatiles by Volume:71.05 ======== Stability and Reactivity Data =========== Stability Indicator/Materials to Avoid:YES ALKALINE MATERIALS, STRONG ACIDS, AND OXIDIZING MATERIALS. Stability Condition to Avoid: EXCESSIVE HEAT, POOR VENTILATION, CORROSIVE ATMOSPHERES, EXCESSIVE AGING. Hazardous Decomposition Products: CARBON MONOXIDE, CARBON DIOXIDE, OXIDES OF NITROGEN. Conditions to Avoid Polymerization: EXCESSIVE HEAT, POOR VENTILATION, CORROSIVE ATMOSPHERES, EXCESSIVE AGING. ======= Disposal Considerations ============

Waste Disposal Methods:COLLECT ABSORBENT/SPILLED LIQUID MIXTURE INTO

Waste Disposal Methods: COLLECT ABSORBENT/SPILLED LIQUID MIXTURE INTO METAL CONTAINERS. CONSULT LOCAL, STATE, & FEDERAL HAZARDOUS WASTE REGULATIONS BEFORE DISPOSING INTO APPROVE

D HAZARDOUS WASTE LANDFILL. OBEY RELEVANT LAWS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.