

CHEMFAB NEW YORK, INC. -- PC 903 FLAT WHITE COLOR CODE 37875 -- 5410-00-193-4092

===== Product Identification =====

Product ID:PC 903 FLAT WHITE COLOR CODE 37875

MSDS Date:11/02/1992

FSC:5410

NIIN:00-193-4092

Kit Part:Y

MSDS Number: BRSRY

=== Responsible Party ===

Company Name:CHEMFAB NEW YORK, INC.

Address:2015 WALDEN AVENUE

City:BUFFALO

State:NY

ZIP:14225-5113

Country:US

Info Phone Num:716-684-0

200

Emergency Phone Num:716-684-0200

CAGE:13214

=== Contractor Identification ===

Company Name:CHEMFAB NEW YORK INC DIV OF CHEMICAL FABRICS CORP

Address:2015 WALDEN AVE

Box:City:BUFFALO

State:NY

ZIP:14225-5113

Country:US

Phone:716-684-0200

CAGE:13214

Company Name:CLIFTON ADHESIVE INC

Address:BURGESS PL

Box:City:WAYNE

State:NJ

ZIP:07470

Country:US

Phone:201-694-0845; 973-694-0845

CAGE:79833

===== Composition/Information on Ingredients =====

Ingred Name:TOLUENE (SARA III)

CAS:1

08-88-3
RTECS #:XS5250000
Fraction by Wt: 35% %
Other REC Limits:NONE RECOMMENDED
OSHA PEL:200 PPM/150 STEL
ACGIH TLV:50 PPM; 9293
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III)
CAS:1330-20-7
RTECS #:ZE2100000
Fraction by Wt: 35% %
Other REC Limits:NONE RECOMMENDED
OSHA PEL:100 PPM/150 STEL
ACGIH TLV:100 PPM/150STEL;9293
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:N-BUTYL ALCOHOL (SARA III)
CAS:71-36-3
RTECS #:EO1400000
Fraction by Wt: 7%
%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:100 PPM
ACGIH TLV:S, C 50 PPM; 9293
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:TITANIUM DIOXIDE
CAS:13463-67-7
RTECS #:XR2275000
Other REC Limits:NONE RECOMMENDED
OSHA PEL:15 MG/M3 TDUST
ACGIH TLV:10 MG/M3 TDUST; 9293

Ingred Name:CHLOROSULFONATED POLYETHYLENE
Other REC Limits:NONE RECOMMENDED

Ingred Name:VOLATILE ORGANIC COMPOUND; 6.21 #/GAL OR 0.742 KG/LITER
RTECS #:9999999VO
Other REC Limits:NONE RECOMMENDED

===== Haz

ards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE: ACUTE: MAY CAUSE SKIN AND EYE
IRRITATION ON CONTACT. MAY IRRITATE RESPIRATORY SYSTEM AND MUCOUS
MEMBRANES IF INHALED; ALSO MAY CAUSE CENTRAL NERVOUS SYSTEM
EFFECTS. INGESTION MAY CAUSE STOMACH DISTRESS. CHRONIC: PROLONGED
OR REPEATED EXPOSURE MAY CAUSE NERVE DAMAGE, DAMAGE HEARING OR

SENSE OF BALANCE.

Explanation of Carcinogenicity:NO INGREDIENT OF A CONCENTRATION OF 0.1%
IS LISTED AS A CARCINOGEN OR SUSPECTED CARCINOGEN.

Effects of Overexposure:HEALTH HAZARDS: ALSO MAY CAUSE LIVER, KIDNEY,
LUNG & SPLEEN DAMAGE. INHALED:COUGHING, SHORTNESS OF BREATH,
NARCOSIS, TINLING AND WEAKNESS IN ARMS. EYES: TEARING, DISCOMFORT,
REDNESS. SKIN: DRY, CRACKED SKIN; RASH, DISCOMFORT. INGESTED:
NAUSEA, VOMITING.

Medical Cond Aggravated by Exposure:RESPIRATORY AILMENTS

==

===== First Aid Measures =====

First Aid:INHALED: MOVE TO FRESH AIR. GIVE RESPIRATORY SUPPORT AS
NEEDED. EYES: FLUSH WITH LOTS OF WATER FOR 15 MINUTES, HOLDING
EYELIDS OPEN. SEE DOCTOR. SKIN: WASH WITH SOAP AND WATER. IF
SYMPTOMS PERSIST, SEE DOCTOR. INGESTED: DO NOT INDUCE VOMITING!
GET IMMEDIATE MEDICAL SUPPORT.

===== Fire Fighting Measures =====

Flash Point Method:TCC

Flash Point:40.0F,4.4C

Autoignition

Temp:Autoignition Temp Text:649F

Lower Limits:1.0

Upper Limits:11.2

Extinguishing Media:CARBON DIOXIDE, FOAM, AND DRY CHEMICAL

Fire Fighting Procedures:WEAR USE NIOSH/MSHA APPROVED RESPIRATOR AND
BUNKER GEAR. USE WATER SPRAY TO COOL FIRE EXPOSED STRUCTURES AND TO
DISPERSE VAPORS IF THERE IS NO FIRE.

Unusual Fire/Explosion Hazard:VAPOR IS HEAVIER THAN AIR AND MAY TRAVEL
CONSIDERABLE DISTANCE TO A SOURCE OF IGNITION AND FLASHBACK.

===== Accidental Release Measures =====

=====

Spill Release Procedures:ELIMINATE ALL SOURCES OF IGNITION. ABSORB WITH SAND, EARTH, VERMICULATE, OIL-DRY, OR SOL-SPEED-DRI. SHOVEL MATERIAL INTO STEEL CONTAINER AND COVER.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP CONTAINERS TIGHTLY CLOSED. STORE IN AN APPROVED SOLVENT STORAGE AREA. KEEP AWAY FROM SOURCES OF IGNITION AND STRONG OXIDIZING AGENTS.

Oth

er Precautions:KEEP AREA CLEAN. CLEAN-UP SPILLS IMMEDIATELY. USE PROPER BONDING AND GROUNDING PROCEDURES DURING TRANSFER OPERATIONS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE USE NIOSH/MSHA APPROVED RESPIRATOR WITH ORGANIC VAPOR CARTRIDGE OR AIR-SUPPLYING RESPIRATOR AS REQUIRED TO MAINTAIN EXPOSURE LEVELS BELOW REGULATORY LIMITS. USE IN ACCORDANCE WITH 29 CFR 1910.134.

Ventilation:USE ADEQUATE MECHANICAL (EXPLOSION-PROOF) VENTILATION OR

LOCAL EXHAUST TO MAINTAIN EXPOSURE BELOW REGULATORY LIMITS.

Protective Gloves:PVA

Eye Protection:SAFETY GLASSES

Other Protective Equipment:PROTECTIVE CLOTHING AS REQUIRED TO PREVENT SKIN CONTACT.

Work Hygienic Practices:WASH HANDS AFTER USE. LAUNDER CONTAMINATED CLOTHES BEFORE REUSE.

Supplemental Safety and Health
PART A OF 5 PART KIT.

===== Physical/Chemical Properties =====

HCC:F2

Boiling Pt:B.P. Text:231F,111C

Vapor Pres:23 MM HG

Vapor Den

sity:3.4(AIR=1)
Spec Gravity:0.978 (WATER=1)
Appearance and Odor:WHITE LIQUID, SWEET RUBBERY ODOR

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS

Stability Condition to Avoid:AVOID HEAT, OPEN FLAMES, SPARKS, HOT
SURFACES AND STRONG OXIDIZING AGENTS.

Hazardous Decomposition Products:OXIDES OF CARBON, SULFUR, ANTIMONY,
MAGNESIUM. HYDROGEN CHLORIDE, HYDROGEN SULFIDE.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND
FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.