

DOW CORNING CORP -- 340 HEAT SINK COMPOUND -- 6850-00-927-9461
===== Product Identification =====

Product ID:340 HEAT SINK COMPOUND

MSDS Date:04/25/1990

FSC:6850

NIIN:00-927-9461

MSDS Number: BSFJH

=== Responsible Party ===

Company Name:DOW CORNING CORP

Address:3901 SOUTH SAGINAW ROAD

Box:997

City:MIDLAND

State:MI

ZIP:48640

Country:US

Info Phone Num:517-496-6000

Emergency Phone Num:517-496-5900

Pr

eparer's Name:JACK L. SHENEBERGER

CAGE:5D028

=== Contractor Identification ===

Company Name:DOW CORNING CORP

Address:3901 S SAGINAW RD

Box:997

City:MIDLAND

State:MI

ZIP:48686-0997

Country:US

Phone:517-496-6000/517-496-6315

CAGE:5D028

Company Name:DOW CORNING CORP

Address:2200 W SALZBURG RD

Box:City:AUBURN

State:MI

ZIP:48611

Country:US

Phone:517-496-4388

CAGE:71984

===== Composition/Information on Ingredients =====

Ingred Name:NO INGREDIENT FOR THIS FORMULATION_INGREDIENT

===

===== Hazards Identification =====

Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE: EYES: TEMPORARY DISCOMFORT.

SKIN: NO KNOWN ADVERSE EFFECTS. INHALATION: NO INJURY LIKELY.

INGESTION: NO INJURY EXPECTED. CHRONIC: SKIN IRRITATON. DIGESTIVE DISCOMFORT.

Explanation of Carcinogenicity:PRODUCT CONTAINS NO INGREDIENTS

CURRENTLY CLASSIFIED AS CARCINOGENIC BY

NTP, IARC OR OSHA.

Effects of Overexposure:EYES: TEMPORARY DISCOMFORT WITH MILD REDNESS

AND DRYNESS SIMILAR TO WINDBURN. SKIN: IRRITATION ON PROLONGED OR

REPEATED CONTACT. INHALATION: NO IRRITATION EXPECTED. INGESTION: NO

IRRITATION EXPECTED. SWALLOWING LARGE AMOUNTS MAY CAUSE DIGESTIVE DISCOMFORT.

Medical Cond Aggravated by Exposure:MAY ENHANCE ALLERGIC CONDITIONS ON CERTAIN INDIVIDUALS.

===== First Aid Measures =====

First Aid:EYES:

FLUSH IMMEDIATELY WITH WATER. SKIN: WIPE OFF AND WASH

WITH WATER. INHALATION: NO FIRST AID SHOULD BE NEEDED. INGESTION:

NO FIRST AID SHOULD BE NEEDED.

===== Fire Fighting Measures =====

Flash Point Method:OC

Flash Point:>250F,>121C

Extinguishing Media:USE WATER FOG, CARBON DIOXIDE, FOAM, OR DRY CHEMICAL.

Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE CLOTHING AND

EQUIPMENT AND A FULL FACED SELF CONTAINED BREATHING APPARATUS.

Unusual Fir

e/Explosion Hazard:NONE SPECIFIED BY MANUFACTURER.

===== Accidental Release Measures =====

Spill Release Procedures:MOP, WIPE OR SOAK WITH ABSORBENT MATERIAL AND

PLACE IN APPROPRIATE DISPOSAL CONTAINER. WASH AREA WITH SOAP AND WATER.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:USE REASONABLE CARE AND CAUTION.

Other Precautions:THESE PRECAUTIONS ARE FO

R ROOM TEMPERATURE HANDLING.

USE AT ELEVATED TEMPERATURES, OR AEROSOL/SPRAY APPLICATIONS, MAY
REQUIRE ADDED PRECAUTIONS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE NORMALLY NEEDED.

Ventilation:MECHANICAL (GENERAL) VENTILATION RECOMMENDED.

Protective Gloves:NONE NORMALLY NEEDED.

Eye Protection:SAFETY GLASSES.

Other Protective Equipment:NONE SPECIFIED BY MANUFACTURER.

Work Hygienic Practices:WASH AT MEALTIME AND AT END OF SHIFT.

Supple

mental Safety and Health

NO INJURY FROM DUSTS SHOULD OCCUR DURING REASONABLE USE. IF USE CREATES
RESPIRABLE PARTICLES, SOME RESPIRATORY SYSTEM INJURY MAY OCCUR.

TRACES OF FORMALDEHYDE (CARCINOGEN) MAY FORM IF HEATED IN AIR AB
OVE 300F(149C). PROVIDE VENTILATION TO CONTROL VAPOR EXPOSURE WHEN
HANDLING AT ELEVATED TEMPERATURES.

===== Physical/Chemical Properties =====

HCC:N1

Boiling Pt:B.P. Text:NOT GIVEN

Melt/Freeze Pt:M.P/F.P Text:NOT GIVEN

Vapor Pre

s: