

INDUSTRIAL PACKAGING CO, INC -- SWEEPING COMPOUND (100 LBS) -- 7930-00-132-5265

===== Product Identification =====

Product ID:SWEEPING COMPOUND (100 LBS)

MSDS Date:05/30/1991

FSC:7930

NIIN:00-132-5265

MSDS Number: BSHRL

=== Responsible Party ===

Company Name:INDUSTRIAL PACKAGING CO, INC

Address:ROUTE 54 EAST

Box:187

City:RIVERSIDE

State:PA

ZIP:17868

Country:US

Info Phone Num:717-275-8650

Emergency

Phone Num:717-275-8650

Preparer's Name:PAUL L OSHIRAK II

CAGE:62067

=== Contractor Identification ===

Company Name:INDUSTRIAL PACKAGING CO INC

Address:RT 54 E

Box:187

City:RIVERSIDE

State:PA

ZIP:17868

Country:US

CAGE:62067

===== Composition/Information on Ingredients =====

Ingred Name:PETROLEUM DISTALLATE 510 (PENZOIL)

CAS:68476-34-6

Fraction by Wt: 10-12%

Other REC Limits:NONE SPECIFIED

Ingred Name:SAWDUST

CAS:9004-34-6

RTECS #:FJ5691460

Fraction by Wt: 39%

Other REC Limit

s:NONE SPECIFIED

Ingred Name:SAND (WHITE MASONS)

Fraction by Wt: 49%

Other REC Limits:NONE SPECIFIED

===== Hazards Identification =====

Routes of Entry: Inhalation:UNKNOWN Skin:YES Ingestion:YES

Health Hazards Acute and Chronic:IRRITATION AND INFLAMMATION OF THE SKIN

Effects of Overexposure:SLIGHT SKIN IRRITATION AND INFLAMMATION

Medical Cond Aggravated by Exposure:NONE KNOWN

===== First Aid Measures =====

First A

id:SKIN: WASH THOROUGHLY WITH PLENTY OF MILD SOAP AND WATER.

EYES: FLUSH EYES WITH CLEAN, LOW PRESSURE WATER FOR AT LEAST 15 MINUTES OCCASIONALLY LIFTING EYE LIDS. IF PAIN PERSISTS SEEK MEDICAL ATTENTION .

===== Fire Fighting Measures =====

Flash Point Method:PMCC

Flash Point:257F,125C

Extinguishing Media:WATER, WATER FOAM, DRY CHEMICAL OR CARBON DIOXIDE

Fire Fighting Procedures:NONE REQUIRED

Unusual Fire/Explosion Hazard:NONE

=====

Accidental Release Measures =====

Spill Release Procedures:SWEEP AND/OR SHOVEL INTO CONTAINER. REUSE IF NOT CONTAMINATED

===== Handling and Storage =====

Handling and Storage Precautions:STORE AWAY FROM STRONG OXIDIZERS, OXYGEN, LIQUID CHLORINE, STRONG ACIDS, ALKALIES AND OPEN FLAMES AND HEAT.

Other Precautions:NONE KNOWN

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NOT REQUIRED (DUST-

DOWN PRODUCT)
Ventilation:NOT REQUIRED
Protective Gloves:ANY GLOVES IF SUSCEPTABLE TO PETROLEUM
Eye Protection:SAFTY GLASSES IF EYE CONTACT VERY LIKELY
Other Protective Equipment:NOT REQUIRED
Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:N1
Spec Gravity:1:1.18(WATER=1)
Solubility in Water:INSOLUBLE
Appearance and Odor:NATURAL WOOD, SAND COLOR WITH FUEL OIL OR DIESEL
FUEL ODOR

===== Stability and Reactivity Data =====
=====

Stability Indicator/Materials to Avoid:YES
MAY REACT WITH VERY STRONG OXIDIZING AGENTS, OXYGEN, LIQUID CHLORINE,
STRONG ACIDS OR ALKALIES
Stability Condition to Avoid:NONE KNOWN
Hazardous Decomposition Products:NONE

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH LOCAL
ENVIRONMENTAL LAWS. MATERIAL CONTAINS 10-12% PETROLEUM DISTILLATE
(DIESEL FUEL NO. 2) PER UNIT WEIGHT.

Disclaimer (provided with
this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.