Product ID:MIL-H-17672 D & AM 3,2075 TH QUAL 634-D 346 MSDS Date:09/12/1996 FSC:9150 NIIN:00-985-7232 MSDS Number: BSHVF === Responsible Party === Company Name: IMPERIAL OIL CO., INC. Address:ORCHARD PLACE Box:279 City:MORGANVILLE State:NJ ZIP:07751 Country:US Info Phone Num:201-591-9400 Emergency Phone Num:908-591-9400 CAGE:58563 === Contr actor Identification === Company Name: IMPERIAL OIL CO INC Address: FOOT OF ORCHARD PL Box:279 City:MORGANVILLE State:NJ ZIP:07751 Country:US Phone:732-591-9400/FAX: 732-591-8825 CAGE:58563 Company Name: NAUGHTON ENERGY CORP Address:RT 940 Box:709 **City: POCONO PINES** State:PA ZIP:18350-0709 Country:US Phone:570-646-0422 CAGE:1DL10

======= Composition/Information on Ingredients ==========

Ingred Name:MINERAL OIL, SOLVENT REVFINED HEAVY PARAFFINIC, SEVERELY HYDROTREATED/LUBE OIL BASE S TOCK CAS:64741-88-4 RTECS #:PY8040501 Fraction by Wt: 95 - 99% Other REC Limits:NONE RECOMMENDED OSHA PEL:5 MG/M3 (OIL MIST) ACGIH TLV:5 MG/M3 (OIL MIST)

Ingred Name:PROPRIETARY ADDITIVES (LUBRIZOL CORP) Fraction by Wt: 1 - 5% Other REC Limits:NONE RECOMMENDED

LD50 LC50 Mixture:TLV FOR OIL MIST IS 5 MG/M3. Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazar ds Acute and Chronic:TARGET ORGANS:EYES, SKIN, RESPIRATORY & GI TRACTS. ACUTE- EYE:MAY CAUSE SLIGHT IRRITATION. SKIN:PROLONGED/REPEATED CONTACT MAY CAUSE IRRITATION. INHALE:MISTS MAY CAUSE IRRITATION OF UPPER RESPIRATORY TRACT. INGESTION:LOW ORDER OF ORAL TOXICITY. CHRONIC- UNKNOWN. Explanation of Carcinogenicity:NONE Effects of Overexposure:IRRITATION, NAUSEA Medical Cond Aggravated by Exposure:PERSONS WITH PRE-EXISTING SKIN DISORDERS, EYE PROBLEMS OR IMPAIRED RESPIRATORY F UNCTION MAY BE MORE SUSCEPTIBLE TO THE EFFECTS OF THIS PRODUCT.

First Aid:GET MEDICAL HELP IF SYMPTOMS PERSIST. INHALED:MOVE TO FRESH AIR. PROVIDE CPR/OXYGEN IF NEEDED. EYES:FLUSH WITH WATER FOR 15 MINUTES, HOLDING EYELIDS OPEN. SKIN:WASH WITH SOAP & WATER. ORAL:DO NOT INDU CE VOMITING. IF CONSCIOUS, RINSE MOUTH WITH WATER. SEEK IMMEDIATE MEDICAL ATTENTION. IF SPONTANEOUS VOMITING OCCURS, KEEP HEAD BEL OW HIPS.

Flash Point Method:COC Flash Point:410F,210C Extinguishing Media:WATER FOG, CARBON DIOXIDE, SAND, FOAM/DRY CHEMICAL. WATER SPRAY MAY BE USED TO KEEP FIRE EXPOSED CONTAINERS COOL. Fire Fighting Procedures:AS WITH ANY FIRE, WEAR PROTECTIVE CLOTHING AND NIOSH-APPROVED SELF-CONTAINED BREATHING APPARATUS TO AVOID INHALATION OF HAZARDOUS DECOMPOSTION PRODUCTS OR SMOKE Unusual Fire/Explosion Hazard:NONE

======

Spill Release Procedures:RECOVER FREE LIQUID IF POSSIBLE. PICK UP SPILL WITH INERT MATERIAL SUCH AS SAND, CLAY, EARTH. SHOVEL INTO CONTAINERS FOR DISPOSAL. PREVENT RUN-OFF TO ENTER WATERWAYS, SEWERS. AREA MAY BE SLIPPERY. CAR E SHOULD BE TAKEN TO AVOID FALL. Neutralizing Agent:NOT RELEVANT

Handling and Storage Precautions:STORE AWAY FROM STRONG OXIDIZERS . KEEP

OUT OF REACH OF CHILDREN. KEEP CONTAINER CLOSED. THESE OILS WILL STOP POURING AT -18 TO -30C (-0.4 TO -22F).

Other Precautions: AVOID CONTACT WITH EYES AND SKIN. WASH THOROUGHLY AFTER HANDLING. LAUNDER CLOTHING BEFORE REUSE. AVOID INHALING MISTS. DO NOT TAKE INTERNALLY. USE PRODUCT WITH CAUTION AROUND OPEN FLAMES, HEAT, SPARKS, PILOT LIGHTS AND STATIC ELECTRICITY.

Respiratory Protection:NONE NORMALLY REQUIRED. IF WORKING IN CONFINED AREAS, IF EXCESSIVE MISTING IS EXPECTED OR IF EXPOSURE MAY OR DOES EXCEED RECOMMENDED PERMISSIBLE EXPOSURE LIMITS (PEL), WEAR NIOSH-APPROVED SUPPLIED-AIR RESPIRATOR. Ventilation:ADEQUATE Protective Gloves:NITRILES, RUBBER, PVC Eye Protection:SAFETY GLASSES/CHEMICAL SPLASH GOGGLES Other Protective Equipment:EYE WASH STATION AND SAFETY SHOWER. INDUSTRIAL-TYPE WORK CLOTHING AND APRON AS REQUIRED. Work Hygienic Practices:OBSERVE GOOD INDUSTRIAL HYGI ENE PRACTICES AND RECOMMENDED PROCEDURES. WASH BEFORE EATING OR DRINKING. Supplemental Safety and Health

FORMULA CHANGED. FOR PREVIOUS FORMULATION, SEE PNI A, SAME NSN.

HCC:V6 NRC/State Lic Num:NOT RELEVANT Boiling Pt:B.P. Text:600F,316C Melt/Freeze Pt:M.P/F.P Text:0F,-18C Vapor Pres:1 @ 68F Spec Gravity:0.876 Evaporation Rate & amp; Reference: