MOBIL OIL CORP -- MOBIL DTE 15M -- 9150-01-220-9321

============ Product Identification =========================

Product ID:MOBIL DTE 15M MSDS Date:09/21/1990

FSC:9150

NIIN:01-220-9321

MSDS Number: BSRFC === Responsible Party ===

Company Name: MOBIL OIL CORP

Address:150 E 42ND ST

City:NEW YORK

State:NY

ZIP:10017-5612 Country:US

Info Phone Num:703-849-3265 OR 800-662-4525

Emergency Phone Num:212-883-4411

Preparer's Name: ENVIRO HEAL & SAFE DEPT

CAGE:1E969

=== Contractor Identification ===

Company Name: MOBIL CHEMICAL CO DIV OF MOBIL OIL CORP

Address: HWY 27

Box:250 City:EDISON State:NJ

ZIP:08818 Country:US CAGE:29430

Company Name: MOBIL CHEMICAL CO., CHEMICAL COATINGS DIV.

Address: RT 27 AND VINEYARD RD.

Box:250 City:EDISON State:NJ

ZIP:08818-0250

Country:US

Phone:609-737-4411 OR 800-424-9300

CAGE:77988

Company Name: MOBIL OIL CORP

Address:530 EAST SWEDESFORD ROAD

Box:1031

City: VALLEY FORGE

State:PA ZIP:19482 Country:US

Phone:703-849-3265

CAGE:1E969

Company Name: MOBIL OIL CORP ENVIRO

NMENTAL AFFAIRS & TOXICOLOGY Address: PENNINGTON-ROCKY HILL RD

Box:City:PENNINGTON

State:NJ ZIP:08534 Country:US CAGE:0AHK0

======= Composition/Information on Ingredients ========

Ingred Name: DISTILLATES, HYDROTREATED HEAVY PARAFFINIC

CAS:64742-54-7 RTECS #:PY8035500

Other REC Limits: NONE RECOMMENDED

OSHA PEL:300 PPM ACGIH TLV:300 PPM

Ingred Name: MINERAL OIL, PETROLEUM DISTILLATES, SOLVENT-DEWAXED HEAVY

PARAFFINIC CAS:64742-65-0 RTECS #:PY8038500

Other REC Limits: NONE RECOMMEN

DED

OSHA PEL:5 MG/M3 AS OIL MIST ACGIH TLV:5 MG/M3 AS OIL MIST

Ingred Name: MINERAL OIL, PETROLEUM DISTILLATES, HYDROTREATED LIGHT

NAPHTHENIC CAS:64742-53-6 RTECS #:PY8036000

Other REC Limits: NONE RECOMMENDED

OSHA PEL:5 MG/M3 (OIL MIST) ACGIH TLV:5 MG/M3 (OIL MIST)

Ingred Name:2-PROPENOIC ACID,2-METHYL-DODECYL ESTER,POLYMER W/METHYL

2-METHYL-2-PROPENOATE & TETRADECYL 2-METHYL-2-PROPENOATE.

CAS:68171-50-6

Fraction by Wt: 330F,>166C

Lower Limits:0.6 Upper Limits:7.0

Extinguishing Media:WA

TER/FOAM CAUSE FROTHING. USE WATER TO COOL CONTAINERS. Fire Fighting Procedures: FIREFIGHTERS MUST USE SCBA FOR FIRES IN **ENCLOSED AREAS.** Unusual Fire/Explosion Hazard:NONE ======== Accidental Release Measures ============ Spill Release Procedures: ADSORB ON FIRE RETARDANT TREATED SAWDUST, DIATOMACEOUS EARTH, ETC. SHOVELUP & DISPOSE OF @ AN APPROPRIATE WASTE DISPOSAL FACILITY.REPORT TO US COASTGUARD 800-424-8802 SPILLS THAT COULD REACH ANY WATERWAY .FOR **ACCI** DENT/ROADSPILLS CALL CHEMTREC800-424-9300 ============= Handling and Storage ========================== Handling and Storage Precautions: NONE SPECIFIED BY MANUFACTURER. Other Precautions: NONE SPECIFIED BY MANUFACTURER. ===== Exposure Controls/Personal Protection ======== Respiratory Protection: NO SPECIAL REQUIREMENTS UNDER ORDINARY CONDITIONS OF USE AND WITH ADEQUATE VENTILATION. Ventilation: NO SPECIAL REQUIREMENTS UNDER ORDINARY CONDITIONS OF USE AND WITH ADEQUA TE VENTILATION. Protective Gloves: NONE SPECIFIED BY MANUFACTURER. Eye Protection: NONE SPECIFIED BY MANUFACTURER. Other Protective Equipment: NONE SPECIFIED BY MANUFACTURER. Work Hygienic Practices: WASH HANDS THOROUGHLY AFTER HANDLING AND BEFORE EATING/SMOKING/DRINKING. Supplemental Safety and Health PRODUCT CONTAINS TWO OR MORE OF INGREDIENTS 1,2,3 WHICH ARE BASE OILS (PETROLEUM DISTILLATES) MAKING UP >90.00%. PRODUCT MAY ALSO CONTAIN THE ZINC ADDITIVE. ======= Physical/C hemical Properties ======== HCC:V6 Boiling Pt:B.P. Text:>600F,>316C Vapor Pres: