

LHB INDUSTRIES -- ECO SURE WHITE 17875 (674-170) P/N 672C870

=====

MSDS Safety Information

=====

FSC: 8010

NIIN: 01-331-6105

MSDS Date: 01/07/1993

MSDS Num: BSSMP

Product ID: ECO SURE WHITE 17875 (674-170) P/N 672C870

MFN: 02

Responsible Party

Cage: 0FTT5

Name: LHB INDUSTRIES

Address: 8833 FLEISCHER PLACE

City: ST.

LOUIS MO 63134

Info Phone Number: 314-522-3141

Emergency Phone Number: 800-424-9300 CHEMTREC/ 314-522-3141

Preparer's Name: RUDOLF OPPENHEIM

Review Ind: Y

Published: Y

=====

Preparer Co. when other than Responsible Party Co.

=====

Cage: 0FTT5

Name: LHB INDUSTRIES

Address: 8833 FLEISCHER PLACE

City: ST. LOUIS MO 63134

=====

Contractor Summary

===

=====

Cage: 0FTT5

Name: LHB INDUSTRIES

Address: 8833 FLEISCHER PLACE

City: ST. LOUIS MO 63134

Phone: 314-522-3141

=====

Item Description Information

=====

Item Manager: GSA

Item Name: ENAMEL

Unit of Issue: PT

UI Container Qty: 0

=====

Ingredients

=====

=
Cas: 1330-20-7
RTECS #: ZE2100000
Name: XYLENE (SARA III)
% Wt: <24.22
Other REC Limits: NONE SPECIFIED
OSHA PEL: NOT ESTABLISHED
ACGIH TLV: 100 PPM
EPA Rpt Qty: 1000 LBS
DOT Rpt Qty: 1000 LBS

Cas: 110-12-3
RTECS #: MP3850000
Name: METHYL ISOAMYL KETONE
% Wt: 5.69
Other REC Limits: NONE SPECIFIED
OSHA PEL: 50 PPM
ACGIH TLV: 50 PPM

Cas: 64742-95-6
RTECS #: SE7546500
Name: AROMATIC 150
% Wt: <2.85
Other REC Limits: NONE SPECIFIE
D
OSHA PEL: 5 PPM
ACGIH TLV: 5 PPM

Cas: 64742-95-6
RTECS #: SE7546500
Name: AROMATIC 100
% Wt: 5.69
Other REC Limits: NONE SPECIFIED
OSHA PEL: 50 PPM
ACGIH TLV: 50 PPM

Cas: 108-10-1
RTECS #: SA9275000
Name: METHYL ISOBUTYL KETONE (SARA III)
% Wt: <2.85
Other REC Limits: NONE SPECIFIED
OSHA PEL: 100 PPM
ACGIH TLV: 50 PPM
EPA Rpt Qty: 5000 LBS
DOT Rpt Qty: 5000 LBS

Cas: 107-87-9
RTECS #: SA7875000
Name

: METHYL PROPYL KETONE
% Wt: <2.85
Other REC Limits: NONE SPECIFIED
OSHA PEL: 200 PPM
ACGIH TLV: 200 PPM

Cas: 95-63-6
RTECS #: DC3325000
Name: 1,2,4-TRIMETHYLBENZENE (SARA III)
% Wt: <2.85
Other REC Limits: NONE SPECIFIED
OSHA PEL: 25 PPM
ACGIH TLV: 25 PPM

Cas: 71-36-3
RTECS #: EO1400000
Name: N-BUTYL ALCOHOL (SARA III)
% Wt: <2.85
Other REC Limits: NONE SPECIFIED
OSHA PEL: 50 PPM
ACGIH TLV: 100 PPM
EPA Rpt Qty: 5000 LBS
DOT
Rpt Qty: 5000 LBS

Cas: 115-10-6
RTECS #: PM4780000
Name: DIMETHYL ETHER
% Wt: 7.76
Other REC Limits: NONE SPECIFIED
OSHA PEL: NOT ESTABLISHED
ACGIH TLV: NOT ESTABLISHED

Cas: 74-98-6
RTECS #: TX2275000
Name: PROPANE
% Wt: 13.96
Other REC Limits: NONE SPECIFIED
OSHA PEL: 1000 PPM
ACGIH TLV: 1000 PPM

RTECS #: 9999999VO
Name: VOC: 65%
Other REC Limits: NONE SPECIFIED
=====

=====

Health Hazards Data

=====

Route Of Entry Inds - Inhalation: YES

Skin: YES

Ingestion: YES

Carcinogenicity Inds - NTP: NO

IARC: NO

OSHA: NO

Effects of Exposure: CONCENTRATING & INHALING CONTENTS MAY BE
HARMFUL/FATAL. REPORTS ASSOCIATE REPEATED/PROLONGED OVEREXPOSURE TO
SOLVENTS

W/PERMANENT BRAIN & NERVOUS SYSTEM DAMAGE. IN CONFINED AREAS, HIGH
CONCENTRATIONS ANESTHETIC. SKIN & RESP TRACT IRRIT. LIGHT HEADED,
ST

AGGERING, GIDDINESS, NAUSEA. HARMFUL IF SWALLOWED. SEVERE EYE IRRIT

Signs And Symptoms Of Overexposure: IRRITATION TO EYES, THROAT, AND
RESPIRATORY TRACT. MAY CAUSE HEADACHES, NAUSEA, AND VOMITING.

Medical Cond Aggravated By Exposure: RESPIRATORY AILMENTS

First Aid: FOR CONTACT WITH SKIN OR CLOTHES, WASH WITH SOAP & WATER; WASH
CLOTHES BEFORE REUSE. FOR CONTACT WITH EYES, FLUSH WITH WATER FOR 15 MINUTES
& CONTACT A PHYSICIAN/OPHTHALMOLOGIST IMMEDIATELY. IF SWALLO WED, DO NOT
IND

UCE VOMITING. GET IMMEDIATE MEDICAL AID. IF INHALED, REMOVE TO FRESH AIR
& GIVE ARTIFICIAL RESPIRATION IF NECESSARY & GET MEDICAL AID. NEVER
GIVE ANYTHING BY MOUTH TO UNCONSCIOUS PERSON

=====

Handling and Disposal

=====

Spill Release Procedures: REMOVE ALL SOURCES OF IGNITION AND VENTILATE AREA.

MOP SPILLS WITH INERT ABSORBENT. AVOID BREATHING VAPORS.

Waste Disposal Methods: DISPOSE

OF IN ACCORD W/FEDERAL, STATE, & LOCAL

REGULATIONS. DON'T PUNCTURE, INCINERATE OR STORE ABOVE 120F. EXPOSURE TO HEAT
OR PROLONGED EXPOSURE TO SUN MAY CAUSE CAN TO BURST. DISCARD EMPTY CAN IN T
RASH PICK-UP. DON'T PLACE IN HOME TRASHCOMPACTOR.

Handling And Storage Precautions: KEEP OUT OF REACH OF CHILDREN. CONTENTS UNDER
PRESSURE. DO NOT STORE WHERE TEMPERATURES MAY EXCEED 120F. AVOID BREATHING
SPRAY MIST OR VAPOR.

Other Precautions: AVOID CONTACT WITH EYES AND SKIN. USE WITH GOOD

VENTILATION.

READ ENTIRE LABEL BEFORE USING. FOLLOW ALL LABEL DIRECTIONS. INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING & INHALING OR SWALLOWING CONTENTS MAY BE HARMFUL OR FATAL.

=====

Fire and Explosion Hazard Information

=====

Flash Point Text: NR

Autoignition Temp Text: 662 F

Lower Limits: 2.2

Upper Limits: 18.0

Extinguishing Media: CARBON DIOXIDE, DRY CHEMICAL, FOAM, SAND, WATER SPRAY.

AVOID SPREADING ANY BURNING LIQUID WITH WATER SPRAY.

Fire Fighting Procedures: WATER MAY BE INEFFECTIVE, USE TO COOL FIRE EXPOSED CONTAINERS. WEAR SCBA. USE SHIELDING TO PROTECT PERSONNEL AGAINST BURSTING, RUPTURING OR VENTING OF CONTAINER

Unusual Fire/Explosion Hazard: DO NOT SPRAY NEAR OPEN FLAME. AT ELEVATED TEMPERATURE (>120F) CONTAINERS MAY VENT, RUPTURE OR BURST. AEROSOL CONTAINER; DON'T EXPOSE TO TEMPERATURES ABOVE 120F.

=====

Control Measures

=====

Respiratory Protection: NONE BELOW TLV. USE NIOSH/MSHA APPROVED MASK IF ABOVE TLV.

Ventilation: LOCAL EXHAUST: PREFERRED. MECHANICAL (GENERAL): ACCEPTABLE AT POINT OF MIST OR SPRAY RELEASE.

Protective Gloves: TO PROTECT SKIN

Eye Protection: CHEMICAL SPLASH GOGGLES

Other Protective Equipment: IMPERVIOUS CLOTHES TO PROTECT SKIN. EYE WASH STATION.

Work Hygienic Practices: USE GOOD PERSONAL HYGIENE. DO NOT EAT, DRINK, OR SMOKE WHILE USING PRODUCT.

=====

Physical/Chemical Properties

=====

HCC: V3

Vapor Pres: 70 @ 68F

Vapor Density: >1.522

Spec Gravity: 1.076 (WATER=1)

Solubility in Water: INSOLUBLE

Appearance and Odor: WHITE / PAINT

=====

Reactivity Data

=====

Stability Indicator: YES

Stability Condi

tion To Avoid: EXTREME HEAT
Hazardous Decomposition Products: CARBON MONOXIDE
Hazardous Polymerization Indicator: NO

=====

Toxicological Information

=====

=====

Ecological Information

=====

=====

MSDS Transport Information

=====

=====

=====

Regulatory Information

=====

=====

Other Information

=====

=====

Transportation Information

=====

Responsible Party Cage: 0FTT5
Trans ID NO: 126030
Product ID:
ECO SURE WHITE 17875 (674-170) P/N 672C870
MSDS Prepared Date: 01/07/1993
Review Date: 12/15/1993
MFN: 2
Multiple KIT Number: 0
Review IND: Y
Unit Of Issue: PT
Container QTY: 0

=====

Detail DOT Information

=====

DOT PSN Code: DTJ
Symbols: D
DOT Proper Shipping Name: CONSUMER COMMODITY
Hazard Class: ORM-D
Label: NONE
Non Bulk Pack: 156,306
Bulk Pack: NONE
Max Qty Pass: 30KGGROSS
Max Qty Cargo: 30

KGGROSS
Vessel Stow Req: A
=====

Detail IMO Information
=====

IMO PSN Code: AKH
IMO Proper Shipping Name: AEROSOLS/AEROSOL PRODUCT ?
IMDG Page Number: SEE 9022
UN Number: 1950
UN Hazard Class: 9?
IMO Packaging Group: -
Subsidiary Risk Label: -
EMS Number: 2-13
=====

Detail IATA Information
=====

I
ATA PSN Code: ALS
IATA UN ID Num: 1950
IATA Proper Shipping Name: AEROSOLS, FLAMMABLE
IATA PSN Modifier: (EACH NOT EXCEEDING 1 L CAPACITY)
IATA UN Class: 2.1
IATA Label: FLAMMABLE GAS
Packing Note Passenger: 203
Max Quant Pass: 75KG
Max Quant Cargo: 150KG
Packaging Note Cargo: 203
=====

Detail AFI Information
=====

AFI PSN Code: ALR
AFI Symbols: *
AFI Proper Shipping Name: AEROSOLS, FLAMMABLE, N.
O.S.
AFI PSN Modifier: (EACH NOT EXCEEDING 1L CAPACITY)
AFI Hazard Class: 2.1
AFI UN ID NUM: UN1950
Special Provisions: P4
Back Pack Reference: A6.3
=====

HAZCOM Label
=====

Product ID: ECO SURE WHITE 17875 (674-170) P/N 672C870
Cage: 0FTT5
Company Name: LHB INDUSTRIES
Street: 8833 FLEISCHER PLACE
City: ST. LOUIS MO
Zipcode: 63134
Health Emergency Phone: 800-424-9300 CHEMTREC/ 314-522-3141
Label

Required IND: Y

Date Of Label Review: 12/16/1998

Status Code: C

Label Date: 12/16/1998

Origination Code: G

Hazard And Precautions: CONCENTRATING & INHALING CONTENTS MAY BE
HARMFUL/FATAL. REPORTS ASSOCIATE REPEATED/PROLONGED OVEREXPOSURE TO
SOLVENTS

W/PERMANENT BRAIN & NERVOUS SYSTEM DAMAGE. IN CONFINED AREAS, HIGH
CONCENTRATIONS ANESTHETIC. SKIN & RESP TRACT IRRIT. LIGHT HEADED,
STAGGERING, GIDDINESS, NAUSEA. HARMFUL IF SWALLOWED. SEVERE EYE
IRRITATION TO EYES, THROAT
, AND RESPIRATORY TRACT. MAY CAUSE HEADACHES,
NAUSEA, AND VOMITING.

=====

Disclaimer (provided with this information by the compiling agencies): This
information is formulated for use by elements of the Department of Defense.
The United States of America in no manner whatsoever expressly or implied
warrants, states, or intends said information to have any application, use or
viability by or to any person or persons outside the Departme

nt of Defense

nor any person or persons contracting with any instrumentality of the United
States of America and disclaims all liability for such use. Any person
utilizing this instruction who is not a military or civilian employee of the
United States of America should seek competent professional advice to verify
and assume responsibility for the suitability of this information to their
particular situation regardless of similarity to a corresponding Department
of Defense or other
government situation.