

HENTZEN COATINGS, INC -- MIL-P-53022B, TYPE I CATALYST, PART B -- 8010-01-193-0517
===== Product Identification =====

Product ID:MIL-P-53022B, TYPE I CATALYST, PART B
MSDS Date:12/02/1993
FSC:8010
NIIN:01-193-0517
Kit Part:Y
MSDS Number: BTGJH
=== Responsible Party ===
Company Name:HENTZEN COATINGS, INC
Address:6937 W MILL ROAD
City:MILWAUKEE
State:WI
ZIP:53218
Country:US
Info Phone Num:414-353-42
00
Emergency Phone Num:414-353-4200/800-424-9300 CHEMTREC
Preparer's Name:JANE FREEMAN
CAGE:09225
=== Contractor Identification ===
Company Name:HENTZEN COATINGS INC
Address:6937 WEST MILL ROAD
Box:18749
City:MILWAUKEE
State:WI
ZIP:53218
Country:US
Phone:414-353-4200
CAGE:09225

===== Composition/Information on Ingredients =====

Ingred Name:1-METHOXY-2-PROPANOL SOLVENT
CAS:107-98-2
RTECS #:UB7700000
Fraction by Wt: 26.770%
Other REC Limits:NONE RECOMME
OSHA PEL:100 PPM;STEL 15

0 PPM
ACGIH TLV:100 PPM;STEL 150 PPM

Ingred Name:TOLUENE (SARA III)
CAS:108-88-3
RTECS #:XS5250000
Fraction by Wt: 2.608%
Other REC Limits:SKIN NOTATIO
OSHA PEL:100 PPM
ACGIH TLV:50 PM
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:BUTYL ALCOHOL SOLVENT (SARA III)
CAS:71-36-3
RTECS #:EO1400000
Fraction by Wt: 15.542%
Other REC Limits:NONE RECOMME
OSHA PEL:50 PPM (CEILING)
ACGIH TLV:50 PPM (CEILING)
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:EPOXY RESIN
Fraction by Wt: 20-30
%
Other REC Limits:NONE RECOMME

Ingred Name:METHYL ISOBUTYL KETONE SOLVENT (SARA III)
CAS:108-10-1
RTECS #:SA9275000
Fraction by Wt: 6.153%
Other REC Limits:NONE RECOMME
OSHA PEL:50 PPM; STEL 75 PPM
ACGIH TLV:50 PPM; STEL 75 PPM
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:METHYL ETHYL KETONE SOLVENT (2-BUTANONE) (SARA III)
CAS:78-93-3
RTECS #:EL6475000
Fraction by Wt: 18.407%
Other REC Limits:NONE RECOMME
OSHA PEL:200 PPM;STEL 300 PPM
ACGIH TLV:200 PPM;STEL 300 PPM
EPA Rpt Qty:5000 L

BS
DOT Rpt Qty:5000 LBS

Ingred Name:XYLENE (SARA III)
CAS:1330-20-7
RTECS #:ZE2100000
Fraction by Wt: 5.371%
Other REC Limits:NONE RECOMME
OSHA PEL:100 PPM;STEL 150 PPM
ACGIH TLV:100 PPM;STEL 150 PPM
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:VOC: 5.681 LBS/GAL; 680.754 GRAMS/LITER
RTECS #:9999999VO
Other REC Limits:NONE RECOMME

===== Hazards Identification =====

Health Hazards Acute and Chronic:INHALATION: ANESTHETIC. RESPIRATORY TRACT IRRITATION, ACUTE NERVOUS SYSTEM DEPRESSION (HEADACHE, DIZZINESS, STAGGERING, CONFUSION, COMA). SKIN OR EYE: IRRITATION. CHRONIC OVEREXPOSURE: REPEATED OR PRO LONGED OVEREXPOSURE WITH PERMANENT BRAIN & NERVOUS SYSTEM DAMAGE, LIVER, KIDNEY DAMAGE. Medical Cond Aggravated by Exposure:ASTHMA AND OTHER RESPIRATORY AILMENTS; CHEMICAL SENSITIZATION.

===== First Aid Measures =====

First Aid:INHALATION: REMOVE FROM EXPOSURE. RESTORE BREATHING. KEEP WARM AND QUIET. NOTIFY PHYSICIAN. EYES: FLUSH IMMEDIATELY WITH LARGE AMOUNTS OF RUNNING WATER FOR AT LEAST 15 MINUTES. TAKE TO A PHYSICIAN FOR MEDICAL TREATMENT. SKIN: WASH AFFECTEDAREAS WITH SOAP AND WATER. REMOVE CONTAMINATED CLOTHING. CONSULT A PHYSICIAN. INGESTION: CALL A PHYSICIAN OR POISON CONTROL CENTER IMMEDIATELY.

===== Fire Fighting Measures =====

Flash Point Method:TCC
Flash Point:21.0F,-6.1C
Autoignition Temp:Autoignition Temp Tex

t:650 F

Lower Limits:1.1

Upper Limits:36.5

Extinguishing Media:FOAM, DRY CHEMICAL, CO2

Fire Fighting Procedures:WEAR PROTECT EQUIP INCLUDING SCBA. WATER MAY BE INEFFECTIVE, USE WATER (FOG NOZZLES PREFERRED) COOL CLOSED CNTNR TO PREVENT PRESSURE BLDUP,AUTOIGNITN,EXPLOSION.

Unusual Fire/Explosion Hazard:KEEP CONTAINER TIGHTLY CLOSED. KEEP FROM HEAT/IGNIT SOURCE. CLOSED CNTNR MAY EXPLODE W/HEAT. DON'T APPLY TO HOT SRFCs. NEVER USE WELD/CUT TORCH ON/NEAR DRUM.

===== Ac

cidental Release Measures =====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION (FLAMES, HOT SURFACES, ELECTRICAL, STATIC OR FRICTIONAL SPARKS). AVOID BREATHING VAPORS. VENTILATE AREA. CONTAIN & REMOVE WITH INERT ABSORBENT AND NONSPARKING TOOLS.

===== Handling and Storage =====

Handling and Storage Precautions:DON'T STORE ABOVE 120F. STORE LARGE QUANTITIES IN BUILDINGS DESIGNED TO COMPLY WITH OSHA 1910.106. KEEP AWAY FROM SPARKS AND OPEN FLAME. DON'T INGEST.

Other Precautions:GROUND CONTAINERS WHEN POURING. AVOID LIQUID FREE FALL >FEW INCHES. USE W/VENT & RESP EQUIP. AVOID PROLONGED VAPOR BREATHING. AVOID PROLONGED/REPEATED SKIN CONTACT. EMPTIED CNTNR RETAIN HZD RESIDUE/EX PLOSIVE VAPOR. OBEY ALL HZD PRECAUTIONS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:WEAR SPRAYED IN OUTDOOR OR DURING SANDING/GRINDING:USE NIOSH MECHAN FILTER RESPRTR (RMV SOLID

PARTICLES). RESTRICTED AREA: NIOSH CHEM/MECHAN FILTER. CONFINED AREA: NIOSH AIR SUPPLIED RSPRTR/HOOD. USE NIOSH RSPRTR WHEN CUT/WELD HAZING TORCH

Ventilation:GENRL DILUTN/LOCAL EXHAUST VENT TO KEEP BELOW PEL/TLV WHILE MIXING,APPLICATION,CURING,REMOVE DECOMP FROM WELD/FLAME CUT.

Protective Gloves:REQ'D FOR PROLONGED OR REPEATED CONTACT

Eye Protection:SAFETY EYEWEAR W/SPLASH GUARDS/SIDE SHLD

Other Protective Equipment:USE PROTECTIVE SKIN CREAM WHERE CONTACT IS LIKELY. PR

EVENT PROLONGED SKIN CONTACT WITH CONTAMINATED CLOTHING.
Work Hygienic Practices:WASH CONTAMINATED CLOTHING BEFORE REUSE. WASH
HANDS BEFORE EATING OR SMOKING. SMOKE IN DESIGNATED AREAS ONLY.
Supplemental Safety and Health

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:170 TO 290F
Decomp Temp:Decomp Text:400F,204C
Vapor Pres:74.00 @68F
Vapor Density:> AIR
Spec Gravity:0.90
Viscosity:*
Evaporation Rate & Reference:FASTER THAN BUTYL ACETATE
Solub
ility in Water:NEGLIGIBLE
Appearance and Odor:CLEAR LIQUID, SOLVENT ODOR
Percent Volatiles by Volume:80.19

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZERS
Hazardous Decomposition Products:MAY PRODUCE HAZARDOUS FUMES WHEN
HEATED TO DECOMPOSITION AS IN WELDING. MAY CONTAIN CARBON MONOXIDE
& CARBON DIOXIDE.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF
IN ACCORDANCE WITH LOCAL, STATE ABOVE
120F. STORE LARGE QUANTITIES IN BUILDINGS DESIGNED TO COMPLY WITH
OSHA 1910.106. KEEP AWAY FROM SPARKS AND OPEN FLAME. EPA HAZARDOUS
WASTE NUMBER/CODE: D001, IGNITABLE. DISPOSAL METHODS:
INCINERATION.

=====

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United State

s of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.