Product ID:TRACER TECH P-149 MSDS Date:12/09/1992 FSC:6850 NIIN:00-703-7406 Kit Part:Y MSDS Number: BTHHQ === Responsible Party === Company Name: ARDROX INC Address:16961 KNOTT AVE City:LA MIRADA State:CA ZIP:90638-6015 Country:US Info Phone Num:714-739-2821 Emergency Phone Num:714-739-2821/800-424-9300 Preparer's Name: ABAYOMI I. OWEI CAGE:23373 === Contractor Identification === Company Name: BRENT AMERICA, INC. Address:16961 KNOTT AVE. Box:City:LA MIRADA State:CA ZIP:90638-6015 Country:US Phone:714-739-2821 CAGE:23373

Ingred Name:AROMATIC NAPHTHA CAS:64741-68-0 Other REC Limits:NONE RECOMMENDED

Ingred Name:FLUORANTHENE (SARA III) CAS:206-44-0 RTECS #:LL4025000 Other REC Limits:NONE RECOMMENDED EPA Rpt Qty:100 LBS DOT Rpt Qty:100 LBS

LD50 LC50 Mixture: NONE SPECIFIED BY MANUFACTURER. Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic: EYE CONTACT: MILD IRRITATION. SKIN: FREQUENT OR PROLONGED CONTACT MAY CAUSE IRRITATION/DERMATITIS.INHALATION: MAY RESULT IN IRRITATION TO THROAT AND LUNGS. INGESTION: SMALL QUANTITIES USUALLY NONFATAL. CHRONIC: LAB. ANIMALS EXPOSED TO MISTSHOWED NERVOUS SYSTEM AND LUNG NON-SP ECIFIC SYMPTOMS. Explanation of Carcinogenicity: THIS PRODUCT DOES NOT CONTAIN CHEMICALS KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER OR REPRODUCTIVE TOXICITY. Effects of Overexposure: SKIN: DRYNESS, CHAPPING AND REDDENING OF SKIN. CONTACT WITH SKIN MAY LEAD TO ABSORPTION OF HARMFUL AMOUNTS OF MATERIAL WITH SIGNS AND SYMPTOMS OF TOXICITY. INGESTION: LARGE AMOUNTS CAN CAUSE UNCONSCIO USNESS, CONVULSIONS AND MAY BE FATAL. Medical Cond Aggravated by Exposure:SKIN CONDITIONS MA **Y BE SUSCEPTIBLE**

TO THE EFFECTS PRODUCT.

First Aid:EYES: WASH EYES IMMEDIATELY WITH RUNNING WATER FOR 15 MINUTES. GET IMMEDIATE MEDICAL ATTENTION. SKIN: WASH SKIN IMMEDIATELY WITH LOTS OF SOAP AND WATER. REMOVE CONTAMINATED CLOTHES AND SHOES. GET MEDI CAL ATTENTION IF ILL EFFECT DEVELOPS. INHALATION: REMOVE VICTIM TO FRESH AIR AT ONCE. GET IMMEDIATE MEDICAL ATTENTION. INGESTION: DO NOT INDUCE VOMITING. GET MEDICAL

ATTENTION.

Flash Point Method:PMCC Flash Point:>200F,>93C Extinguishing Media:CARBON DIOXIDE, FOAM, DRY CHEMICAL. Fire Fighting Procedures:USE WATER TO KEEP FIRE-EXPOSED CONTAINERS COOL. DO NOT USE A DIRECT STREAM OF WATER. A SOLID STREAM OF WATER/FOAM CAN CAUSE FROTHING WHICH CAN BE VIOLENT. Unusual Fire/Explosion Hazard:MODERATE FIRE HAZARD WHEN EXPOSED TO HEAT OR FLAME.

====== Acc

Spill Release Procedures: MOP UP OR SOAK UP WITH NON-COMBUSTIBLE ABSORBENT INORGANIC MATERIAL. CONTAIN LARGE SPILLS BY DIKING. PREVENT RUNOFF FROM ENTERING SEWERS, STORM DRAINS, SURFACE WATER AND SOIL. PLACE CONTAMINATED ABSOR BENT IN A DOT-APPROVED CONTAINER.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

Handling and Storage Precautions: AVOID BREATHING VAPORS A ND/OR MISTS

AND GETTING PRODUCT IN THE EYES OR ON THE SKIN. KEEP CONTAINERS COOL, DRY, AND AWAY FROM SOURCES OF IGNITION.

Other Precautions:DO NOT STORE IN DIRECT SUNLIGHT, HIGH TEMPERATURE, OR BELOW FREEZING AREAS. KEEP PRODUCT CONTAINER TIGHTLY CLOSED WHEN NOT IN USE. PROTECT CONTAINERS FROM PHYSICAL DAMAGE. GROUND ALL EQUIPMENT.

Respiratory Protection:ATMOSPHERIC LEVELS SHOULD BE MAINTAINED BELOW EXP

OSURE GUIDELINES. WHEN RESPIRATORY PROTECTION IS REQUIRED FOR CERTAIN OPERATIONS, USE A NIOSH-APPROVED CANNISTER-TYPE RESPIRATOR. IN CONFINED OR POORLY VENTLATED AREAS, USED APPROVED SCBA.

Ventilation: MECHANICAL VENTILATION, IF NECESSARY. LOCAL EXPLOSION-PROOF EXHAUST VENTILATION MAY BE NECESSARY FOR SOME OPERATIONS.

Protective Gloves: IMPERMEABLE

Eye Protection: GOGGLES/FACE SHIELD

Other Protective Equipment:SAFETY SHOWERS, EYE WASHES AND PROPER FIRE EXTINGUISHING MEDIA. PROTECTI

VE CLOTHING AS NEEDED.

Work Hygienic Practices: WASH THOROUGHLY AFTER HANDLING CHEMICALS. Supplemental Safety and Health

KEY1: N-1. THIS KIT CONTAINS 1 CAN ZL-22 PENETRANT, 4 CANS OF ZC-7 CLEANER, 2 CANS OF ZP-4 DEVELOPER, 1 CAN OF ZP-9 DRY DEVELOPER, ONE 100 W BLACK LIGHT, CLEANING CLOTHES, 1 WIRE BRUSH, STEEL CARRYING CASE ALONG WITH OTHER POWER ELEMENTS. KIT IS A SELF-CONTAINED PORTABLE UNIT. NOTE: THIS ITEM HAS CHANGE FROM FSC 6635.

========= Physical/Chemical Prop

erties =================

HCC:N1 Boiling Pt:B.P. Text:>200F,>93C Vapor Pres: