

ASHLAND CHEMICAL COMPANY -- TECTYL 502C -- 8030-00-244-1298

=====
Product Identification
=====

Product ID:TECTYL 502C

MSDS Date:07/02/1992

FSC:8030

NIIN:00-244-1298

MSDS Number: BTSDZ

=== Responsible Party ===

Company Name:ASHLAND CHEMICAL COMPANY

Box:2219

City:COLUMBUS

State:OH

ZIP:43216-2219

Country:US

Info Phone Num:614-276-6143

Emergency Phone Num:614-276-6143

CAGE:34897

=== Contractor Identif

ication ===

Company Name:ASHLAND CHEMICAL CO

Box:2219

City:COLUMBUS

State:OH

ZIP:43216-2219

Country:US

Phone:614-790-3333/800-274-5263

CAGE:34897

=====
Composition/Information on Ingredients
=====

Ingred Name:ALIPHATIC PETROLEUM DISTILLATES

CAS:8052-41-3

RTECS #:WJ8925000

Fraction by Wt: 25-40%

Other REC Limits:NIOSH RECOMMENDS

OSHA PEL:500 PPM

ACGIH TLV:100 PPM; 9293

Ingred Name:SEVERLY HYDROTREATED HEAVY NAPHTHENIC DISTILLATE

CAS:64742-52-5

RTECS #:PY8035000

Fraction by Wt

: 10-15%

Other REC Limits:NONE RECOMMENDED

Ingred Name:OIL ADDITIVE

Fraction by Wt: 10-25%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:5 MG/M3

ACGIH TLV:5 MG/M3

=====
===== Hazards Identification =====

LD50 LC50 Mixture:PEL: NOT ESTABLISHED FOR PRODUCT.

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:EYES-CAN CAUSE SEVERE IRRITATION.

SKIN-PROLONGED OR REPEATED CONTACT C

AN CAUSE MODERATE IRRITATION,

DEAFITTING, DERMATITIS. BREATHING-EXCESSIVE INHALATION CAN CAUSE

NASAL & RESPIRATORY IRRITATION. SWALLOWING-CAN CAUSE

GASTROINTESTINAL IRRITATION. ASPIRATION OF MATERIAL INTO THE LUNGS

CAN CAUSE CHEMICAL PNEUMONITIS.

Explanation of Carcinogenicity:NOT CARCINOGENIC.

Effects of Overexposure:EYES-CAN CAUSE REDNESS, TEARING, BLURRED

VISION. BREATHING-EXCESSIVE INHALATION OF VAPORS CAN CAUSE

DIZZINESS, WEAKNESS, FATIGUE, NAUSEA, HEADACHE AND POSSI

BLE

UNCONSCIOUSNESS AND EVEN DEATH. SWALLOWING-CAN CAUSE NAUSEA,

VOMITING AND DIARRHEA.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

=====
===== First Aid Measures =====

First Aid:SKIN-THOROUGHLY WASH AREA WITH SOAP & WATER. REMOVE

CONTAMINATED CLOTHING. EYES-FLUSH WITH LARGE AMOUNTS OF WATER,

LIFTING UPPER & LOWER LIDS OCCASIONALLY, GET MEDICAL ATTENTION.

SWALLOWED-DO NOT INDUCE VOMITING, KEEP PERSON WARM, QUIET, &GET

T

MEDICAL ATTENTION. BREATHING-IF AFFECTED, REMOVE INDIVIDUAL TO

FRESH AIR. IF BREATHING IS HARD, ADMINISTER OXYGEN. IF STOPPED

BREATHING, GIVE CPR. SEE DOC.

=====
===== Fire Fighting Measures =====

Flash Point:>100F,>38C

Lower Limits:1.0

Extinguishing Media:REGULAR FOAM OR CARBON DIOXIDE OR DRY CHEMICAL.

Fire Fighting Procedures:WEAR SCBA W/FULL FACE PIECE OPERATED IN

PRESSURE-DEMAND OR OTHER POSITIVE PRESSURE MODE WHEN FIGHTING

FIRES.

Unusual F

ire/Explosion Hazard:VAPORS ARE HEAVIER THAN AIR & MAY TRAVEL
ALONG THE GROUND OR BE MOVED BY VENTILATION & IGNITED BY HEAT,
ETC., AT SOURCES DISTANT FROM MATERIAL HANDLING POINT.

===== Accidental Release Measures =====

Spill Release Procedures:SMALL: ABSORB LIQUID ON VERMICULITE, FLOOR
ABSORB OR OTHER ABSORBANT MATERIAL.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP AWAY FROM HEAT/SPARKS/OPEN
FLAME.

USE OR STORE ONLY WITH ADEQUATE VENTILATION. MAINTAIN AMBIENT AIR
CONCENTRATIONS BELOW PERMISSIBLE LIMITS.

Other Precautions:AVOID CONTACT WITH EYES AND PROLONGED OR REPEATED
CONTACT WITH SKIN. WEAR SAFETY GLASSES OR GOGGLES, RESISTANT
GLOVES, AND OTHER APPROPRIATE PROTECTIVE EQUIPMENT ESSENTIAL FOR
YOUR OPERATION.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF WORKPLACE EXPOSURE LIMIT OF PRODUCT OR ANY
COMPONENT IS
EXCEEDED, A NIOSH/MSHA APPROVED AIR SUPPLIED
RESPIRATOR IS ADVISED. OSHA REGULATIONS ALSO PERMIT OTHER
NIOSH/MSHA RESPIRATORS (NEGATIVE PRESS URE TYPE) UNDER SPECIFIED
CONDITIONS.

Ventilation:PROVIDE SUFFICIENT MECHANICAL (GENERAL AND/OR LOCAL
EXHAUST) VENTILATION TO MAINTAIN EXPOSURE BELOW TLV(S).

Protective Gloves:NEOPRENE, NITRILE RUBBER.

Eye Protection:CHEM SPLASH GOGGLES, SAFETY GLASSES.

Other Protective Equipment:NORMAL WORK CLOTHING COVERING ARMS AND LEGS.

Work Hygienic Pr

actices:MINIMIZE EXPOSURE THROUGH GOOD HYGIENIC
PRACTICES.

Supplemental Safety and Health

DO NOT TANSFER TO UNLABELED CONTAINER. DO NOT USE CUTTING OR WELDING
TORCH ON THIS CONTAINER (EVEN EMPTY). FOR INDUSTRIAL USE ONLY.

24-HOUR EMERGENCY NUMBER 1-800-274-5263.

===== Physical/Chemical Properties =====

HCC:F4

Boiling Pt:B.P. Text:334F,168C

Vapor Pres:2.00 MM/HG

Vapor Density:> THAN AIR

Spec Gravity:.871

Evaporation Rate & Reference:SLOWER THAN ETHER

Appearance and Odor:LIQUID.
Percent Volatiles by Volume:25-40%

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
AVOID CONTACT WITH: STRONG OXIDIZING AGENTS.
Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER.
Hazardous Decomposition Products:MAY FORM TOXIC MATERIALS: CARBON
DIOXIDE AND CARBON MONOXIDE, VARIOUS HYDROCARBONS, SULFUR
COMPOUNDS, ETC.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH ALL LOCAL, STATE
AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to ve
rify and
assume responsibility for the suitability of this information to their
particular situation.