View NSN Online: https://aerobasegroup.es/nsn/9150-01-035-5392

Product ID:SCT BUR-Z-LUBE

MSDS Date:04/21/1994

FSC:9150

NIIN:01-035-5392

MSDS Number: BTSYG === Responsible Party ===

Company Name: SOUTH COAST TERMINALS, INC

Address:7401 WALLISVILLE ROAD

City:HOUSTON

State:TX ZIP:77020 Country:US

Info Phone Num:713-672-2401 EXT 232 Emergency Phone Num:713-672-2401/

800-424-9300(CHEMTREC)

CAGE:1L506

=== Contractor Identification ===

Company Name: CHEMICAL SPECIALISTS AND DEVELOPMENT INC

Address:2210 HACKBERRY LN

Box:687

City:CONROE

State:TX ZIP:77305 Country:US

Phone: 409-756-1065

CAGE:4N760

Company Name: SOUTH COAST TERMINALS, INC

Address:7401 WALLISVILLE ROAD

Box:15535 City:HOUSTON State:TX

ZIP:77020 Country:US

Phone:713-672-2401/800-424-9300(CHEMTREC)

CAGE:1L506

======= Composition/Information on Ingredients ========

Ingred Name: LUBRICATING O

IL BASE STOCK CAS:64791-97-5 Fraction by Wt: 80 - 90% Other REC Limits:NONE RECOMMENDED OSHA PEL:5 MG/M3 (OIL MIST) ACGIH TLV:5 MG/M3 (OIL MIST)
========== Hazards Identification =============
LD50 LC50 Mixture:TLV FOR OIL MIST IS 5 MG/M3. Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:TARGET ORGANS:EYES, SKIN, RESPIRATORY AND GI TRACTS. ACUTE- MAY CAUSE EYE, SKIN AND GASTROINTE STINAL
TRACT IRRITATION. INHALATION OF HEATED MISTS OR VAPORS MAY CAUSE NOSE AND THROAT IRRITATION. CHRONI C- MAY CAUSE SKIN BURNING, REDNESS AND DERMATITIS.
Explanation of Carcinogenicity:NONE  Effects of Overexposure:EYE, SKIN, RESPIRATORY AND GASTROINTESTINAL  TRACTS IRRITATION, REDNESS AND BURNING OF EYES AND SKIN  Medical Cond Aggravated by Exposure:DUE TO ITS IRRITATING PROPERTIES,  REPEATED SKIN CONTACT MAY AGGRAVATE AN EXISTING DERMATITIS.
======================================
Aid Measures ====================================
First Aid:GET MEDICAL HELP IF SYMPTOMS PERSIST. INHALATION:REMOVE TO FRESH AIR. PROVIDE CPR/OXYGEN IF NEEDED. EYES:FLUSH WITH WATER FOR 15 MINUTES, HOLDING EYELIDS OPEN. SKIN:WASH WITH SOAP & WATER. INGESTION:D O NOT INDUCE VOMITING. GET IMMEDIATE MEDICAL ATTENTION.
======================================
Flash Point:392F,200C MIN. Extinguishing Media:USE WATER FOG, CARBON DIOXIDE, FOAM, SAND, EARTH, OR DRY CHE MICAL. WATER OR FOAM MAY CAUSE FROTHING.
Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A FULL FACED SELF CONTAINED BREATHING APPARATUS. COOL FIRE EXPOSED CONTAINERS WITH WATER SPRAY.

Unusual Fire/Explosion Hazard: TOXIC FUMES, GASES OR VAPORS MAY EVOLVE ON BURNING. CONTAINER MAY RUPTURE ON HEATING.

======== Accidental Release Measures ===========

Spill Release Procedures:WEAR PROTECTIVE EQUIPMENTS. REMOVE SOURCES OF **IGNITION. VENTILATE A** 

REA. CONTAIN SPILL. ABSORB ON FIRE RETARDANT TREATED SAWDUST, DIATOMACEOUS EARTH, ETC. SHOVEL UP AND TRANSFER TO A CONTAINER FOR DISP OSAL. PREVENT ENTRY INTO SEWERS AND WATERWAYS. Neutralizing Agent:NOT RELEVANT ============= Handling and Storage ========================== Handling and Storage Precautions: STORE IN COOL PLACE. KEEP AWAY FROM FLAME AND STRONG OXIDIZING AGENTS. KEEP CONTAINER CLOSED. Other Precautions: DO NOT GET IN EYES, ON SKIN OR ON CLOTHING. WASH THOROUG HLY AFTER HANDLING. ====== Exposure Controls/Personal Protection ======== Respiratory Protection: NON REQUIRED UNDER NORMAL CONDITIONS. IF HIGH VAPOR OR MIST CONCENTRATIONS EXPECTED, USE NIOSH-APPROVED RESPIRATOR FOR ORGANIC VAPORS AND MISTS. Ventilation: ADEQUATE Protective Gloves:LATEX, RUBBER RECOMMENDED Eye Protection: SAFETY GOGGLES OR SPLASH GOGGLES Other Protective Equipment: EYE WASH STATION AND SAFETY SHOWER. INDUSTRIAL-TYPE WORK CLOTHING AND APRON AS REQUIRED. W ork Hygienic Practices: OBSERVE GOOD PERSONAL HYGIENE PRACTICES AND RECOMMENDED PROCEDURES. DO NOT WEAR CONTAMINATED CLOTHING OR FOOTWEAR. Supplemental Safety and Health ======== Physical/Chemical Properties =============== HCC:T6 NRC/State Lic Num:NOT RELEVANT

NRC/State Lic Num:NOT RELEVANT Boiling Pt:B.P. Text:>500F,>260C Vapor Pres:1 Spec Gravity:0.87 - 0.88

Evaporation Rate & Deference: