

MSDS Safety Information

FSC: 8040
NIIN: 00-291-8625
MSDS Date: 10/30/1991
MSDS Num: BTTGQ
Product ID: LA 2889
MFN: 01
Responsible Party
Cage: 79833
Name: CLIFTON ADHESIVE INC
Address: BURGESS PL
Box: 282
City: WAYNE NJ 07474-0282
Info Phone Number: 201-694-0845
Emergency Phone Number: 201-694-0845/800-424-9300(CHEMTREC)
Proprietary Ind: Y
Review Ind: Y
Published: Y

Contractor Summary

Cage: 79833
Name: CLIFTON ADHESIVE INC
Address: BURGESS PL
City: WAYNE NJ 07470
Phone: 201-694-0845; 973-694-0845
Cage: 33150
Name: STEVEN INDUSTRIES
Address: 39 AVENUE C
Box: 8
City: BAYONNE NJ 07002-3417
Phone: 201-437-6501

Item Description Information

Item Manager: GSA
Item Name: ADHESIVE
Specification Number: A-A-863
Type/Grade/Class: UNKNOWN
Unit of Issue: JR
Quantitative Expression: 00000000004OZ
UI Container Qty: S
Type of Container: JAR

Ingredients

Name: *** PROPRIETARY ***

Health

Hazards Data

LD50 LC50 Mixture: UNKNOWN

Route Of Entry Inds - Inhalation: YES

Skin: YES

Ingestion: YES

Carcinogenicity Inds - NTP: NO

IARC: NO

OSHA: NO

Effects of Exposure: ACUTE:NAUSEA &/OR NARCOSIS. CHRONIC:MAY CAUSE ITCHING REDNESS, RASHES. TARGET ORGANS:ETHANOL 190 MAY CAUSE LIVER, NERVUS SYSTEM OR BLOOD CELL DAMAGE.

Explanation Of Carcinogenicity: PER MSDS CARCINOGENCICITY:NO.

Signs And Symptions Of Overexposure: IRRIT TO EYES

AND MUCOUS MEMBRANES. DRY

AND CRACKED SKIN. LIQUID INGESTION MAY RESULT IN VOMITING.

Medical Cond Aggravated By Exposure: RESPIRATORY AILMENTS.

First Aid: IN EMERGENCY SITUATIONS NOTIFY A PHYSICIAN IMMED. SKIN:WASH W/SOAP

& WATER. EYE:FLUSH ABUNDANTLY W/CLEAN WATER. INGEST:DO NOT INDUCE VOMIT.

INHAL:REMOVE TO FRESH AIR OR GIVE OXYGEN. USE CPR IF PATIENT IS NOT

BREATHING. IN ALL CASES REFER TO PHSYCIAN.

Handling and Disposal

Spill Release Procedures: ABSORB SPILL IN SAND, EARTH, VERMICULITE, OIL-DRI, OR SOL-SPEED-DRI. SHOVEL ABSORBED MATERIAL INTO STEEL CONTAINER AND COVER. IN CASE OF SPILL OR LEAK INVOLVING MATL CALL 800-424-9300(CHEMTREC) 24 HRS /DAY.

Neutralizing Agent: NOT RELEVANT.

Waste Disposal Methods: DISPOSE IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL CHEMICAL AND SOLVENT WASTE DISPOSAL REGULATIONS.

Handling And Storage Precautions: KEEP CONTAINERS

TIGHTLY CLOSED & STORE IN

APPROVED SOLVENT STORAGE AREA. KEEP AWAY FROM OPEN FLAME, HEAT, SPARKS, HOT SURFACES, & OXIDIZING AGENTS.

Other Precautions: N/A.

Fire and Explosion Hazard Information

Flash Point Method: TCC

Flash Point Text: <0F,<-18C(HEXAN)

Autoignition Temp Text: 480F

Lower Limits: 0.9

Upper Limits: 19.0

Extinguishing Media: CARBON DIOXIDE, FOAM, AND DR

Y CHEMICAL.

Fire Fighting Procedures: NIOSH/MSHA APPROVED SELF-CONTAINED BREATHING APPARATUS SHOULD BE WORN.USE WATER SPRAY TO COOL FIRE-EXPOSED SRUCTURES & DISPERSE VAPOR CLOUD IF FIRE ISN'T PRESEN
Unusual Fire/Explosion Hazard: VAPOR IS HEAVIER THAN AIR & MAY TRAVEL CONSIDERABLE DISTANCE TO A SOURCE OF IGNITION AND FLASHBACK.

Control Measures

Respiratory Protection: US
E NIOSH-APPROVED ATMOSPHER SUPPLYING OR AIR PURIFYING RESPIRATOR FOR ORGANIC VAPORS AS REQUIRED TO MAINTAIN EXPOSURE LEVELS BELOW RECOMMENDED LIMITS.
Ventilation: LOCAL EXHAU:REMOVE VAPORS DURING PROCESSING. MECH EXHAU:EXPLOSION-PROOF EQPMT. SPECIAL:REDUCE VAPOR CONCEN BELOW LIMITS.
Protective Gloves: PVA GLOVES.
Eye Protection: SAFETY GLASSES.
Other Protective Equipment: PROTECTIVE CLOTHING AS REQUIRED TO PREVENT SKIN CONTACT.
Work Hygienic Practices: KEEP AREA CLEAN. CLEAN UP SPILLS IM
MED. PRACTICE GOOD
PERSONAL HYGIENE.
Supplemental Safety and Health: BOILING & FLASHING PTS FOR HEXANE. AUTOIGNI
TEMP FOR VM&P NAPHTHA.

Physical/Chemical Properties

HCC: F2
B.P. Text: 149F,65C
Vapor Pres: 117 @20C
Vapor Density: 3.0
Spec Gravity: 0.703
Appearance and Odor: SLIGHTLY HAZY, CHARCTERISTIC ODOR.

Reactivity

Data
Stability Indicator: YES
Stability Condition To Avoid: AVOID HEAT, OPEN FLAMES, SPARKS, HOT SURFACES.
Materials To Avoid: OXIDIZING AGENTS.
Hazardous Decomposition Products: OXIDES OF CARBON.
Hazardous Polymerization Indicator: NO
Conditions To Avoid Polymerization: NOT RELEVANT.

Toxicological Information

=====

Ecological Information

=====

=====

MSDS Transport Information

=====

=====

Regulatory Information

=====

=====

Other Information

=====

=====

=====

Transportation Information

=====

Responsible Party Cage: 79833
Trans ID NO: 68032
Product ID: LA 2889
MSDS Prepared Date: 10/30/1991
Review Date: 08/16/1994
MFN: 1
Tech Entry NOS Shipping Nm: ADHESIVE, FLAMMABLE LIQUID.
Multiple KIT Number: 0
Review IND: Y
Unit Of Issue: JR
Container QTY: S
Type Of Container: JAR
Additional Data: PER MSDS TRANSP INFO: DOT/IMDG/IATA
:ADHESIVE, UN 1133, FLAMM
LIQ.

=====

Detail DOT Information

=====

DOT PSN Code: AFR
DOT Proper Shipping Name: ADHESIVES,
DOT PSN Modifier: CONTAINING A FLAMMABLE LIQUID
Hazard Class: 3
UN ID Num: UN1133
DOT Packaging Group: II
Label: FLAMMABLE LIQUID
Special Provision: B52,T,T30
Packaging Exception: 150
Non Bulk Pack: 173
Bulk Pack: 242
Max Qty Pass: 5 L
Max Qty Cargo: 60 L
Vessel Stow Req: B
=

=====

Detail IMO Information

=====

IMO PSN Code: XXX

=====

Detail IATA Information

=====

IATA PSN Code: AKY

IATA UN ID Num: 1133

IATA Proper Shipping Name: ADHESIVES

IATA PSN Modifier: ,CONTAINING FLAMMABLE LIQUID

IATA UN Class: 3

IATA Label: FLAMMABLE LIQUID

UN Packing Group: II

Packing Note Passe

nger: 305

Max Quant Pass: 5L

Max Quant Cargo: 60L

Packaging Note Cargo: 307

Exceptions: A7

=====

Detail AFI Information

=====

AFI PSN Code: AKY

AFI Proper Shipping Name: ADHESIVES

AFI PSN Modifier: ,CONTAINING FLAMMABLE LIQUID

AFI Hazard Class: 3

AFI UN ID NUM: UN1133

AFI Packing Group: II

Special Provisions: P5

Back Pack Reference: A7.3

=====

HAZ

COM Label

=====

Product ID: LA 2889

Cage: 79833

Company Name: CLIFTON ADHESIVE INC

Street: BURGESS PL

City: WAYNE NJ

Zipcode: 07470

Health Emergency Phone: 201-694-0845/800-424-9300(CHEMTREC)

Label Required IND: Y

Date Of Label Review: 08/16/1994

Status Code: C

Label Date: 08/16/1994

Origination Code: F

Eye Protection IND: YES

Skin Protection IND: YES

Signal Word: DANGER

Respiratory Protection IND: YES

Health Hazard: Moderate

Contact Hazard: Sli

ght
Fire Hazard: Severe
Reactivity Hazard: None
Hazard And Precautions: ACUTE:NAUSEA &/OR NARCOSIS. CHRONIC:MAY CAUSE
ITCHING REDNESS, RASHES. TARGET ORGANS:ETHANOL 190 MAY CAUSE LIVER, NERVUS
SYSTEM OR BLOOD CELL DAMAGE. FIRST AID: IN EMERGENCY SITUATIONS NOTIFY A
PHYSIC IAN IMMED. SKIN:WASH W/SOAP & WATER. EYE:FLUSH ABUNDANTLY W/CLEAN
WATER. INGEST:DO NOT INDUCE VOMIT. INHAL:REMOVE TO FRESH AIR OR GIVE OXYGEN.
USE CPR IF PATIENT IS NOT BREATHING. IN ALL CASES REFER T O PHSYCI
AN.
SPILL:ABSORB IN SAND, EATRH, VERMICULITE, OIL-DRI, SOL-SPEED-DRI. SHOVEL INTO
STEEL CONTAINER & COVER. DISPOSAL:IN ACCORDANCE W/ FED/STATE/LOCAL
CHEMICAL & SOLVENT WSTE DISOSAL REGS.

=====
Disclaimer (provided with this information by the compiling agencies): This
information is formulated for use by elements of the Department of Defense.
The United States of America in no manner whatsoever expressly or implied
warrants, s
tates, or intends said information to have any application, use or
viability by or to any person or persons outside the Department of Defense
nor any person or persons contracting with any instrumentality of the United
States of America and disclaims all liability for such use. Any person
utilizing this instruction who is not a military or civilian employee of the
United States of America should seek competent professional advice to verify
and assume responsibility for the suitabilit
y of this information to their
particular situation regardless of similarity to a corresponding Department
of Defense or other government situation.