

FLAMEMASTER CORP THE CHEM SEAL DIV -- E-400 (TSC) TOP COAT SEALER, PE-400. --
8030-01-067-7586

===== Product Identification =====

Product ID:E-400 (TSC) TOP COAT SEALER, PE-400.

MSDS Date:06/25/1992

FSC:8030

NIIN:01-067-7586

Kit Part:Y

MSDS Number: BTTKF

=== Responsible Party ===

Company Name:FLAMEMASTER CORP THE CHEM SEAL DIV

Address:11120 SHERMAN WAY

City:SUN VALLEY

State:CA

ZIP:91352-4949

Count

ry:US

Info Phone Num:818-982-1650 FAX 818-765-5603

Emergency Phone Num:818-982-1650

Preparer's Name:HERBERT MOORE

CAGE:14439

=== Contractor Identification ===

Company Name:FLAMEMASTER CORP THE CHEM SEAL DIV

Address:11120 SHERMAN WAY

Box:City:SUN VALLEY

State:CA

ZIP:91352-4949

Country:US

Phone:818-982-1650

CAGE:14439

===== Composition/Information on Ingredients =====

Ingred Name:BISPHENOL A DIGLYCIDYL ETHER POLYMER (PER MSDS CAS#
25068-38-6).

Fraction by Wt: 21-22%

Other R

EC Limits:NONE RECOMMENDED

Ingred Name:CALCIUM CARBONATE (MARBLE) (LIMESTONE)

CAS:1317-65-3

RTECS #:EV9580000

Fraction by Wt: 15-18%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:15 MG/M3 TDUST

ACGIH TLV:10 MG/M3 TDUST; 9394

Ingred Name:ALIPHATIC POLYAMIDOAMIDE (PER MSDS CAS# 68410-23-1).

Fraction by Wt: 10-12%

Other REC Limits:NONE RECOMMENDED

Ingred Name:DIATOMITE (PER MSDS CAS# 61790-53-2).

Fraction by Wt: 0-10%

Other REC Limits:NONE RECOMMENDED

Ingred Name:TITANIUM DIOXIDE

CAS:13463-67-7

RT

ECS #:XR2275000

Fraction by Wt: 7-9%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:15 MG/M3 TDUST

ACGIH TLV:10 MG/M3 TDUST; 9394

Ingred Name:PROPYLENE GLYCOL MONOMETHYL ETHER

CAS:107-98-2

RTECS #:UB7700000

Fraction by Wt: 6-7%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:100 PPM

ACGIH TLV:100 PPM/150STEL;9394

Ingred Name:2-BUTOXYETHANOL (SARA III)

CAS:111-76-2

RTECS #:KJ8575000

Fraction by Wt: 9-10%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:S, 50 PPM

ACGIH TLV:S, 25 PPM; 9394

Ingred Name:ISOPRO

PYL ALCOHOL (SARA III)
CAS:67-63-0
RTECS #:NT8050000
Fraction by Wt: 4-5%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:400 PPM
ACGIH TLV:400 PPM/500STEL;9394

Ingred Name:N-BUTYL ALCOHOL (SARA III)
CAS:71-36-3
RTECS #:EO1400000
Fraction by Wt: 4-5%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:100 PPM
ACGIH TLV:S, C 50 PPM; 9394
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:PROPRIETARY COMMERCIAL SOLVENT BLEND
Fraction by Wt: 9-10%
Other REC Limits:NONE RECOMMENDED

=====
Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:SENSITIZER-MAY CAUSE ALLERGIC SKIN
REACTION WHICH CAN BE SEVERE IN CERTAIN INDIVIDUALS.
Effects of Overexposure:ALLERGIC SKIN REACTION.
Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MFG.

===== First Aid Measures =====

First Aid:SKIN:PROMPTLY WASH W/MILD SOAP
& WATER. EYE:IMMED FLUSH EYES
W/WATER FOR @ LEAST 15MINS. CONSULT A PHYSICIAN.

===== Fire Fighting Measures =====

Flash Point Method:TCC
Flash Point:60.0F,15.6C
Lower Limits:0.9
Upper Limits:15.8
Extinguishing Media:CARBON DIOXIDE, FOAM, DRY CHEMICAL, WATER SPRAY.
Fire Fighting Procedures:USE SELF-CONTAINED BREATHING APPARATUS.
Unusual Fire/Explosion Hazard:DECOMPOSITIN AND COMBUSTIN PRODUCTS MAY
BE TOXIC.

===== Accidental Release Measur

es =====

Spill Release Procedures:REMOVE ALL SOURCES OF HEAT AND OPEN FLAME.
DIKE SPILL. ABSORB W/INERT MATERIAL. SHOVEL INTO A CLOSABLE
CONTAINER FOR DISPOSAL.

Neutralizing Agent:NOT APPLICABLE.

===== Handling and Storage =====

Handling and Storage Precautions:FLAMMABLE LIQUID. STORE IN COOL DRY
PLACE AWAY FROM HEAT AND OPEN FLAME.

Other Precautions:WASH THOROUGHLY AFATER HANDLING AND BEFORE EATING,
DRINKING, OR SMOKING.

=====

===== Exposure Controls/Personal Protection =====

Respiratory Protection:PAPROV/CCRFOV.

Ventilation:GOOD MECHANICAL VENTILATION WITH LOCAL EXHAUST.

Protective Gloves:NEOPRENE.

Eye Protection:CHEMICAL SPLASH GOGGLES.

Other Protective Equipment:SKIN CREAMS.

Work Hygienic Practices:PRACTICE GOOD HYDGIENE PROCEDURES.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:F2

Boiling Pt:B.P. Text:231F,111C

Melt/Freeze Pt:M.P/F.P Text:-65

F,-54C

Vapor Pres:13.72

Vapor Density:3.64

Spec Gravity:1.2

Viscosity:70KU

Evaporation Rate & Reference:0.93 BUAC=1

Solubility in Water:INSOLUBLE.

Appearance and Odor:CLEAR, WHITE,GREY LIQUIDS, SWEETLY AROMATIC

Percent Volatiles by Volume:70

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS.

Stability Condition to Avoid:NONE KNOWN.

Hazardous Decomposition Products:CARBON MONOXIDE, CARBON DIOXIDE,
ALDE

HYDES AND NITROGEN.

Conditions to Avoid Polymerization:BLEND OF A & B COMPONENTS WILL
SLOWLY POLYMERIZE.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE IN ACCORDANCE WITH LOCAL, STATE AND
FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or impl

ied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.