

CRC CHEMICALS U.S.A./CRC INDUSTRIES, INC. -- 03030, EXTREME DUTY SILICONE AEROSOL --
6850-01-265-3115

===== Product Identification =====

Product ID:03030, EXTREME DUTY SILICONE AEROSOL

MSDS Date:11/12/1992

FSC:6850

NIIN:01-265-3115

MSDS Number: BTTKZ

=== Responsible Party ===

Company Name:CRC CHEMICALS U.S.A./CRC INDUSTRIES, INC.

Address:885 LOUIS DRIVE

City:WARMINSTER

State:PA

ZIP:18974-2820

Country:US

Info Phone Num:215-674-4300

Emergency Phone Num:215-674

-4300

Preparer's Name:JON BROWN

CAGE:10136

=== Contractor Identification ===

Company Name:CRC INDUSTRIES, INC.

Address:885 LOUIS DRIVE

Box:City:WARMINSTER

State:PA

ZIP:18974-2820

Country:US

Phone:215-674-4300/800-424-9300

CAGE:10136

Company Name:GENERAL TOOL & SUPPLY CO.

Address:5614 7TH AVENUE SOUTH

Box:80904

City:SEATTLE

State:WA

ZIP:98108-3317

Country:US

Phone:206-762-1500

CAGE:3Z323

Company Name:NETEX INDUSTRIES(FORMER NORTHEAST TEXAS IND)

Address:1700 NORTH EDWARDS STREET

Box:City:MOUNT PLE

ASANT
State:TX
ZIP:75455
Country:US
Phone:903-577-0388
CAGE:0WAG0
Company Name:PIONEER VALVE AND FITTING CO INC
Address:93 SEIGAL ST
Box:City:BROOKLYN
State:NY
ZIP:11206-3204
Country:US
Phone:718-387-4724
CAGE:66200
Company Name:SAN DIEGO MARINE HARDWARE INC
Address:1660 LOGAN AVENUE
Box:City:SAN DIEGO
State:CA
ZIP:92113
Country:US
Phone:619-231-8334
CAGE:7F580

===== Composition/Information on Ingredients =====

Ingred Name:SILICONE FLUID (PER MSDS CAS# 58957-05-1).
Fraction by Wt: 2-5%
Other REC Limits:NONE RECOMMENDED

Ingred Name:ISOHEXANE
CAS:107-83-5
RTECS #:SA2995000
Fraction by Wt: 55-65%
Other REC Limits:NONE RECOMMENDED

Ingred Name:HEXANE (N-HEXANE)
CAS:110-54-3
RTECS #:MN9275000
Fraction by Wt: 5-10%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:500 PPM
ACGIH TLV:50 PPM; 9394
EPA Rpt Qty:1 LB
DOT Rpt Qty:1 LB

Ingred Name:PROPANE
CAS:74-98-6
RTECS #:TX2275000
Fraction by Wt: 10-20%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:1000 PPM
ACGIH TLV:ASPHYXIAN; 9394

Ingred Name:ISOBUTANE
CAS:75-28-5
RTECS #:TZ4300000
Fraction by Wt: 10-20%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:1000 PPM
ACGIH TLV:1000 PPM

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE:EYE:BURNING & IRRIT. SKIN:MILD
IRRIT. INHAL:IRRIT OF RESP TRACT. CHRONIC:REPEATED OVEREXPOSRES MAY
CAUSE HARM TO NERVOUS SYST
EM.
Explanation of Carcinogenicity:PER MSDS NO CHEM LISTED AS CARCINOGEN OR
POTENTIAL CARCINOGE IN NTP/IARC/OSHA LISTINGS.
Effects of Overexposure:DIZZINESS, HEADACHES, CENTRAL NERVOUS SYSTEM
DEPRESSION.
Medical Cond Aggravated by Exposure:PRE-EXISTING LUNG DISORDERS.

===== First Aid Measures =====

First Aid:IF SYMPTOMS PERSIST CALL DOCTOR. INHAL: REMOVE TO FRESH AIR.
APPLY ARTI RESP IF NECESSARY. EYE:FLUSH W/LG AMTS OF WATER FOR
15MINS. SK
IN:WASH W/SOAP & WATER. REMOVE CONTAMINATED CLOTHING.
INGEST:DO NO T INDUCE VOMITING. CALL PHYSICIAN.

===== Fire Fighting Measures =====

Flash Point Method:TCC
Flash Point: