

DEL PAINT MFG CORP -- 86904 MIL-L-81352 LACQUER (P/N 37886) -- 8010-01-303-0236

=====  
Product Identification  
=====

Product ID:86904 MIL-L-81352 LACQUER (P/N 37886)

MSDS Date:12/03/1992

FSC:8010

NIIN:01-303-0236

MSDS Number: BTTLW

=== Responsible Party ===

Company Name:DEL PAINT MFG CORP

Address:3105 E. RENO

City:OKLAHOMA CITY

State:OK

ZIP:73117-6699

Country:US

Info Phone Num:405-672-1431

Emergency

Phone Num:800-866-6823, CHEMTREC 800-424-9300

CAGE:EO310

=== Contractor Identification ===

Company Name:DEL PAINT MFG

Address:3105 EAST RENO

Box:City:OKLAHOMA CITY

State:OK

ZIP:73117

Country:US

Phone:405-672-1431

CAGE:39934

Company Name:DEL PAINT MFG CORP

Address:3105 E RENO AVE

City:OKLAHOMA CITY

State:OK

ZIP:73117-6699

Country:US

Phone:405-672-1431

CAGE:EO310

=====  
Composition/Information on Ingredients  
=====

Ingred Name:TOLUENE (SARA III)

CAS:108-88-3

RTECS #:XS5250000

Fr

action by Wt: 44.05%  
Other REC Limits:200 PPM  
OSHA PEL:200 PPM/150 STEL  
ACGIH TLV:50 PPM; 9293  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

Ingred Name:N-BUTYL ALCOHOL, 1-BUTANOL (VAPOR PRESSURE 4.4 MM HG @ 20  
C)

CAS:71-36-3  
RTECS #:EO1400000  
Fraction by Wt: 2.86%  
Other REC Limits:100 PPM  
OSHA PEL:100 PPM  
ACGIH TLV:S, C 50 PPM; 9293  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

Ingred Name:PMGE ACETATE  
CAS:108-65-6  
RTECS #:AI8295000  
Fraction by Wt: 7.67%  
Other REC Limits:NONE SPECIFIED

=====  
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:ACUTE-EYES/SKIN:IRRITATION.  
INHALATION:IRRITATION TO THE RESPIRATORY TRACT.  
INGESTION:INTESTINAL IRRITATION, ASPIRATION INTO LUNGS MAY CAUSE  
CHEMICAL PNEUMONITIS WHICH CAN BE FATAL. CHRONIC-DERMATITS, LIVER  
AND KIDNEY DAMAGE. TARGET ORGANS: CNS, LIVER AND REPRODUCTIVE  
SYSTEM.

Effects of Overexposure:INHALATION:IRRITATION, HEADACHE, DIZZINESS,  
INTOXICATION. SKIN:REDNESS, DRYNESS. EYE:REDNESS AND PAIN.  
INHALATION: LABORED BREATHING, DULLNESS AND DROWSINESS. INGESTION:  
ABDOMINAL PAIN AND NAUSEA.  
Medical Cond Aggravated by Exposure:DISEASES OF THE RESPIRATORY SYSTEM.

===== First Aid Measures =====

First Aid:SKIN: REMOVE CONTAMINATED CLOTHING. SHOWER OR RINSE SKIN WITH  
PLENTY OF WATER. EYE: RINSE WITH COPIUS AMOUNTS

OF WATER, TRANSPORT

TO PHYSICIAN IF NECESSARY. INHALATION: REMOVE TO FRESH AIR. GIVE ARTIFICIAL RESPIRATION IF NECESSARY AND CONTACT A PHYSICIAN.

INGESTION: RINSE MOUTH AND DRINK PLENTY OF WATER. DO NOT INDUCE VOMITING. SEEK MEDICAL ASSISTANCE.

===== Fire Fighting Measures =====

Flash Point Method:TCC

Flash Point:45.0F,7.2C

Lower Limits:1.2

Extinguishing Media:FOAM, ALCOHOL FOAM, CO2, DRY CHEMICAL.

Fire Fighting Procedures:SELF-CONTAINED BREATHING

THING APPARATUS WITH A FULL

FACEPIECE OPERATED IN PRESSURE-DEMAND OR OTHER POSITIVE MODE.

Unusual Fire/Explosion Hazard:VAPORS ARE HEAVIER THAN AIR, MAY SETTLE AT LOW AREAS OR TRAVEL SOME DISTANCE ALONG THE GROUND TO IGNITION SOURCES WHERE THEY MAY IGNITE & FLASH BACK.

===== Accidental Release Measures =====

Spill Release Procedures:WEAR PROTECTIVE EQUIPMENT, ABSORB LIQUID ON VERMICULITE, OR OTHER ABSORBENT MATERIAL AND TRANSFER TO HOOD OR DISPOSAL CONTAINERS.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN A CLEAN DRY AREA. KEEP AWAY FROM FOOD, SPARKS, FIRES AND REMOTE IGNITION SOURCES.

Other Precautions:EMPTY CONTAINERS RETAIN RESIDUE. DO NOT PRESSURIZE, CUT, WELD OR EXPOSE TO HEAT, FLAME, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION; THEY MAY EXPLODE AND CAUSE INJURY.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:

IF TLV OF PRODUCT/ANY COMPONENT IS EXCEEDED, A NIOSH/MSHA JOINTLY APPROVED AIR SUPPLIED RESPIRATOR IS ADVISED IN ABSENCE OF PROPER ENVIRONMENTAL CONTROL. OSHA REGULATIONS ALSO PERMIT OTHER NIOSH/MSHA RESPIRATOR UNDER SPECIFIED CONDITIONS.

Ventilation:GENERAL OR LOCAL VENTILATION TO MAINTAIN EXPOSURE BELOW TLV'S.

Protective Gloves:RESISTANT GLOVES: BUNA-N

Eye Protection:SPLASH GOGGLES OR SAFETY GLASSES.

Other Protective Equipment:WEAR IMPERVIOUS CLOTHING AND BOOTS.

Work H

Hygienic Practices: WASH HANDS AND FACE BEFORE EATING.  
Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:F2

Boiling Pt: B.P. Text: 230F, 110C

Vapor Density: >AIR

Spec Gravity: 9.27 WT/GAL

Evaporation Rate & Reference: