

FARSTAD OIL INC. -- NO.2 DIESEL FUEL/FURNACE OIL/FURNACE OIL LP/NO.2 FUEL OIL --
9140-00-000-0184

=====
===== Product Identification =====

Product ID:NO.2 DIESEL FUEL/FURNACE OIL/FURNACE OIL LP/NO.2 FUEL OIL

MSDS Date:05/29/1987

FSC:9140

NIIN:00-000-0184

MSDS Number: BTTQZ

=== Responsible Party ===

Company Name:FARSTAD OIL INC.

Address:COUNTY RD 19N

Box:1842

City:MINOT

State:ND

ZIP:58702

Country:US

Info

Phone Num:701-852-1194

Emergency Phone Num:701-852-1194

CAGE:JO755

=== Contractor Identification ===

Company Name:FARSTAD OIL INC

Address:COUNTY RD 19 N

Box:1842

City:MINOT

State:ND

ZIP:58701

Country:US

CAGE:3R470

Company Name:FARSTAD OIL INC.

Address:COUNTY RD 19N

Box:1842

City:MINOT

State:ND

ZIP:58702

Country:US

Phone:701-852-1194

CAGE:JO755

=====
===== Composition/Information on Ingredients =====

Ingred Name:AROMATIC & PARAFFINIC HYDROCARBONS

Other REC Limits:NONE RECOMMENDED

=====
Hazards Identification
=====

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:PRODUCT CONTAINS HYDROCARBONS WHICH
MAY CAUSE IRRITATION TO EYES, LUNGS, OR SKIN AFTER PROLONGED OR
REPEATED EXPOSURE. THIS PRODUCT MAY ALSO BE TOXIC TO THE LIVER AND
KIDNEY. EXTREME EXPOSURE OR ASPIRATION INTO LUNGS MAY CAUSE
PNEUMONIA ORCENTRAL NERVOUS SYSTEM DEPRESSION

Explanation of Carcinogenicity:NO INGREDIENTS OF A CONCENTRATION OF
0.1% OR GREATER IS LISTED AS A CARCINOGEN OR SUSPECTED CARCINOGEN.
Effects of Overexposure:INHALED: WEAKNESS, DIZZINESS, UNCONSCIOUSNESS,
CONVULSIONS, SHORTNESS OF BREATH. EYES: REDNESS, SWELLING, TEARING,
PAIN. SKIN: REDNESS, ITCHING, BURNING SENSATION OR DISCOMFORT.
SWALLOWED: NAUSEA, VOMITING, DIARRHEA.
Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

=====
First Aid Measures
=====

First Aid:EYES-FLUSH WITH LOTS OF WATER FOR 15 MINUTES. SEEK MEDICAL
ATTENTION. SKIN-REMOVE CONTAMINATED CLOTHING AS SOON AS POSSIBLE.
WASH WITH SOAP & WATER. IF IRRITATION DEVELOPS, SEE DOCTOR.
INHALED-REMOVE TO FRESH AIR. GIVE ARTIFICIAL RESPIRATION IF
BREATHING STOPPED. SEEK MEDICAL ATTENTION. INGESTED-DO NOT INDUCE
VOMITING! IF VOMITING STARTS; LOWER HEAD BELOW KNEES. GET MEDICAL
ATTENTION.

=====
Fire Fighting Measures
=====

Flash Point Method:TCC
Flash Point:130F,54C
Autoignition Temp:Autoignition Temp Text:>475F
Extinguishing Media:WATER SPRAY, DRY CHEMICAL, FOAM, OR CARBON DIOXIDE.
Fire Fighting Procedures:USE WATER TO COOL FIRE EXPOSED CONTAINERS,
DISPERSE VAPORS, PROVIDE PROTECTION TO FIRE FIGHTERS. WEAR
SELF-CONTAINED BREATHING APPARATUS & FULL BUNKER GEAR.
Unusual Fire/Explosion Hazard:PRODUCTS OF COMBUSTION MAY CONTAIN CARBON
MONOXIDE, CARBON DIOXIDE, AND OTHER TOXIC M

ATERIALS. DO NOT ENTER
ENCLOSED OR CONFINED SPACE W/O PROPER EQUIPMENT.

===== Accidental Release Measures =====

Spill Release Procedures:CONTAIN SPILL.RECOVER AS MUCH AS
POSSIBLE;FOLLOWED BY ABSORPTION ON INERT MATERIALS.PLACE ABSORBED
MATERIAL IN A CONTAINER FOR LATER DISPOSAL.KEEP OUT OF
SEWERS/WATERWAYS.IF SPILL ENTERS WATERWAY/SEWER,NOTIFY NATIONAL
RESPONSE CENTER AT 800-424-8802.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:HANDLE AND STORED IN ACCORDANCE WITH
NFPA PROCEDURES FOR CLASS II COMBUSTIBLE LIQUID.

Other Precautions:FROM HEALTH/1ST AID-NOTE TO PHYSICIANS-GASTRIC LAVAGE
BY QUALIFIED MEDICAL PERSONNEL MAY BE CONSIDERED, DEPENDING ON
QUANTITY OF MATERIAL INGESTED.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF ENGINEERING CONTROLS FAIL OR EMERGENCY
OCCU

RS; USE NIOSH/MSHA APPROVED RESPIRATOR OR SUPPLIED AIR
RESPIRATOR OR SCBA, AS REQUIRED. USE IAW MANUFACTURER'S
RECOMMENDATIONS AND 29 CFR 1910.134.

Ventilation:USE ADEQUATE MECHANICAL VENTILATION TO MAINTAIN EXPOSURE
BELOW TLV.

Protective Gloves:VINYL, NEOPRENE, NBR

Eye Protection:FACE SHIELD

Other Protective Equipment:COVERALLS OR OTHER PROTECTIVE APPAREL NEEDED
IF SPLASHING POSSIBLE.

Work Hygienic Practices:WASH HANDS AFTER SUE AND BEFORE EATING,
DRINKING, OR SMOKING. LAUNDRY
CONTAMINATED CLOTHES BEFORE REUSE.

Supplemental Safety and Health

EXTREMELY CONTAMINATED LEATHER SHOES SHOULD BE DISCARDED.

===== Physical/Chemical Properties =====

HCC:F4

Boiling Pt:B.P. Text:>350F,>177C

Vapor Pres:1 MMHG@68F

Spec Gravity:0.85-0.93

Solubility in Water:INSOLUBLE

Appearance and Odor:CLEAR OR LIGHT YELLOW LIQUID; AROMATIC ODOR

Percent Volatiles by Volume:0

===== Stability and Reactivity Data =====

Stability Indicator/Mat

erials to Avoid: YES

STRONG OXIDIZING AGENTS

Stability Condition to Avoid: AVOID EXPOSURE TO SOURCES OF IGNITION AND STRONG OXIDIZING AGENTS.

Hazardous Decomposition Products: INCOMPLETE COMBUSTION MAY PRODUCE CARBON MONOXIDE.

===== Disposal Considerations =====

Waste Disposal Methods: RECYCLE AS MUCH AS POSSIBLE. DISPOSE OF NON-RECYCLABLE MATERIAL AS A RCRA HAZARDOUS WASTE BY SUCH METHODS AS INCINERATION, COMPLYING WITH LOCAL, STATE AND FEDERAL

REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.