

EZE PRODUCTS, INC -- EZE 458 -- 6850-01-235-0873

===== Product Identification =====

Product ID:EZE 458

MSDS Date:08/21/1992

FSC:6850

NIIN:01-235-0873

MSDS Number: BTTVF

=== Responsible Party ===

Company Name:EZE PRODUCTS, INC

Address:603 HIGH TECH CT

Box:5744

City:GREER

State:SC

ZIP:29606

Country:US

Info Phone Num:803-879-7100

Emergency Phone Num:803-879-7100 OR 404-842-0430

CAGE:8Z357

=== Contractor Identification ===

Company Name:EZE PRODUCTS, INC

Address:60

3 HIGH TECH CT

Box:5744

City:GREENVILLE

State:SC

ZIP:29606

Country:US

Phone:803-242-1002 OR 803-879-7100

CAGE:8Z357

Company Name:SILVER SALES

Address:5115 DOUGLAS FIR RD SUITE C

Box:City:CALABASES

State:CA

ZIP:91302

Country:US

Phone:818-591-0788 WAS IN TX

CAGE:0WG65

===== Composition/Information on Ingredients =====

Ingred Name:PETROLEUM HYDROCARBON

CAS:64742-47-8

RTECS #:OA5504000

Fraction by Wt: 10-20%

Other REC Limits:NONE RECOMMENDED

Ingred Name:2-BUTOXYETHANOL

CAS:111

-76-2
RTECS #:KJ8575000
Fraction by Wt: 1-7%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:S, 50 PPM
ACGIH TLV:S, 25 PPM; 9394

Ingred Name:HEXYLENE GLYCOL
CAS:107-41-5
RTECS #:SA0810000
Fraction by Wt: 1-7%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:C 25 PPM
ACGIH TLV:C 25 PPM; 9394

Ingred Name:VOLATILE ORGANIC CONTENT: 266.4 GRAMS/LITER.
RTECS #:9999999VO
Other REC Limits:NONE RECOMMENDED

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin
:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE: IRRITANT; SLIGHTLY TOXIC WHEN
INHALED OR INGESTED. CAN CAUSE BURNS TO EXPOSED TISSUE. CHRONIC:
SLIGHTLY TOXIC IF INHALED OR INGESTED.
Explanation of Carcinogenicity:NO INGREDIENTS OF A CONCENTRATION OF
0.1% OR GREATER IS LISTED AS A CARCINOGEN OR SUSPECTED CARCINOGEN.
Effects of Overexposure:EYES: IRRITATION, CORNEA DAMAGE. SKIN: BURNS.
INHALED: HEADACHE, DIZZINESS, NA
USEA, IRRITATION OF UPPER
RESPIRATORY TRACT. INGESTED: NAUSEA, VOMITING, DIARRHEA.
Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

===== First Aid Measures =====

First Aid:EYES-FLUSH WITH LOTS OF WATER FOR 15 MINUTES, LIFT LIDS. GET
MEDICAL ATTENTION. SKIN-REMOVE CONTAMINATED CLOTHES. WASH WITH SOAP
& WATER. INHALED-REMOVE TO FRESH AIR. GET MEDICAL ATTENTION IF
SYMPTOMS PERSIST. INGESTED-DO NOT INDUCE VOMITING! IF CONSC

IOUS,
GIVE WATER TO DILUTE. SEEK MEDICAL ASSISTANCE. TARGET ORGANS: SKIN,
EYES, RESPIRATORY SYSTEM, CNS.

===== Fire Fighting Measures =====

Flash Point Method:TCC
Flash Point:200F,93C
Extinguishing Media:WATER FOG, CARBON DIOXIDE, DRY CHEMICAL
Fire Fighting Procedures:DO NOT ENTER CONFINED SPACE WITHOUT
SELF-CONTAINED BREATHING APPARATUS.
Unusual Fire/Explosion Hazard:COOL FIRE EXPOSED CONTAINERS. ALTHOUGH
NOT FLAMMABLE IN AQUEOUS STATE; IT WIL
L BURN IN THE PRESENCE OF A
STRONG IGNITION SOURCE, AFTER WATER REMOVED.

===== Accidental Release Measures =====

Spill Release Procedures:CONTAIN THE SPILL. ELIMINATE ANY IGNITION
SOURCE. ABSORB SMALL SPILLS WITH SAND, DIRT OR CLAY. LARGE SPILLS
MAY BE PUMPED INTO CONTAINERS FOR RECOVERY OR DISPOSAL.
Neutralizing Agent:NOT APPLICABLE.

===== Handling and Storage =====

Handling and Storage Precautions:STORE CONTAINERS I
N A COOL PLACE, BUNG
UP AND TIGHTLY CLOSED.
Other Precautions:HAVE EYE WASH STATION & SAFETY SHOWER, LAUNDRY
FACILITIES AVAILABLE.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE NORMALLY REQUIRED. USE NIOSH/MSHA APPROVED
RESPIRATOR WITH ORGANIC VAPOR CARTRIDGE IF ENGINEERING CONTROLS
FAIL OR EMERGENCY OCCURS. USE IAW 29 CFR 1910.134.
Ventilation:ADEQUATE-LOCAL EXHAUST.
Protective Gloves:RUBBER OR NEOPRENE
Eye Protection:CHEMICAL
SPLASH GOGGLES
Other Protective Equipment:EYE WASH STATION AND SAFETY SHOWER AND
LAUNDRY FACILITIES AVAILABLE. PROTECTIVE CLOTHING TO PREVENT SKIN
CONTACT.
Work Hygienic Practices:USE GOOD CHEMICAL HYGIENE PRACTICE. AVOID
UNNECESSARY CONTACT. WASH THOROUGHLY BEFORE EATING OR DRINKING.
Supplemental Safety and Health
CONTRACT NUMBER: SP0450-M-Z797.

===== Physical/Chemical Properties =====

HCC:N1
Boiling Pt:B.P. Text:212F,100C
Melt/Freeze Pt:M.P/F.P Text:6F

, -14C
Vapor Density:>1
Spec Gravity:0.98
pH:9.9
Solubility in Water:FORMS AN EMULSION
Appearance and Odor:OPAQUE VISCOUS LIQUID, SOLVENT ODOR

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZING OR REDUCING AGENTS
Stability Condition to Avoid:AVOID TEMPERATURE EXTREMES AND
INCOMPATIBLE MATERIAL.
Hazardous Decomposition Products:BURNING CAN PRODUCE OXIDES OF CARBON.

===== Disposal Considerations ====
=====

Waste Disposal Methods:DISPOSAL SHOULD BE MADE IN ACCORDANCE WITH ALL
APPLICABLE FEDERAL, STATE AND LOCAL LAWS AND REGULATIONS.
CONTAMINATED ABSORBENT MAY BE DEPOSITED IN A LANDFILL OR WASTE MAY
BE INCINERATED. NO RCRA WASTE CODE IS APPLICABLE.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.