View NSN Online: https://aerobasegroup.es/nsn/7920-00-823-9817

Product ID:PAD. METAL POLISH IMPREGNATED 5 OZ CAN MSDS Date:12/01/1991 FSC:7920 NIIN:00-823-9817 MSDS Number: BTVRG === Responsible Party === Company Name: M & M HERITAGE INC Address:817 FRANKLIN ST **City: JOHNSTOWN** State:PA ZIP:15901-5000 Country:US Info Phone Num:814-539-0396 Emergenc y Phone Num:814-539-0396 CAGE:MMHER === Contractor Identification === Company Name: M & M HERITAGE INC Address:817 FRANKLIN ST **City: JOHNSTOWN** State:PA ZIP:15901-5000 Country:US Phone:814-539-0396 CAGE:MMHER Company Name: M&M HERITAGE INC Address:611 KIMBERLY DR **City:DENTON** State:TX ZIP:76202-5000 Country:US Phone:817-898-1400 CAGE:MHERT

Ingred Name:MEDIUM ALIPHATIC NAPHTHA (AROMATIC 100), PARAFFIN-NAPTHANES MINERAL SPIRITS CAS:64742-88-7 Fraction by Wt: 56.2% Other REC Limits:350 MG/CUM OSHA PEL:100 PPM ACGIH TLV:100 PPM

Ingred Name:STODDARD SOLVENT (PETROLEUM DISTILLATE), MINERAL SPIRITS CAS:8052-41-3 RTECS #:WJ8925000 Fraction by Wt: 9.9% Other REC Limits:350 MG/CUM OSHA PEL:100 PPM ACGIH TLV:100 PPM

Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:E

YES: IRRITATION. SKIN:

PROLONGED/REPEATED CONTACT MAY CAUSE IRRITATION & DERMATITIS. INHALATION: NASAL/RESPIRATORY IRRITATION, CNS EFFECTS. INGESTION: GASTROINTESTINAL IRRITATION. ASPIRATION INTO LUN GS CAN CAUSE CHEMICAL PNEUMONITIS WHICHCAN BE FATAL.

Explanation of Carcinogenicity:NONE

Effects of Overexposure: IRRITATION, DEFATTING, DIZZINESS, WEAKNESS, FATIGUE, NAUSEA, HEADACHE, UNCONSCIOUSNESS, NARCOSIS, VOMITING, DIARRHEA.

First Aid:SKIN: THOROUGHLY WASH W/SOAP & WATER. EYES: FLUSH W/LARGE AMOUNTS OF WATER. INGESTION: DON'T INDUCE VOMITING. KEEP WARM & QUIET. ASPIRATION HAZARD. INHALATION: REMOVE TO FRESH AIR. GIVE CPR/OXYGEN IF NEEDED. KEEP WARM & QUIET. OBTAIN MEDICAL ATTENTION IN ALL CASES.

Flash Point Method:TCC Flash Point:136F Lower Limits:1 Extinguishing Media:FOAM, DRY CHEMICAL, CO2, WATER FOG Fire Fighting Procedures:WEAR SCBA W/FULL FACEPIECE OPERATED IN POSITIVE PRESSURE DEMAND MODE. AVOID SPREADING BURNING MATERIAL W/WATER USED FOR COOLING PURPOSES.

Unusual Fire/Explosion Hazard: VAPORS ARE >AIR & MAY TRAVEL ALONG GROUND/MOVED BY VENTILATION TO DISTANT SOURCES OF IGNITION.

Spill Release Procedures: ELIMINATE ALL IGNITION SOURCES. EVACUATE AREA. SOLID MATERIAL SHOULD BE SHOVELED INTO CONTAINERS. ANY REMAINING

LIQUID MAY BE TAKEN UP ON SAND, CLAY, EARTH, FLOOR ABSORBENT/OTHER ABSORBENT MATERIAL & SHOVELED INTO CONTAINERS.

======= Exposure Controls/Personal Protection ==========

Respiratory Protection:WEAR NIOSH/MSHA APPROVED AIR SUPPLIED RESPIRATOR IN ABSENCE OF PROPER ENVIRONMENTAL CONTROL IF WORKPLACE EXPOSURE LIMITS ARE EXCEEDED.

Ventilation:SUFFICIENT MECHANICAL/GENERAL/LOCAL EXHAUST TO MAINTAIN EXPOSURE