

GRYPHIN COMPANY, INC -- TT-S-711C, INTERIOR WOOD STAIN -- 8010-00-281-2075

=====  
Product Identification  
=====

Product ID:TT-S-711C, INTERIOR WOOD STAIN

MSDS Date:05/18/1994

FSC:8010

NIIN:00-281-2075

MSDS Number: BTVYB

=== Responsible Party ===

Company Name:GRYPHIN COMPANY, INC

Address:RICHMOND AND TIOGA STREETS

City:PHILADELPHIA

State:PA

ZIP:19134

Country:US

Info Phone Num:215-739-6172

Emergency P

hone Num:215-247-6280 / 800-424-9300

CAGE:0E5W3

=== Contractor Identification ===

Company Name:GRYPHIN COMPANY, INC

Box:5910

City:PHILADELPHIA

State:PA

ZIP:19119

Country:US

Phone:800-482-1886

CAGE:0E5W3

=====  
Composition/Information on Ingredients  
=====

Ingred Name:PETROLEUM SOLVENT (VAPOR PRESSURE 3.1 MM HG)

CAS:8052-41-3

RTECS #:WJ8925000

Fraction by Wt: 60%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:500 PPM

ACGIH TLV:100 PPM

Ingred Name:AMSCO 460 SOLV (VAPOR PRESSURE 0 MM

HG)  
CAS:64475-85-0  
RTECS #:PY8240000  
Fraction by Wt: 1.7%  
Other REC Limits:NONE RECOMMENDED  
ACGIH TLV:200 PPM

Ingred Name:METHANOL (SARA III) (VAPOR PRESSURE 96 MM HG)  
CAS:67-56-1  
RTECS #:PC1400000  
Fraction by Wt: 0.11%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:200 PPM  
ACGIH TLV:200 PPM  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

Ingred Name:SOLVENT G (VAPOR PRESSURE 3 MM HG)  
CAS:64742-94-5  
RTECS #:WF3100000  
Fraction by Wt: 3.8%  
Other REC Limits:NONE RECOMMENDED

Ingred Name:HI FLASH NAPHTHA  
(VAPOR PRESSURE 10 MM HG)  
CAS:64742-95-6  
Fraction by Wt: 0.082%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:100 PPM  
ACGIH TLV:25 PPM

Ingred Name:ANTI-OXIDANT (VAPOR PRESSURE 10 MM HG)  
CAS:96-29-7  
RTECS #:EL9275000  
Fraction by Wt: 0.068%  
Other REC Limits:NONE RECOMMENDED

Ingred Name:XYLENE (SARA III) (VAPOR PRESSURE 8 MM HG)  
CAS:1330-20-7  
RTECS #:ZE2100000  
Fraction by Wt: 0.28%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:100 PPM  
ACGIH TLV:100 PPM  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

Ingred

Name:VOC: 5.22 LB/GAL  
RTECS #:9999999VO  
Other REC Limits:NONE RECOMMENDED

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:INHAL: NOSE, THROAT, RESP TRACT IRRIT.  
PROLONGED:HEADACHE, NAUSEA, DIZZINESS, UNCOORDINATION.  
CONCENTRATING & INHALING MAY BE HARMFUL OR FATAL. SKIN: IRRIT.  
PROLONGED:BURNING, REDNESS, DRYING, DERMATI  
TIS. INGESTION:  
DIGESTIVE TRACT IRRIT, ENTER LUNGS CAUSING VOMITING & LUNG DAMAGE.  
EYE: IRRIT, BURING, TEARING, REDNESS.

===== First Aid Measures =====

First Aid:INHAL: REMOVE INTO FRESH AIR. CALL DR IMMED. IF BREATHING  
IRREGULAR OR HAS STOPPED, START RESUSCITATION & GIVE OXYGEN. SKIN:  
REMOVE ANY CONTAMINATED CLOTHING & WASH SKIN WITH MILD SOAP & WATER  
IMMED. CONSULT DR IF IRRITATION PERSISTS. INGEST: DO NOT INDUCE  
VOMITING. CALL  
DR & POISON CTR IMMED. EYE: FLUSH WITH CLEAR WATER  
FOR 15 MIN OR UNTIL IRRITATION SUBSIDES. IF IRRITATION PERSISTS,  
CALL DR.

===== Fire Fighting Measures =====

Flash Point Method:TCC  
Flash Point:54.0F,12.2C  
Lower Limits:0.8  
Extinguishing Media:WATER FOG, FOAM, CARBON DIOXIDE, DRY CHEMICAL  
Fire Fighting Procedures:SCBA,COMPLT PERSN PROTECT EQUIP &CLOTH.AVOID  
SPREAD BURN LIQ W/H2O.FIGHT FIRE FROM DISTANCE.CLS VALVE TO  
AREA.SHUT OFF POWER.TURN ON  
EMERG LIGHT.COOL CTNR W/H2O  
Unusual Fire/Explosion Hazard:VAPOR/DUST MAY FORM EXPLOS MIX  
W/AIR.VAPOR>AIR,MAY TRAVEL,IGNIT/FLASHBACK.CLSD CNTNR EXPLODE  
W/HEAT.DONT WELD,CUT,EXPOSE EMPTY CNTNR TO FLAME OR SPARK-EXPLODE.

===== Accidental Release Measures =====

Spill Release Procedures:ABSORB WITH SAND & DISPOSE OF IN APPROVED  
MANNER. REMOVE ALL SOURCES OF IGNITION. DIKE AREA WITH SAND TO  
CONTAIN SPILLED LIQUID. WEAR PROTECTIVE CLOTHING. KEEP SOURCES OF

