

GRYPHIN COMPANY, INC -- TT-S-711C, INTERIOR WOOD STAIN -- 8010-00-281-2077

=====  
Product Identification  
=====

Product ID:TT-S-711C, INTERIOR WOOD STAIN

MSDS Date:05/18/1994

FSC:8010

NIIN:00-281-2077

MSDS Number: BTZWY

=== Responsible Party ===

Company Name:GRYPHIN COMPANY, INC

Address:RICHMOND AND TIOGA STREETS

City:PHILADELPHIA

State:PA

ZIP:19134

Country:US

Info Phone Num:215-739-6172

Emergency P

hone Num:215-247-6280 / 800-424-9300

CAGE:0E5W3

=== Contractor Identification ===

Company Name:GRYPHIN COMPANY, INC

Box:5910

City:PHILADELPHIA

State:PA

ZIP:19119

Country:US

Phone:800-482-1886

CAGE:0E5W3

=====  
Composition/Information on Ingredients  
=====

Ingred Name:PETROLEUM SOLVENT (VAPOR PRESSURE 3.1 MM HG)

CAS:8052-41-3

RTECS #:WJ8925000

Fraction by Wt: 60%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:500 PPM

ACGIH TLV:100 PPM

Ingred Name:AMSCO 460 SOLV (VAPOR PRESSURE 0 MM

HG)  
CAS:64475-85-0  
RTECS #:PY8240000  
Fraction by Wt: 1.7%  
Other REC Limits:NONE RECOMMENDED  
ACGIH TLV:200 PPM

Ingred Name:METHANOL (SARA III) (VAPOR PRESSURE 96 MM HG)  
CAS:67-56-1  
RTECS #:PC1400000  
Fraction by Wt: 0.11%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:200 PPM  
ACGIH TLV:200 PPM  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

Ingred Name:SOLVENT G (VAPOR PRESSURE 3 MM HG)  
CAS:64742-94-5  
RTECS #:WF3100000  
Fraction by Wt: 3.8%  
Other REC Limits:NONE RECOMMENDED

Ingred Name:HI FLASH NAPHTHA  
(VAPOR PRESSURE 10 MM HG)  
CAS:64742-95-6  
Fraction by Wt: 0.082%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:100 PPM  
ACGIH TLV:25 PPM

Ingred Name:ANTI-OXIDANT (VAPOR PRESSURE 10 MM HG)  
CAS:96-29-7  
RTECS #:EL9275000  
Fraction by Wt: 0.068%  
Other REC Limits:NONE RECOMMENDED

Ingred Name:XYLENE (SARA III) (VAPOR PRESSURE 8 MM HG)  
CAS:1330-20-7  
RTECS #:ZE2100000  
Fraction by Wt: 0.28%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:100 PPM  
ACGIH TLV:100 PPM  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

Ingred

Name:VOC: 5.22  
RTECS #:9999999VO  
Other REC Limits:NONE RECOMMENDED

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:INHAL: NOSE, THROAT, RESP TRACT IRRIT.  
PROLONGED:HEADACHE, NAUSEA, DIZZINESS, UNCOORDINATION.  
CONCENTRATING & INHALING MAY BE HARMFUL OR FATAL. SKIN: IRRIT.  
PROLONGED:BURNING, REDNESS, DRYING, DERMATI TIS. I  
NGESTION:  
DIGESTIVE TRACT IRRIT, ENTER LUNGS CAUSING VOMITING & LUNG DAMAGE.  
EYE: IRRIT, BURNING, TEARING, REDNESS

===== First Aid Measures =====

First Aid:INHAL: REMOVE INTO FRESH AIR. CALL DR IMMED. IF BREATHING  
IRREGULAR OR HAS STOPPED, START RESUSCITATION & GIVE OXYGEN. SKIN:  
REMOVE ANY CONTAMINATED CLOTHING & WASH SKIN WITH MILD SOAP & WATER  
IMMED. CONSULT DR IF IRRITATION PERSISTS. INGEST: DO NOT INDUCE  
VOMITING. CALL DR & PO  
ISON CTR IMMED. EYE: FLUSH WITH CLEAR WATER  
FOR 15 MIN OR UNTIL IRRITATION SUBSIDES. IF IRRITATION PERSISTS,  
CALL DR.

===== Fire Fighting Measures =====

Flash Point Method:TCC  
Flash Point:54.0F,12.2C  
Lower Limits:0.8  
Extinguishing Media:WATER FOG, FOAM, CARBON DIOXIDE, DRY CHEMICAL  
Fire Fighting Procedures:SCBA,COMPLT PERSN PROTECT EQUIP &CLOTH.AVOID  
SPREAD BURN LIQ W/H2O.FIGHT FIRE FROM DISTANCE.CLS VALVE TO  
AREA.SHUT OFF POWER.TURN ON EMERG L  
IGHT.COOL CTNR W/H2O  
Unusual Fire/Explosion Hazard:VAPOR/DUST MAY FROM EXPLOS MIX  
W/AIR.VAPOR>AIR,MAY TRAVEL,IGNIT/FLASHBACK.CLSD CNTNR EXPLODE  
W/HEAT.DONT WELD,CUT,EXPOSE EMPTY CNTNR TO FLAME OR SPARK-EXPLODE.

===== Accidental Release Measures =====

Spill Release Procedures:ABSORB WITH SAND & DISPOSE OF IN APPROVED  
MANNER. REMOVE ALL SOURCES OF IGNITION. DIKE AREA WITH SAND TO  
CONTAIN SPILLED LIQUID. WEAR PROTECTIVE CLOTHING. KEEP SOURCES OF  
IGN

ITION & HOT, METAL SURFACE S ISOLATED FROM SPILL OR PRODUCT  
CONTAINERS.

=====  
===== Handling and Storage =====

Handling and Storage Precautions:OVERHEATING MAY CAUSE CONTAINER TO  
RUPTURE. USE EXPLOSION-PROOF ELECTRICAL EQUIPMENT. MUST BE KEPT IN  
COVERED AREA. AVOID CONTACT WITH SKIN OR CLOTHES

Other Precautions:KEEP CNTNR CLSD. CHECK CNTNRS FOR LEAK. WEAR PROTECT  
CLOTHING. DON'T STACK CNTNR >2 HIGH. AVOID PROLONGED  
BREATHING/CONTACT W/SKIN. GROU  
ND CNTNRS WHEN POUR/TRANSFER. CHANGE  
CLOTHES & WASH HAND BEFORE EATING, DRINKING, SMOKING.

=====  
===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE NIOSH APPROVED GAS MASK OR RESPIRATOR.  
Ventilation:USE WITH ADEQUATE VENTILATION. EXHAUST AT POINT OF USE.

Protective Gloves:GLOVES IMPERVIOUS TO SOLVENTS

Eye Protection:SAFETY OR SPLASH GOGGLES, FACE SHIELD

Other Protective Equipment:EYEWASH STATION, EMERGENCY SHOWER,  
IMPERMEABLE APRONS.

Work Hygienic

Practices:CHANGE CLOTHES AND WASH HAND THOROUGHLY BEFORE  
EATING, DRINKING, OR SMOKING.

Supplemental Safety and Health

=====  
===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:148 TO 505F

Melt/Freeze Pt:M.P/F.P Text:WONT FREEZE

Vapor Density:> AIR

Spec Gravity:0.95

Viscosity:20-25 SEC Z-2

Evaporation Rate & Reference:< N-BUTYL ACETATE

Solubility in Water: