

CONOCO INC -- PARAFFINIC/NAPHTHENIC SOLVENT, CONOSOL C-200 -- 6850-01-377-1809

===== Product Identification =====

Product ID: PARAFFINIC/NAPHTHENIC SOLVENT, CONOSOL C-200

MSDS Date: 09/05/1993

FSC: 6850

NIIN: 01-377-1809

MSDS Number: BVBSV

=== Responsible Party ===

Company Name: CONOCO INC

Box: 2197

City: HOUSTON

State: TX

ZIP: 77252

Country: US

Info Phone Num: 713-293-5550

Emergency Phone Num: 800-441-3637/800-424-9300 (CHEMTREC)

CAGE: 5R396

=== Contractor Identification ===

Company Name: CONOCO INC

Address: 5 GREENWAY PLAZA E

Box: 2197

City: HOUSTON

State: TX

ZIP: 77252

Country: US

Phone: 713-293-5550 PRODUCT / 800-441-3637 MED

CAGE: 5R396

Company Name: HOC INDUSTRIES, INC

Address: 3511 N. OHIO

Box: 2609

City: WICHITA

State: KS

ZIP: 67219

Country: US

Phone: 316-838-4663

CAGE: 0A9L8

===== Composition/Information on Ingredients =====

Ingred Name: CYCLOPARAFFINIC, ISOPARAFFINIC & NORMAL PARAFFINIC
HYDROCARBONS

CAS: 64742-47-8

RTECS #: OA5504000

Fraction by Wt: >99%

Ot

her REC Limits:NONE RECOMMENDED

OSHA PEL:5 MG/M3 (OIL MIST)

ACGIH TLV:5 MG/M3 (OIL MIST)

===== Hazards Identification =====

LD50 LC50 Mixture:TLV FOR OIL MIST IS 5 MG/M3.

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:TARGET ORGANS:EYE, SKIN, CNS,
RESPIRATORY & GI TRACTS. ACUTE- MAY CAUSE EYES, SKIN, LUNGS
IRRITATION. EXTREME OVEREXPOSURE OR ASPIRATION INTO TH
E LUNGS MAY

CAUSE LUNG DAMAGE OR DEATH. MAY CAUSE CNS EF FECTS. ORAL:HARMFUL IF
INGESTED. ASPIRATION HAZARD. CNS EFFECTS. CHRONIC- UNKNOWN.

Explanation of Carcinogenicity:NONE

Effects of Overexposure:IRRITATION, DROWSINESS, DIZZINESS, NAUSEA,
VOMITING, HEADACHE, REDNESS, TEARING, BLURRED VISION, DEFATTING,
DERMATITIS, FATIGUE, CONVULSION, COMA, DEATH

Medical Cond Aggravated by Exposure:INDIVIDUALS WITH PRE-EXISTING
DISEASES OF THE EYE, SKIN, RESPIRATORY TRACT, CNS MAY HAVE

INCREASED SUSCEPTIBILITY TO THE TOXICITY OF EXCESSIVE EXPOSURES.

===== First Aid Measures =====

First Aid:GET MEDICAL HELP IF SYMPTOMS PERSIST. INHALED:REMOVE TO FRESH
AIR. PROVIDE CPR/OXYGEN IF NEEDED. EYES:FLUSH WITH WATER FOR 15
MINUTES. HOLD EYELIDS OPEN. CALL DOCTOR. SKIN:WASH WITH SOAP &
WATER. ORAL :DO NOT INDUCE VOMITING. IF CONSCIOUS, DRINK 2 GLASSES
OF WATER. GET MEDICAL ATTENTION IMMEDIATELY. IF VOMITING, KEEP HEAD
BELOW HI

PS. NEVER GIVE ANYTIHING BY MOUTH TO AN UNCONSCIOUS PERSON.

===== Fire Fighting Measures =====

Flash Point Method:PMCC

Flash Point:200F,93C

Lower Limits:1.0%

Upper Limits:6.0%

Extinguishing Media:WATER FOG/SPRAY, CARBON DIOXIDE, FOAM/DRY CHEMICAL.
DIRECTLY SPRAYING WATER/FOAM ONTO BURNING OIL MAY CAUSE FROTHING.

Fire Fighting Procedures:DO NOT ENTER ANY ENCLOSED OR CONFINED AREA
WITHOUT PROPER PROTECTIVE EQUIPMENT AND NIOSH-APPROVED
SELF-CONTAINED

BREATHING APPARATUS. COOL CONTAINER WITH WATER.
Unusual Fire/Explosion Hazard:MAY FORM TOXIC MATERIALS.

===== Accidental Release Measures =====

Spill Release Procedures:WEAR PROTECTIVE EQUIPMENT. ELIMINATE SOURCES OF IGNITION. VENTILATE AREA. RECOVER IF POSSIBLE. PICK UP SPILL WITH NON-FLAMMABLE ABSORBENT SUCH AS SAND, EARTH/PUMP (EXPLOSION PROOF). GROUND ALL HANDLING EQUIPMENTS. PREVENT LIQUID FROM ENTERING SEWERS.

Neutralizing Agent:NOT RELEVANT

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL, WELL VENTILATED AREA AWAY FROM HEAT, SPARKS & OXIDIZING AGENTS. KEEP OUT OF REACH OF CHILDREN.

Other Precautions:EMPTY CONTAINERS RETAIN RESIDUE. FOLLOW ALL LABEL INSTRUCTIONS. AVOID REPEATED OR PROLONGED SKIN CONTACT. DO NOT GET IN EYES. DO NOT BREATHE VAPOR OR MIST. DO NOT INGEST.

===== Exposure Controls/Personal Protection =====

Respiratory P

rotection:IF WORKING IN CONFINED AREAS, IF EXCESSIVE MISTING IS EXPECTED OR IF EXPOSURE MAY OR DOES EXCEED RECOMMENDED PERMISSIBLE EXPOSURE LIMITS (PEL), WEAR NIOSH-APPROVED RESPIRATORY PROTECTION FOR ORGANIC VAPORS (REFER TO 29 CFR 1910.134).

Ventilation:GOOD GENERAL VENTILATION SHOULD BE USED. VENTILATION RATES SHOULD BE MATCHED TO CONDITIONS.

Protective Gloves:NEOPRENE IF REPEATED CONTACT POSSIBLE

Eye Protection:CHEMICAL SPLASH GOGGLES IF SPLASHING

Other Protective Equipment:

EYE WASH STATION AND SAFETY SHOWER.

INDUSTRIAL-TYPE WORK CLOTHING, APRON, AND BOOTS IF SPILLS OR SPLASHING CAN OCCUR.

Work Hygienic Practices:OBSERVE GOOD INDUSTRIAL HYGIENE PRACTICES AND RECOMMENDED PROCEDURES. WASH AFTER HANDLING AND BEFORE EATING OR DRINKING.

Supplemental Safety and Health

FORMULA CHANGED, SEE PNI A, SAME NSN. NOTE TO PHYSICIAN:ACTIVATED CHARCOAL SLURRY MAY BE ADMINISTERED. TO PREPARE ACTIVATED CHARCOAL, SUSPEND 50 GRAMS ACTIVATED CHARCOAL IN 400 ML WA

TER AND MIX THOROU
GHLY. ADMINSTER 5 ML/KG OR 350 ML FOR AN AVERAGE ADULT.

===== Physical/Chemical Properties =====

HCC:N1
NRC/State Lic Num:NOT RELEVANT
Boiling Pt:B.P. Text:440F - 550F
Vapor Pres:0.4 @ 100F
Vapor Density:6.2
Spec Gravity:0.82 - 0.83
Solubility in Water:INSOLUBLE
Appearance and Odor:CLEAR, COLORLESS LIQUID, NIL ODOR
Percent Volatiles by Volume:NIL

===== Stability and Reactivity Data =====

Stability Indicator/Material
s to Avoid:YES
OXIDIZING AGENTS
Stability Condition to Avoid:EXCESSIVE HEAT, SPARKS, FLAMES
Hazardous Decomposition Products:CARBON MONOXIDE, CARBON DIOXIDE MAY BE
FORMED.

===== Disposal Considerations =====

Waste Disposal Methods:INCINERATE ABSORBED MATERIAL IN A LICENSED
HAZARDOUS WASTE FACILITY. DISPOSAL SHOULD BE IN ACCORDANCE WITH
LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This

information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.