

STEVENS INDUSTRIES -- 1015 -- 8040-00-063-2835

===== Product Identification =====

Product ID:1015

MSDS Date:02/04/1990

FSC:8040

NIIN:00-063-2835

MSDS Number: BVFVT

=== Responsible Party ===

Company Name:STEVENS INDUSTRIES

Address:39 AVE C

City:BAYNNE

State:NJ

ZIP:07002

Country:US

Info Phone Num:201-437-6500

Emergency Phone Num:201-437-6500

Preparer's Name:STEVE BASCH

CAGE:70372

=== Contractor Iden

tification ===

Company Name:STEVENS INDUSTRIES

Address:39 AVE C

Box:8

City:BAYONNE

State:NJ

ZIP:07002

Country:US

Phone:201-437-6500

CAGE:70372

===== Composition/Information on Ingredients =====

Ingred Name:TRADE SECRET COMPONENTS

Fraction by Wt: 100%

Other REC Limits:NONE RECOMMENDED

===== Hazards Identification =====

Routes of Entry: Inhalation:NO Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Ac

ute and Chronic:INHALATION: ACUTE-MAY CAUSE SLIGHT IRRITATION TO THE NASAL TRACT. CHRONIC-N/A. INGESTION-NOT LIKELY NOR PROBABLE. EYES-MAY CAUSE SLIGHT IRRITATION. SKIN-MAY CAUSE SLIGHT IRRITATION.

Explanation of Carcinogenicity:HAS NOT BEEN IDENTIFIED AS A CARCINOGEN OR PROBABLE CARCINOGEN BY NTP, IARC OR OSHA.

Effects of Overexposure:NONE.

Medical Cond Aggravated by Exposure:NONE.

===== First Aid Measures =====

First Aid:EYES-IRRIGATE IMM

EDIATELY WITH WATER FOR AT LEAST 15 MIN.

SKIN-WASH OFF IN FLOWING WATER. WASH CONTAMINATED CLOTHING BEFORE RESUE. INGESTION-DRINK WATER AND/OR MILK. DO NOT INDUCE VOMITING.

CALL A PHY SICIAN AND/OR TRASNPOR TO EMERGENCY IFREQUIRED.

INHALATION-REMOVE TO FRESH AIR AND IF SYMPTOMS OF OVEREXPOSURE DEVELOP SEEK MEDICAL ATTENTION.

===== Fire Fighting Measures =====

Flash Point:NONE

Extinguishing Media:LIQUID WILL NOT BURN. DRY FILM CAN BURN. EXTINGUISH

WITH WATER, FOAM, CARBON DIOXIDE, DRY CHEMICAL.

Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS WHEN EXTINGUISHING FIRE.

Unusual Fire/Explosion Hazard:MATERIAL MAY SPLATTER OVER 212F.

===== Accidental Release Measures =====

Spill Release Procedures:SHOVEL OR CLEAN UP SPILLED MATERIAL WITH SUITABLE ABSORBENT AND PLACE IN AN APPROVED CONTAINER. THE VISCOSITY OF MATERIAL WILL KEEP IT IN SAME AREA. LET FILM DRY AND THEN SCRAP

E UP.

===== Handling and Storage =====

Handling and Storage Precautions:FOR BEST RESULTS OF PRODUCT STORE AT TEMPERATURES BETWEEN 50 AND 90F. KEEP FROM FREEZING.

Other Precautions:NONE

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE REQUIRED.

Ventilation:LOCAL EXHAUST WITH MECHANICAL ASSISTANCE IF REQUIRED.

Protective Gloves:USE WATER PROOF OR IMPERVIOUS GLOVES.

Eye Protection:USE SPLASH PROOF EYE PROTECTI

ON.

Other Protective Equipment:NO SPECIAL CLOTHING REQUIRED.

Work Hygienic Practices:GOOD HOUSEKEEPING PRACTICES ARE IMPORTANT. WASH THOROUGHLY AFTER USING.

Supplemental Safety and Health

NONE.

===== Physical/Chemical Properties =====

HCC:C3

Boiling Pt:B.P. Text:212F,100C

Melt/Freeze Pt:M.P/F.P Text:32.0F,0.0C

Vapor Pres:18 MMHG

Vapor Density: