

GASCO GASOLINE INC -- UNLEADED GASOLINE, PRODUCT CODE:1104/1410/1411 --  
9130-01-272-0983

===== Product Identification =====

Product ID:UNLEADED GASOLINE, PRODUCT CODE:1104/1410/1411

MSDS Date:07/01/1990

FSC:9130

NIIN:01-272-0983

MSDS Number: BVHKT

=== Responsible Party ===

Company Name:GASCO GASOLINE INC

Address:2060 KNOLL DR

City:VENTURA

State:CA

ZIP:93003-2060

Country:US

Info Phone Num:805-654-8084/618-245-2855

Emergency Phone Num:800-424-9300TRANSP/805-254-2855

Preparer's Name:SAF,HEALTH,ENVIRO AFFAIRS

CAGE:6W116

=== Contractor Identification ===

Company Name:GASCO GASOLINE INC

Address:2060 KNOLL DR

Box:City:VENTURA

State:CA

ZIP:93003-2060

Country:US

Phone:805-654-8084/800-424-9300(CHEMTREC)

CAGE:6W116

Company Name:HARTFORD/WOOD RIVER TERM. INC

CAGE:0820Y

===== Composition/Information on Ingredients =====

Ingred Name:GASOLINE UNLEADED (MIXTURE) WHICH INCLUDES FOLLOWING  
INGREDIENTS.

Fraction by Wt: 100%

Other REC Limits:NONE

RECOMMENDED

Ingred Name:BENZENE (SARA III)

CAS:71-43-2

RTECS #:CY1400000

Fraction by Wt: 0.1-4.9%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:SEE 1910.1028

ACGIH TLV:10 PPM; A2; 9394

EPA Rpt Qty:10 LBS

DOT Rpt Qty:10 LBS

Ingred Name:ETHYL BENZENE (SARA III)

CAS:100-41-4

RTECS #:DA0700000

Fraction by Wt: 2%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:100 PPM

ACGIH TLV:100 PPM/125STEL;9394

EPA Rpt Qty:1000 LBS

action by Wt: 1%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:S, 50 PPM  
ACGIH TLV:S, 50 PPM; 9394  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

Ingred Name:1,2,4-TRIMETHYLBENZENE (SARA III) (PSEUDOCUMENE)  
CAS:95-63-6  
RTECS #:DC3325000  
Fraction by Wt: 2%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:25 PPM  
ACGIH TLV:25 PPM; 9394

Ingred Name:METHYL TERT-BUTYL ETHER (SARA III)  
CAS:1634-04-4  
RTECS #:KN5250000  
Fraction by Wt: 0-15%  
Other REC Limits:NONE RECOMMENDED  
EPA Rpt Qty:1 LB  
DOT Rpt Qty:1 LB

Ingred Name:TOLUENE (SARA III)  
CAS:108-88-3  
RTECS #:XS5250000  
Fraction by Wt: 15%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:200 PPM; Z-2  
ACGIH TLV:S, 50 PPM; 9394  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III)  
CAS:1330-20-7  
RTECS #:ZE2100000  
Fraction by Wt: 12%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:100 PPM  
ACGIH TLV:100 PPM/150STEL;9394  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

Ingred Name:NON-HAZARDOUS INGREDIENTS (TRADE SECRET)  
RTECS #:9999999ZZ

Fraction by Wt: N/GIVEN

Other REC Limits:NONE RECOMMENDED

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:YES

Health Hazards Acute and Chronic:BENZENE TOXIC TO BLOOD/BLOOD-FORMING  
TISSUES.WORKERS EXPOSED TO HI CONCEN MANY YEARS HAVE SLIGHTLY  
HIGHER INCIDENCE OF LEUKEMIA. IRRIT EYES/SKIN/LUNGS AFTER  
PROLONGED/REPEATED EXPOSURE.

Explanation of Carcinogen

icity:CONTAINS BENZENE & IARC LISTS GASOLINE

IN CATEGORY 2B (POSSIBLE CARCINOGEN TO HUMANS).

Effects of Overexposure:WEAKNESS, HEADACHE, NAUSEA, CONFUSION, BLURRED  
VISION, DROWSINESS, OTHER NERVOUS SYSTEM EFFECTS. GREATER EXPOSURE  
MAY CAUSE DIZZINESS, SLURRED SPEECH, FLUSHED FACE, UNCONSCIOUSNESS  
OR CONVULSIONS.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MFG.

===== First Aid Measures =====

First Aid:EYE:IMMED FLUSH W/PLENTY OF WA

TER FOR 15MINS.CALL DR.

SKIN:IMMED WASH W/SOAP & WATER.IRRIT DEVELOPS CALL DR. INHAL:REMOVE  
TO FRESH AIR.NOT BREATH GIVE ART RESP.BREATHING DIFF GIVE OXY.

INGEST:DO NOT I NDUCE VOMIT.IMMED GIVE 2 GLASSES OF WATER.NEVER  
GIVE ANYTHING BY MOUTH TO AN UNCONSC PERSON.CALL DR. NOTE TO  
DOCTOR:5ML/KG(350ML) OF ACTIVATED CHARCOAL SLURRY(50G  
CHARCOAL/400ML WATER)MAY BE GIVEN.

===== Fire Fighting Measures =====

Flash Point Method:TCC

Flash Point:-

50F,-46C

Autoignition Temp:Autoignition Temp Text:536F

Lower Limits:1

Spec Gravity:0.70-0.77

Solubility in Water:SLIGHTLY SOLUBLE.

Appearance and Odor:WATER WHITE TO STRAW YELLOW LIQUID, GASOLINE ODOR.

Percent Volatiles by Volume:100

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

OXIDIZING MATERIALS.

Stability Condition to Avoid:UNDUE EXPOSURE TO AIR, OXIDIZING  
MATERIALS, HEAT, FLAME.

Hazardous Decomposition Products:CARBON M

ONOXIDE MAY BE FORMED FROM  
INCOMPLETE COMBUSTION.

===== Disposal Considerations =====

Waste Disposal Methods:TREATMENT/STORAGE/TRANSP/DISPOSAL MUST BE IAW  
APPLICABLE LOC/STATE/PROVINCIAL/FED REGS. DO NOT FLUSH TO SURFACE  
WATER/SANITARY SEWER SYSTEM. BY ITSELF LIQ IS EXPECTED TO BE  
RCRA-IGNITABLE HAZ WASTE. C ONTAINS RQ-PETROLEUM HYDROCARGON.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated f  
or use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.