

ECOLINK, INC. -- SAFE-STRIP -- 6850-01-386-8424

===== Product Identification =====

Product ID:SAFE-STRIP

MSDS Date:02/01/1994

FSC:6850

NIIN:01-386-8424

MSDS Number: BVHNP

=== Responsible Party ===

Company Name:ECOLINK, INC.

Address:1481 ROCK MOUNTAIN BLVD.

City:STONE MOUNTAIN

State:GA

ZIP:30086

Country:US

Info Phone Num:800-886-8240

Emergency Phone Num:404-621-8240(CHEMTREC 800-424-9300)

CAGE:NO580

=== Contractor Identification ===

Company Name:ECOLINK INC

Add

ress:1481 ROCK MOUNTAIN BLVD

Box:City:STONE MOUNTAIN

State:GA

ZIP:30083-1505

Country:US

Phone:800-886-8240/770-621-8240

CAGE:0WU71

Company Name:ECOLINK, INC.

Address:1481 ROCK MOUNTAIN BLVD.

Box:City:STONE MOUNTAIN

State:GA

ZIP:30086

Country:US

Phone:800-886-8240

CAGE:NO580

Company Name:SMITH-EASTERN CORPORATION (301-937-4548

CAGE:40811

===== Composition/Information on Ingredients =====

Ingred Name:THE MANUFACTURER STATES THAT NO HAZARDOUS INGREDIENTS ARE
PRESENT IN THIS

PRODUCT.
RTECS #:9999999ZZ
Fraction by Wt: 100%
Other REC Limits:NONE RECOMMENDED

Ingred Name:PROPRIETARY MIXTURE
Fraction by Wt: 100%
Other REC Limits:NONE RECOMMENDED

===== Hazards Identification =====

Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE: INHALATION NOT EXPECTED TO BE
HAZARD; AT VERY HIGH CONCENTRATIONS MAY CAUSE DIZZINESS OR
HEADACHE. ASPIRA
TION MAY CAUSE LUNG INJURY. EXPOSURE TO HIGH
CONCENTRATIONS MAY CAUSE EYE IRRITATION. IN GESTION MAY CAUSE GI
TRACT IRRITATION. CHRONIC: PROLONGED OR REPEATED EXPOSURE MAY CAUSE
SKIN IRRITATION.
Explanation of Carcinogenicity:NO INGREDIENTS OF A CONCENTRATION OF
0.1% OR GREATER IS LISTED AS A CARCINOGEN OR SUSPECTED CARCINOGEN.
Effects of Overexposure:INGESTED: NAUSEA, VOMITING. INHALED: DIZZINES,
HEADACHE. SKIN-RASH, DEFATTING, REDNESS, DISCOMFORT. EYES: REDNES,
TEARING,
DISCOMFORT.
Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

===== First Aid Measures =====

First Aid:INGESTED-CALL A PHYSICIAN. IF CONSCIOUS, GIVE 2 GLASSES OF
WATER & INDUCE VOMITING. INHALED-REMOVE TO FRESH AIR. IF BREATHING
DIFFICULT, GIVE OXYGEN. CALL A PHYSICIAN. SKIN-FLUSH WITH LOTS OF
WATER. R EMOVE CONTAMINATED CLOTHES. EYES-IMMEDIATELY FLUSH WITH
LOTS OF WATER FOR AT LEAST 15 MINUTES. CALL A PHYSICIAN.

===== Fire Fighting Measures =====

Flash Point Method:PMCC
Flash Point:199F,93C
Lower Limits:2.18
Upper Limits:12.24
Extinguishing Media:ALCOHOL FOAM, CARBON DIOXIDE, DRY CHEMICALS.
Fire Fighting Procedures:FIGHT AS HYDROCARBON FIRE. FIREFIGHTERS SHOULD
WEAR FULL PROTECTIVE CLOTHING INCLUDING POSITIVE-PRESSURE
SELF-CONTAINED BREATHING APPARATUS.
Unusual Fire/Explosion Hazard:NON-TOXIC AND TOXIC FUMES MAY FORM UPON
COMBUSTION. STAY UPWIND OF FIRE.

=====

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION. ABSORB LIQUID ON VERMICULITE ABSORBENT. PREVENT RUN-OFF FROM ENTERING DRAINS, SEWERS, WATERWAYS. IF RUN-OFF OCCURS; NOTIFY NATIONAL RESPONSE CENTER 800-424-8802 AND STATE/LOCAL AUTHORITIES.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:TREAT AS A COMBUSTIBLE LIQUID. ALWAYS

KEEP CONTAINER CLOSED. AVOID EXCESSIVE CONTACT WITH FUMES OR LIQUID.

Other Precautions:READ MANUFACTURER'S LABEL BEFORE USE.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE NORMALLY REQUIRED. IF ENGINEERING CONTROLS FAIL OR NON-ROUTINE USE OR EMERGENCY OCCURS; USE NIOSH/MSHA APPROVED RESPIRATOR OR SUPPLIED AIR RESPIRATOR OR SCBA, AS REQUIRED. USE IAW 29 CFR 1910.134 AND MANUFACTURER'S RECOMMENDATIONS.

Ventilation:LOCAL EXHAUST/HOOD/FAN.

Protective Gloves:NEOPRENE

Eye Protection:SAFETY GLASSES W/SIDE SHIELD

Other Protective Equipment:NONE SPECIFIED BY MANUFACTURER.

Work Hygienic Practices:WASH HANDS AFTER USE AND BEFORE EATING, DRINKING, OR SMOKING. LAUNDER CONTAMINATED CLOTHES BEFORE REUSE.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:V4

Boiling Pt:B.P. Text:396F,202C

Vapor Pres:1

Spec Gravity:1.062

Evaporation Rate & Reference: