View NSN Online: https://aerobasegroup.es/nsn/8030-00-753-4599

COURTAULDS AEROSPACE, INC -- PR-1440 B-2, BASE -- 8030-00-753-4599

Product ID:PR-1440 B-2, BASE MSDS Date:10/21/1993 FSC:8030 NIIN:00-753-4599 Kit Part:Y MSDS Number: BVNCT === Responsible Party === Company Name: COURTAULDS AEROSPACE, INC Address:5430 SAN FERNANDO ROAD Box:1800 City:GLENDALE State:CA ZIP:91209 Country:US Info Phone Num:818-240-2060 / 818-549-7825 Emergency Phone Num:800-228-5635/800-424-9300 CHEMTREC Preparer's Name: SEROJE HARTOONIANI CAGE:83574 === Contractor Identification === Company Name: PRC-DESOTO INTERNATIONAL, INC. A PPG INDUSTRIES COMPANY Address:5430 SAN FERNANDO RD Box:1800 City:GLENDALE State:CA ZIP:91209 Country:US Phone:818-240-2060 CAGE:83574 Ingred Name: TITANIUM DIOXIDE (LISTED AS REQ'D BY 29 CFR1910.1200, FULLY ENCAPSULATED, NOT HAZARDOUS UNDER NOR MAL USE) CAS:13463-67-7 RTECS #:XR2275000 Fraction by Wt: 3.140% Other REC Limits:NONE RECOMMENDED OSHA PEL:10 MG/M3 ACGIH TLV:10 MG/M3 Ingred Name:CALCIUM CARBONATE(LIMESTONE)(LISTED AS REQ'D BY 29CFR 1910:1200, FULLY ENCAPSULATD, NOT HZDOUS UNDER NORMAL CIRCUMSTANCES) CAS:1317-65-3 RTECS #: EV9580000 Fraction by Wt: 30.421% Other REC Limits:NONE RECOMMENDED OSHA PEL:15.0 MG/M3 ACGIH TLV:10.0 MG/M3 Ingred Name: TOLUENE (SARA III) (VAPOR PRESSURE 23 MM HG) CAS:108-88-3 RTECS #:XS5250000

Fract

ion by Wt: 0.978% Other REC Limits:NONE RECOMMENDED OSHA PEL:100 PPM;STEL 150 PPM ACGIH TLV:50 PPM EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS

Ingred Name:POLYSULFIDE POLYMER (NON HAZARDOUS INGREDIENT) CAS:68611-50-7 Other REC Limits:NONE RECOMMENDED

Ingred Name:SILICA DERIVATIVES (NON HAZARDOUS INGREDIENT) CAS:67762-90-7 Other REC Limits:NONE RECOMMENDED

Ingred Name:VOC PER EPA METHOD 24: 35 G/L (COMBINED PART A & B) RTECS #:9999999VO Other REC Limits:NONE RECOMMENDED

azards Identification ====== H

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:EYES: MAY CAUSE BURNING, TEARING, REDDENING. SKIN: PROLONGED EXPOSURE MAY CAUSE DRYING & CRACKING OF SKIN & DERMATITIS. INHALATION: MAY CAUSE DIZZINESSS, DROWSINESS, & FATIGUE. MAY CAUSE LIVER & KIDNE Y DAMAGE. INGESTION: DROWSINESS, DIZZINESS, & NAUSEA. CHRONIC: DISTURBANCE IN MEMORY, THINKING

EMOTIONS & COORDINATION.

First Aid:EYES: FLUSH WITH WATER. IF SYMPTOMS PERSIST, CONSULT A PHYSICIAN. SKIN: WASH WITH SOAP AND WATER. IF SYMPTOMS PERSISTS, CONSULT A PHYSICIAN. INHALATION: REMOVE TO FRESH AIR. IF SYMPTOMS ARE PRESENT, C ONSULT A PHYSICIAN. INGESTION: DRINK LARGE AMOUNTS OF WATER; INDUCE VOMITING; CONSULT A PHYSICIAN.

F

lash Point:>200F,>93C Extinguishing Media:CARBON DIOXIDE, DRY CHEMICAL, FOAM, WATER SPRAY. Fire Fighting Procedures:USE AIR SUPPLIED RESPIRATOR. Unusual Fire/Explosion Hazard:NONE KNOWN

Spill Release Procedures: SCOOP INTO CONTAINERS. CLEAN-UP RESIDUE WITH A SUITABLE SOLVENT. CERCLA RQ FOR TOLUENE IS 1,000 LBS.

Handling and Storage Precautions:WASH THOROU GHLY AFTER HANDLING AND BEFORE SMOKING OR EATING.

======= Exposure Controls/Personal Protection ===============

Respiratory Protection:NONE Ventilation:GENERAL VENTILATION. Protective Gloves:SOLVENT RESISTANT GLOVES Eye Protection:SAFETY GLASSES Other Protective Equipment:NONE KNOWN Work Hygienic Practices:WASH THOROUGHLY AFTER HANDLING AND BEFORE SMOKING OR EATING. Supplemental Safety and Health KEY1:N1.

HCC: N1 Boiling Pt:B.P. Text:230 TO 350F Vapor Density:> AIR Spec Gravity:1.571 Viscosity:10500P#7@2RPM Evaporation Rate & amp; Reference:< N-BUTYL ACETATE Solubility in Water:SLIGHT Appearance and Odor:BEIGE THIXOTROPIC PASTE Percent Volatiles by Volume:3.3

Stability Indicator/Materials to Avoid:YES NONE KNOWN Stability Condition to Avoid:NOT KNOWN Hazardous Decomposition Products:OXIDES OF CARBON, SULFUR DIOXIDE, TRACES OF HYD

ROGEN SULFIDE

Waste Disposal Methods:NOT A HAZARDOUS WASTE ACCORDING TO EPA REGULATIONS. CONSULT STATE REGULATIONS PRIOR TO DISPOSAL OF SPILLAGE.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate a nd

disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.