Product ID:BCGAM688 MAGNA TAC M688 MSDS Date:10/14/1994 FSC:8040 NIIN:01-203-2251 MSDS Number: BVSLL === Responsible Party === Company Name: BEACON CHEMICAL CO INC Address:125 MACQUESTEN PKY S **City: MOUNT VERNON** State:NY ZIP:10550-5000 Country:US Info Phone Num:914-699-3400 Emergency Phone Num:914-699-3400 CAGE:5B981 === Contractor Identification === Company Name: BEACON CHEMICAL COMPANY, INC. Address:125 MACQUESTEN PARKWAY Box:City:MOUNT VERNON State:NY ZIP:10550 Country:US Phone:914-699-3400 CAGE:5B981

Ingred Name:BISPHENOL A DIGLYCIDYL ETHER RESIN, EPOXY RESIN, EPON 820, ARALDITE 6004, 4,4'-ISOPROPYLIDENEDIPHENOL-EPICHLOROHYDRIN CAS:25068-38-6 RTECS #:KD4380000 Fraction by Wt: >1%

Ingred Name:DIBUTYL PHTHALATE, DI-N-BUTYL PHTHALATE CAS:84-74-2 RTECS #:TI0875000 Fraction by Wt: 11% Other REC Limits:5 MG/CUM OSHA PEL:5 MG/CUM ACGIH TLV:5 MG/CUM EPA Rpt Qty:10 LBS DOT Rpt Qty:10 LBS

LD50 LC50 Mixture:ORAL LD50(RAT): 8 G/KG DIBUTYL PHTHALATE Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:EYES: IRRITATION. SKIN: FREQUENT/PROLONGED CONTACT MAY CAUSE IRRITATION & DERMATITIS. INHALATION: IRRITATION . INGESTION: LOW ODER OF TOXICITY. CHRONIC: EYE CONTACT MAY CAUSE CONJUNCTIVITIS. SKIN: SENS ITIZATION DERMATITIS. Explanation of Carcinogenicity:NONE Effects of Overexposure:IRRITATION

First Aid:EYES: FLUSH W/LARGE AMOUNTS OF WATER FOR 15 MINS. SKIN: FLUSH AREAS THOROUGHLY W/SOAP & WATER. INHALATION: REMOVE TO FRESH AIR. INGESTION: INDUCE VOMITING ONLY IF ALERT. DON'T ATTEMPT TO GIVE ANYTHING BY MOUTH TO A DROWSY/UNCONSCIOUS PERSON. OBTAIN MEDICAL ATTENTION IN ALL CASES.

Flash Point Method:SCC
Flash Point:>200F
Extinguishing Media:WATER FOG, FOAM, CO2, DRY CHEMICAL
Fire Fighting Procedures:WEAR SELF-CONTAINED APPARATUS. COOL EXPOSED EQUIPMENT W/WATER SPRAY.
Unusual Fire/Explosion Hazard:COMBUSTIBLE AT HIGH TEMPS. POLYMERIZATION MAY TAKE PLACE AT ELEVATED TEMPS.

Spill Release Procedures: TAKE UP W/SAND/OTHER ABSORBENT MATERIAL & PLACE IN CONTAINER FOR LATER DISPOSAL.
======================================
Handling and Storage Precautions:STORE AT ROOM TEMP. AVOID EXCESSIVE HEAT. STORE OUT OF DIRECT SUNLIGHT IN A DRY AREA. MAXIMUM STORAGE

TEMPERATURE IS 100F/ Other Precautions:DON'T WEAR CONTACT LENSES WHEN WORKING W/THIS MATERIAL.

Respiratory Protection:NONE REQUIRED UNDER NORMAL HANDLING CONDITIONS. USE NIOSH APPROVED RESPIRATOR IF VAPOR/MIST LEVELS ARE IRRITATING. Ventilation:GENERAL Protective Gloves:NORMALLY NOT NECESSARY Eye Protection:SAFETY GLASSES, GOGGLES/FACE SHIELD Work Hygienic Practices:REMOVE/LAUNDER CONTAMINATED CLOTHING BEFORE

REUSE.

Supplemental Safety and Health

Vapor Pres:NEGLIGIBLE Vapor Density:>1 Spec Gravity:1.2 6 Solubility in Water:INSOLUBLE Appearance and Odor:CREAM COLORED LIQUID W/MILD ODOR

Stability Indicator/Materials to Avoid:YES STRONG ACIDS & BASES, AMINE COMPOUNDS, MERCAPTANS Stability Condition to Avoid:HIGH TEMPS & EXCESSIVE HEAT Hazardous Decomposition Products:CO, CO2, UNKNOWN HYDROCARBONS Conditions to Avoid Polymerization:ELEVATED TEMPERATURES

Waste

Disposal Methods:DISPOSE OF IAW/LOCAL, STATE & FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsib ility for the suitability of this information to their

particular situation.