

DAVLIN PAINT CO -- B60011105D 600 INDUSTRIAL ENAMEL #11105 -- 8010-00-616-7486

===== Product Identification =====

Product ID:B60011105D 600 INDUSTRIAL ENAMEL #11105

MSDS Date:03/20/1992

FSC:8010

NIIN:00-616-7486

MSDS Number: BVTYF

==== Responsible Party ===

Company Name:DAVLIN PAINT CO

Address:1401 E 14TH

City:OAKLAND

State:CA

ZIP:94606-4401

Country:US

Info Phone Num:510-848-2863

Emergency Phone Nu

m:800-424-9300 (CHEMTREC)

CAGE:91007

==== Contractor Identification ===

Company Name:DAVLIN PAINT CO

Address:1401 E 14TH

Box:City:OAKLAND

State:CA

ZIP:94606-4401

Country:US

CAGE:91007

===== Composition/Information on Ingredients =====

Ingred Name:HYDROCARBON MIXTURE [NAPHTHA, HEAVY STRAIGHT RUN]

CAS:64741-41-9

Fraction by Wt: 30%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:300 PPM

ACGIH TLV:300 PPM

===== Hazards Identification =====

Routes of

Entry: Inhalation: YES Skin: YES Ingestion: YES

Reports of Carcinogenicity: NTP: NO IARC: NO OSHA: NO

Health Hazards Acute and Chronic: ACUTE: INHALATION/INGESTION MAY CAUSE

CENTRAL NERVOUS SYSTEM (CNS) DEPRESSION. INHALATION MAY CAUSE RESPIRATORY IRRITATION. INGESTION MAY CAUSE GI TRACT IRRITATION. CONTACT MAY CAUSE EYE IRRITATION. ASPIRATION MAY CAUSE LUNG DAMAGE. CHRONIC: PROLONGED OR REPEATED EXPOSURE MAY CAUSE SKIN IRRITATION OR DERMATITIS; CNS DAMAGE.

Explanation of Carcinogenic

ity: NO INGREDIENT OF A CONCENTRATION OF 0.1%

OR GREATER IS LISTED AS A CARCINOGEN OR SUSPECTED CARCINOGEN.

Effects of Overexposure: CNS DEPRESSION: HEADACHE, NAUSEA, VOMITING, DIZZINESS, DROWSINESS, FATIGUE, WEAKNESS, UNCONSCIOUSNESS. INHALED: COUGHING, WHEEZING, SHORTNESS OF BREATH. EYES: REDNESS, TEARING, BLURRED VISION. SKIN: DRYING, DEFATTING, RASH, REDNESS, ITCHING, DISCOMFORT. INGESTED: NAUSEA, VOMITING, DIARRHEA.

Medical Cond Aggravated by Exposure: RESPIRATORY TRACT IRRITATION, DERMATITIS, NAUSEA.

===== First Aid Measures =====

First Aid: INHALATION: REMOVE TO FRESH AIR. GIVE ARTIFICIAL RESPIRATION OR OXYGEN IF NEEDED. CONSULT A DOCTOR. EYE: FLUSH WITH LOTS OF WATER FOR 15 MINUTES, HOLD LIDS OPEN. GET MEDICAL ATTENTION. SKIN: WASH WITH SOAP & WATER. REMOVE CONTAMINATED CLOTHING. INGESTION: DO NOT INDUCE VOMITING! IF CONSCIOUS, GIVE WATER OR MILK TO DRINK. GET MEDICAL ATTENTION IMMEDIATELY.

=====

===== Fire Fighting Measures =====

Flash Point Method: SCC

Flash Point: 104F, 40C

Lower Limits: 1.0

Upper Limits: 6.1

Extinguishing Media: WATER FOG, CARBON DIOXIDE, DRY CHEMICAL, ALCOHOL FOAM. WATER MAY BE INEFFECTIVE; USE TO COOL FIRE EXPOSED CONTAINERS.

Fire Fighting Procedures: FIREFIGHTERS SHOULD WEAR FULL PROTECTIVE CLOTHING INCLUDING POSITIVE-PRESSURE SELF-CONTAINED BREATHING APPARATUS. USE WATER TO COOL FIRE EXPOSED CONTAINERS.

Unusual Fire/Explosion

n Hazard:VAPORS FORM AN EXPLOSIVE MIXTURE WITH AIR WHICH MAY BE IGNITED BY MANY SOURCES.CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO HEAT.ISOLATE FROM IGNITION SOURCES.

===== Accidental Release Measures =====

Spill Release Procedures:EVACUATE ALL NON-ESSENTIAL PERSONNEL. ELIMINATE ALL SOURCES OF IGNITION. VENTILATE THE AREA. PROVIDE ADEQUATE PROTECTIVE EQUIPMENT. DIKE AROUND THE AREA. COVER SPILL WITH INERT ABSORBANT AND TRANSFER WITH NON-SPARKING TOOLS.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:STORE BELOW 80F IN A CLOSED CONTAINER.STORE IN ORIGINAL CONTAINER.AVOID FLAME & HIGH TEMPERATURES.DO NOT STORE NEAR STRONG OXIDIZING AGENTS/ACIDS.

Other Precautions:DO NOT TAKE INTERNALLY, AVOID PROLONGED OR REPEATED INHALATION OF HEATED VAPORS OR MISTS. KEEP AWAY FROM HEAT. GROUND ALL CONNECTIONS, CONTAINERS, ETC. WHEN POURING OR TRANSFERRING. USE NON-SPARKING TOOLS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF ENGINEERING CONTROLS FAIL OR NON-ROUTINE USE OR EMERGENCY OCCURS; USE NIOSH/MSHA APPROVED RESPIRATOR OR SUPPLIED AIR RESPIRATOR OR SCBA, AS REQUIRED. USE IAW 29 CFR 1910.134 AND MANUFACTURER'S RECOMMENDATIONS.

Ventilation:USE ADEQUATE EXPOSURE-PROOF MECHANICAL VENTILATION TO MAINTAIN EXPOSURE BELOW AIRBORNE EXPOSURE LIMITS.

Prot

ective Gloves:NITRILE, PVA.

Eye Protection:SAFETY GLASSES/CHEMICAL SPLASH GOGGLES

Other Protective Equipment:WEAR IMPERMEABLE APRONS & PROTECTIVE CLOTHING WHENEVER POSSIBLE TO PREVENT REPEATED OR PROLONGED CONTACT.

Work Hygienic Practices:WASH HANDS AFTER USE AND BEFORE EATING, DRINKING, USING THE TOILET OR SMOKING.LAUNDER CONTAMINATED CLOTHES BEFORE REUSE.

Supplemental Safety and Health

MSDS ENTERED BY DLA-HMIS UNDER PROJECT FOR GSA.

===== Physical/Chemical Proper

ties =====

HCC:F4

Boiling Pt:B.P. Text:315F,157C

Vapor Density:>1

Spec Gravity:1.1

Evaporation Rate & Reference: