

NCH CORP DIV OF PLUMBMASTER INC -- HY-ZINC -- 8010-00-501-5798

=====
Product Identification
=====

Product ID:HY-ZINC

MSDS Date:03/12/1991

FSC:8010

NIIN:00-501-5798

MSDS Number: BVZFY

=== Responsible Party ===

Company Name:NCH CORP DIV OF PLUMBMASTER INC

Address:2727 CHEMSEARCH BLVD

Box:152170

City:IRVING

State:TX

ZIP:75015

Country:US

Info Phone Num:214-438-1381

Emergency Phone Num:214-438-1381

Pre

parer's Name:RICHARD STOLLEY

CAGE:FO113

=== Contractor Identification ===

Company Name:JOHN J. MCMULLEN ASSOC.

Address:11771 ROCK LANDING DRIVE

Box:City:NEWPORT NEWS

State:VA

ZIP:23607

Country:US

Phone:804-873-6500

CAGE:3P768

Company Name:NCH CORP

Address:2727 CHEMSEARCH BLVD

Box:152170

City:IRVING

State:TX

ZIP:75015-2170

Country:US

Phone:972-438-0563

CAGE:20913

Company Name:NCH CORP DIV OF PLUMBMASTER INC

Address:2727 CHEMSEARCH BLVD

Box:152170

City:IRVING

State:TX

ZIP:75015

Country:US

Phone:21

4-438-1381
CAGE:FO113

=====
Composition/Information on Ingredients
=====

Ingred Name:ZINC (SARA III)
CAS:7440-66-6
RTECS #:ZG8600000
Other REC Limits:NONE RECOMMENDED
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III)
CAS:1330-20-7
RTECS #:ZE2100000
Other REC Limits:NONE RECOMMENDED
OSHA PEL:100 PPM
ACGIH TLV:100 PPM/150STEL;9394
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:BENZIN
CAS:8030-30-6
RTECS #:DE3030000
Other REC L
imits:NONE RECOMMENDED

Ingred Name:VM&P NAPHTHA (LIGROINE)
CAS:8032-32-4
RTECS #:OI6180000
Other REC Limits:NONE RECOMMENDED
OSHA PEL:300 PPM
ACGIH TLV:300 PPM; 9394

Ingred Name:2-ETHOXYETHYL ACETATE (EGEEA)
CAS:111-15-9
RTECS #:KK8225000
Other REC Limits:NONE RECOMMENDED
OSHA PEL:S, 100 PPM
ACGIH TLV:S, 5 PPM; 9394

=====
Hazards Identification
=====

LD50 LC50 Mixture:ORAL LD50 (RAT) IS 75MG/KG(XYLENE)
Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:EYES:MAY CAUSE MODERATE IRRITATION.SKIN:MAY CAUSE MODERATE IRRITATION AND DEFATTING.INGEST:MAY CAUSE GI TRACT IRRITATION.MAY CAUSE LUNG DAMAGE IF VOMITED AFTER INGESTING.INHAL:MAY CAUSE RESPIRATORY IRRITATION AND CNS EFFECTS.CHRONIC:HMIS SUGGESTS THAT EXPOSURE TO XYLENE CAN CAUSE BRAIN,CNS,LIVER,KIDNEY AND BLOOD DAMAGE

Explanation of Carcinogenicity:THERE ARE NO INGREDIENTS ABOVE 0.1% W

HIGH ARE IDENTIFIED AS CARCINOGENS BY NTP,IARC OR OSHA.

Effects of Overexposure:INHAL:ANESTHETIC EFFECT(EG.SLEPPINESS),HEADACHE,BLURRED VISION,BLUIISH TINT TO SKIN.SKIN:REDNESS,DERMATITIS.

Medical Cond Aggravated by Exposure:PERSONS WITH PRE-EXISTING SKIN AILMENTS MAY BE AT INCREASED RISK FROM EXPOSURE.

===== First Aid Measures =====

First Aid:SKIN:REMOVE CONTAMINATED CLOTHING;WASH WITH SOAP AND WATER.EYES:FLUSH WITH WATER FOR 15 MINUTES.INH AL:REMOVE TO FRESH AIR.GIVE OXYGEN OR ARTIFICIAL RESPIRATION IF NEEDED.INGEST:DO NOT INDUCE VOMITING. GET PROMPT QUALIFIED MEDICAL ATTENTION.PHYSICIAN SHOULD USE GASTRIC LAVAGE.

===== Fire Fighting Measures =====

Flash Point Method:TCC
Flash Point:106F,41C
Extinguishing Media:WATER FOG,DRY CHEMICAL,CARBON DIOXIDE.
Fire Fighting Procedures:USE A SELF-CONTAINED BREATHING APPARATUS AND FULL PROTECTIVE EQUIPMENT.COOL FIRE EXPOSED CONTAINERS WITH WATER FOG.
Unusual Fire/Explosion Hazard:VAPORS ARE HEAVIER THAN AIR,CAN TRAVEL DISTANCES ALONG THE GROUND,AND FLASHBACK AT THE SOURCE.

===== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE SOURCES OF IGNITION.USE PROPER RESPIRATORY AND PROTECTIVE EQUIPMENT.VENTILATE AREA.SHOVEL OR SCRAPE UP;SOAK UP REMAINDER WITH A NON-COMBUSTIBLE INERT ABSORBANT(CLAY,SAND);PLACE IN PROPER CONTAINER FOR DISPOSAL.
Neutralizing Agent:NONE

=====

===== **Handling and Storage**=====

Handling and Storage Precautions:STORE AT TEMPERATURES BELOW 100F.FOLLOW LABEL DIRECTIONS.AVOID TEMPERATURES BELOW 0F.KEEP AWAY FROM OPEN FLAMES.

Other Precautions:FOLLOW LABEL DIRECTIONS.AVOID BREATHING VAPORS.AVOID SKIN AND EYE CONTACT.

===== **Exposure Controls/Personal Protection**=====

Respiratory Protection:WHERE ENVIRONMENTAL CONTROLS ARE LACKING OR IN ENCLOSED SPACES USE EITHER A SELF-CONTAINED BREATHING APPARATUS OR

A NOISH/MSHA APPROVED RESPIRATOR FOR ORGANIC VAPORS AND PARTICULATES,DEPENDING ON THE AIRBORN CONCENTRATION.

Ventilation:LOCAL VENTILATION AT THE WORKSITE;MECHANICAL(GENERAL) VENTILATION TO MAINTAIN TLV/PEL.

Protective Gloves:NEOPRENE,NITRILE

Eye Protection:CHEMICAL SPLASH GOGGLES

Other Protective Equipment:PROTECTIVE CLOTHING,AS NEEDED.PROVIDE A LOCAL EYE WASH STATION AND SAFETY SHOWER.

Work Hygienic Practices:USE REASONABLE CARE IN HANDLING THIS

PRODUCT.WASH HANDS AFTER USE AND BEFORE EATING.

Supplemental Safety and Health

NONE

===== **Physical/Chemical Properties**=====

HCC:V3

Spec Gravity:2.61

Solubility in Water:NEGLIGIBLE

Appearance and Odor:AEROSOL.CONTENTS IS A HEAVY PASTE;GRAY;XYLENE ODOR.

Percent Volatiles by Volume:17.1

===== **Stability and Reactivity Data**=====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZERS,ACIDS,NITRATES,STRONG ALKALIES.

Stability Condition to

Avoid:HIGH HEAT,SOURCES OF IGNITION.

Hazardous Decomposition Products:CARBON DIOXIDE,CARBON MONOXIDE,SMOKE.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH FEDERAL,STATE AND LOCAL REGULATIONS.DO NOT PUNCTURE OR INCINERATE AEROSOL CANS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America

in no manner whatsoever,

expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.