

HULS AMERICA INC -- MIL-H-6083E -- 9150-00-935-9810

===== Product Identification =====

Product ID:MIL-H-6083E

MSDS Date:01/16/1989

FSC:9150

NIIN:00-935-9810

MSDS Number: BVZHV

=== Responsible Party ===

Company Name:HULS AMERICA INC

Address:80 CENTENNIAL AVE

Box:456

City:PISCATAWAY

State:NJ

ZIP:08855-0456

Country:US

Info Phone Num:201-980-6800

Emergency Phone Num:201-980-6800

Preparer's Name:P.A. PARKER

CAGE:63182

=== Contractor Identification ===

Company Name:

HULS AMERICA INC

Address:TURNER PLACE

Box:365

City:PISCATAWAY

State:NJ

ZIP:08855

Country:US

Phone:201-763-7173

CAGE:63182

===== Composition/Information on Ingredients =====

Ingred Name:THE MANUFACTURER STATES THAT NO HAZARDOUS INGREDIENTS ARE
PRESENT IN THIS PRODUCT.

Fraction by Wt: 100%

Other REC Limits:NONE SPECIFIED

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO

Reports of Carcinogenicity:N

TP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:LOW ORAL AND DERMAL TOXICITY. MISTS OR FUMES FROM EXCESSIVE HEATING AMY CAUSE EYE AND SKIN IRRITATION. MAY ALSO CAUSE RESPIRATORY TRACT IRRITATION.

Explanation of Carcinogenicity:NO INGREDIENT OF A CONCENTRATION OF 0.1% OR GREATER IS LISTED AS A CARCINOGEN OR SUSPECTED CARCINOGEN.

Effects of Overexposure:MIST OR FUMES FROM EXCESSIVE HEATING MAY CAUSE NAUSEA AND/OR VOMITING.

Medical Cond Aggravated by Exposure:NONE SPECIFIE
D BY MANUFACTURER.

===== First Aid Measures =====

First Aid:CONTACT- WASH SKIN WITH SOAP AND EATER; FLUSH EYES WITH WATER FOR 25 MIN. CALL A PHYSICIAN IF IRRITATION DEVELOPS. INHALATION- REMOVE VICTIM TO FRESH AIR AND GIVE ARTIFICIAL RESPIRATION OR OXYGEN IF N EEDED. INGESTION- DO NOT INDUCE VOMITING. CALL A PHYSICIAN.

===== Fire Fighting Measures =====

Flash Point Method:COC

Flash Point:200F,93C

Lower Li

mits:1

Upper Limits:6

Extinguishing Media:WATER FOG, DRY CHEMICAL, FOAM OR CARBON DIOXIDE.

Fire Fighting Procedures:BURNING WILL PRODUCE TOXIC FUMES. WEAR SELF-CONTAINED BREATHING APPARATUS AND FULL TURN-OUT GEAR TO FIGHT FIRE. AVOID SPREADING LIQUIE AND FIRE WITH WATER.

Unusual Fire/Explosion Hazard:EXPOSURE TO HEAT BUILDS UP PRESSURE IN CLOSED CONTAINERS. COOL WITH WATER SPRAY.

===== Accidental Release Measures =====

Spill Release Procedures:COVER WIT
H AN INERT ABSORBENT MATERIAL AND
REMOVE TO DISPOSAL CONTAINER.

Neutralizing Agent:NONE

===== Handling and Storage =====

Handling and Storage Precautions:DO NOT USE OIL ABOVE THE MAXIMUM RECOMMENDED OPERATING TEMPERATURE OF 200F. MAY SOFTEN SOME PLASTIC AND PAINT SURFACES.

Other Precautions:NONE

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF OVERHEATED, USE APPROPRIATE NIOSH-APPROVED RESPIRATORY

PROTECTIVE EQUIPMENT.
Ventilation:LOCAL EXHAUST AND MECHANICAL VENTILATION RECOMMENDED.
Protective Gloves:IMPERMEABLE GLOVES
Eye Protection:CHEMICAL SPLASH GOGGLES OR FACE SHIELD
Other Protective Equipment:EYEWASH FOUNTAIN, SAFETY SHOWER. WASH
CONTAMINATED CLOTHING BEFORE REUSE.
Work Hygienic Practices:NONE SPECIFIED BY MANUFACTURER.
Supplemental Safety and Health
MSDS PRESENTED BY CAGE 63182 FOR CONTRACT NUMBER SP0451-95-C004.

===== Physical/Chemical Properties =====
=====

HCC:V6
Boiling Pt:B.P. Text:420F,216C
Vapor Pres:0.07 MM HG
Vapor Density:>1
Spec Gravity: