

3M, INDUSTRIAL SPECIALTIES DIV -- EC-3924 BRUSHABLE STRUCTURAL ADHESIVE PRIMER

=====
MSDS Safety Information
=====

FSC: 8040
NIIN: 01-280-1462
MSDS Date: 11/08/1993
MSDS Num: BWHBQ
Product ID: EC-3924 BRUSHABLE STRUCTURAL ADHESIVE PRIMER (XD)
MFN: 02
Responsible Party
Cage: 52152
Name: 3M, INDUSTRIAL SPECIALTIES DIVISION
Address: 3M
CENTER
City: SAINT PAUL MN 55144-1000
Info Phone Number: 612-733-1110
Emergency Phone Number: 612-733-1110
Preparer's Name: UNKNOWN
Review Ind: Y
Published: Y

=====
Contractor Summary
=====

Cage: 52152
Name: MINNESOTA MINING & MFG CO INDUSTRIAL TAPE & SPECIALTIES DIV
Address: 3M CENTER
City: ST PAUL MN 55144-1000
Phone: 1-800-364-3577

==
Item Description Information
=====

Item Manager: GSA
Item Name: PRIMER,ADHESIVE
Specification Number: NONE
Type/Grade/Class: NONE
Unit of Issue: QT
UI Container Qty: 0
Type of Container: CAN

=====
Ingredients
=====

Cas: 123-42-2
RTECS #: SA9100000
Name: DIACETONE ALCOHOL (4-HYDROXY-4-METHYL-2-PENTANONE)
% Wt: 15-40
Other REC Limits: NONE RECOM

MENDED
OSHA PEL: 50 PPM
ACGIH TLV: 50 PPM; 9394

Cas: 78-93-3
RTECS #: EL6475000
Name: METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)
% Wt: 15-40
Other REC Limits: NONE RECOMMENDED
OSHA PEL: 200 PPM
ACGIH TLV: 200 PPM/300STEL;9394
EPA Rpt Qty: 5000 LBS
DOT Rpt Qty: 5000 LBS

Cas: 109-99-9
RTECS #: LU5950000
Name: TETRAHYDROFURAN (SARA III)
% Wt: 10-30
Other REC Limits: NONE RECOMMENDED
OSHA PEL: 200 PPM
ACGIH TLV: 200 PPM/250STEL;9
394
EPA Rpt Qty: 1000 LBS
DOT Rpt Qty: 1000 LBS

Cas: 25036-25-3
Name: BISPHENOL A EPOXY RESIN
% Wt: 1-5
Other REC Limits: NONE RECOMMENDED
OSHA PEL: NOT ESTABLISHED
ACGIH TLV: NOT ESTABLISHED

Cas: 107-98-2
RTECS #: UB7700000
Name: 1-METHOXY-2-PROPANOL (PROPYLENE GLYCOL MONOMETHYL ETHER)
% Wt: 1-5
Other REC Limits: NONE RECOMMENDED
OSHA PEL: 100 PPM
ACGIH TLV: 100 PPM/150STEL;9394

Cas: 7732-18-5
RTECS #:

ZC0110000

Name: WATER

% Wt: 1-5

Other REC Limits: NONE RECOMMENDED

OSHA PEL: NOT ESTABLISHED

ACGIH TLV: NOT ESTABLISHED

Cas: 7789-06-2

RTECS #: GB3240000

Name: STRONTIUM CHROMATE (SARA III)

% Wt: 0.5-1.5

Other REC Limits: NONE RECOMMENDED

OSHA PEL: C 0.1 MG (CRO3)/M3

ACGIH TLV: 0.0005MG(CR)/M3,A294

EPA Rpt Qty: 10 LBS

DOT Rpt Qty: 10 LBS

Cas: 67-56-1

RTECS #: PC1400000

Name: METHYL ALCOHOL (METHANOL) (SARA III)

% Wt: 0.1-0.5

Other R

EC Limits: NONE RECOMMENDED

OSHA PEL: S,200PPM

ACGIH TLV: S,200PPM/250STEL; 94

EPA Rpt Qty: 5000 LBS

DOT Rpt Qty: 5000 LBS

Cas: 17526-94-2

Name: N,N'-(METHYL-1,3-PHENYLENE)BIS(N,N'-DIMETHYLUREA)

% Wt: 0.1-0.5

Other REC Limits: NONE RECOMMENDED

OSHA PEL: NOT ESTABLISHED

ACGIH TLV: NOT ESTABLISHED

Cas: 67-64-1

RTECS #: AL3150000

Name: ACETONE (SARA III)

% Wt: 0.1-0.5

Other REC Limits: NONE RECOMMENDED

OSHA PEL: 1000 PPM

ACGIH TLV: 750PP

M/1000STEL;9294
EPA Rpt Qty: 5000 LBS
DOT Rpt Qty: 5000 LBS

=====
Health Hazards Data
=====

LD50 LC50 Mixture: UNKNOWN

Route Of Entry Inds - Inhalation: YES

Skin: YES

Ingestion: YES

Carcinogenicity Inds - NTP: YES

IARC: YES

OSHA: NO

Effects of Exposure: ACUTE: MAY CAUSE CNS DEPRESSION IF INHALED OR SWALLOWED.

INHALATION MAY CAUSE RESPIRATORY TRACT IRRITATION, LIVER/KIDNEY EFFECTS.

INGESTION M

AY CAUSE GI TRACT IRRITATION, ASPIRATION. CONTACT MAY CAUSE

MODERATE EYE IRRITATION OR ALLERGIC SKIN REACTION. CHRONIC: PROLONGED OR REPEATED EXPOSURE MAY CAUSE SKIN ULCERATIONS.

Explanation Of Carcinogenicity: CHROMIUM (HEXAVALENT COMPOUNDS) ARE LISTED BY NTP, IARC, ACGIH AS KNOWN HUMAN CARCINOGENS.

Signs And Symptoms Of Overexposure: EYES: REDNESS, SWELLING, PAIN, TEARING, HAZY VISION. SKIN: REDNESS, SWELLING, BLISTERING, ITCHING. INHALED/INGESTED

CNS: DIZZINESS, DROWSINESS, INCOORD

INATION, SLOWED REACTION TIME, SLURRED

SPEECH, GI DDINESS, UNCONSCIOUSNESS. INHALED(IRR.): COUGH, SNEEZING. INGESTED

(IRR.): NAUSEA, VOMITING, ABDOMINAL TENDERNESS.

Medical Cond Aggravated By Exposure: NONE SPECIFIED BY MANUFACTURER.

First Aid: INHALATION-REMOVE TO FRESH AIR. RESTORE BREATHING. GET MEDICAL ATTENTION. EYE-IMMEDIATELY FLUSH WITH LOTS OF WATER FOR 15 MINUTES. GET MEDICAL ATTENTION IMMEDIATELY. SKIN-WASH WITH SOAP & WATER. REMOVE CONTAMINATED CLOTHING. INGESTION-DO NO

T INDUCE VOMITING, UNLESS INSTRUCTED BY

PHYSICIAN. NOTHING BY MOUTH IF UNCONSCIOUS. GET MEDICAL ATTENTION IMMEDIATELY.

=====
Handling and Disposal
=====

Spill Release Procedures: VENTILATE AREA. ELIMINATE ALL SOURCES OF IGNITION.

CONTAIN SPILL. COLLECT USING NON-SPARKING TOOLS. COVER WITH ABSORBENT

MATERIAL. COVER AREA WITH AFFF FOAM. COLLECT SPILLED MATERIAL. CLEAN-UP

RESIDUE WITH SOLV

ENT. PLACE IN APPROVED METAL CONTAINER.

Neutralizing Agent: NONE SPECIFIED BY MANUFACTURER.

Waste Disposal Methods: PER MANUFACTURER-UNUSED/UNCONTAMINATED PRODUCT MAY BE HAZARDOUS WASTE UNDER RCRA/EPA 40CFR261: D001 (IGNITEABLE); D007 (CHROMIUM); D035 (METHYL ETHYL KETONE). DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS.

Handling And Storage Precautions: SORE AT TEMPERATURES BELOW 0F (-18C). ALLOW TO RETURN TO ROOM TEMPERATURE BEFORE USE. STORE IN A COOL, DRY PLACE AWAY FROM SOURCES OF IGNITION.

FROM SOURCES OF IGNITION.

Other Precautions: KEEP AWAY FROM INCOMPATIBLE MATERIALS. AVOID STATIC DISCHARGE, PROPERLY BOND & GROUND WHEN TRANSFERRING PRODUCT. KEEP CONTAINER TIGHTLY CLOSED. KEEP OUT OF REACH OF CHILDREN.

=====
Fire and Explosion Hazard Information
=====

Flash Point Method: TCC

Flash Point Text: 6F,-14C

Autoignition Temp Text: UNKNON

Lower Limits: 1.8

Upper Limits: 11

.8

Extinguishing Media: WATER, CARBON DIOXIDE, DRY CHEMICAL, FOAM.

Fire Fighting Procedures: FIREFIGHTERS SHOULD WEAR FULL PROTECTIVE CLOTHING INCLUDING POSITIVE-PRESSURE SELF-CONTAINED BREATHING APPARATUS.

Unusual Fire/Explosion Hazard: CLOSED CONTAINERS EXPOSED TO HEAT FROM FIRE MAY BUILD PRESSURE & EXPLODE.

=====
Control Measures
=====

Respiratory Protection: IF ENGINEERING CONTROLS FAIL OR NON-ROUTINE USE OR

EMERGENCY OCCURS; USE NIOSH/MSHA APPROVED RESPIRATOR OR SUPPLIED AIR RESPIRATOR OR SCBA, AS REQUIRED. USE IAW 29 CFR 1910.134 AND MANUFACTURER'S RECOMMENDATIONS.

Ventilation: USE ADEQUATE EXPLOSION-PROOF MECHANICAL VENTILATION OR LOCAL EXHAUST TO MAINTAIN EXPOSURE BELOW TLV(S).

Protective Gloves: PVA

Eye Protection: SAFETY GLASSES/CHEMICAL SPLASH GOGGLES

Other Protective Equipment: WEAR APRON & COVERALLS. DLA-: EYE WASH STATION & SAFETY SHOWER.

Work Hygienic P

actices: WASH HANDS AFTER USE AND BEFORE EATING, DRINKING, OR
SMOKING. LAUNDRER CONTAMINATED CLOTHES BEFORE REUSE.
Supplemental Safety and Health: MSDS ENTERED BY DLA- UNDER PROJECT FOR GSA.

=====
Physical/Chemical Properties
=====

HCC: F2
B.P. Text: 151F,66C
M.P/F.P Text: UNKNOWN
Decomp Text: UNKNOWN
Vapor Pres: 145
Vapor Density: 2.5
Spec Gravity: 0.89
Viscosity: 10 CENTIPOISE
Evaporation Rat
e & Reference: >2 (ETHER=1)
Solubility in Water: SLIGHT
Appearance and Odor: VERY THIN YELLOW LIQUID, SOLVENT ODOR.
Percent Volatiles by Volume: 94
Corrosion Rate: UNKNOWN

=====
Reactivity Data
=====

Stability Indicator: YES
Stability Condition To Avoid: NONE KNOWN.
Materials To Avoid: NONE KNOWN.
Hazardous Decomposition Products: CARBON MONOXIDE AND CARBON DIOXIDE, OXIDES OF
NITROGEN, HYDR
OGEN CYANIDE.
Hazardous Polymerization Indicator: NO
Conditions To Avoid Polymerization: WILL NOT OCCUR.

=====
Toxicological Information
=====

=====
Ecological Information
=====

=====
MSDS Transport Information
=====

=====
=====
Regulatory Information
=====
=====

Other Information
=====
=====

Transportation Information
=====
=====

Responsible Party Cage: 52152

Trans ID NO: 121555

Product ID: EC-3924 BRU

SHABLE STRUCTURAL ADHESIVE PRIMER (XD)

MSDS Prepared Date: 11/08/1993

Review Date: 02/09/1995

MFN: 2

Tech Entry NOS Shipping Nm: CONTAINS DIACETONE ALCOHOL AND METHYL ETHYL KETONE

Net Unit Weight: 1.9 LBS

Multiple KIT Number: 0

Review IND: Y

Unit Of Issue: QT

Container QTY: 0

Type Of Container: CAN
=====

Detail DOT Information
=====
=====

DOT PSN Code: LFJ

DOT Proper Shipping Name: PAINT RELATED MATERI
AL

DOT PSN Modifier: INCLUDING PAINT THINNING, DRYING, REMOVING, OR REDUCING
COMPOUND

Hazard Class: 3

UN ID Num: UN1263

DOT Packaging Group: II

Label: FLAMMABLE LIQUID

Special Provision: B52,T7,T30

Packaging Exception: 150

Non Bulk Pack: 173

Bulk Pack: 242

Max Qty Pass: 5 L

Max Qty Cargo: 60 L

Vessel Stow Req: B
=====

Detail IMO Information
=====
=====

IMO PSN Code: LCP

IMO Proper Shipping Name: PAIN

T OR PAINT RELATED MATERIAL

IMO PSN Modifier: (INCLUDING PAINT, LACQUER, ENAMEL, STAIN, SHELLAC SOLUTIONS, VARNISH, POLISH, LIQUID FILLER AND LIQUID LACQUER BASE) OR (INCLUDING PAINT THINNING OR REDUCING COMPOUND) o

IMDG Page Number: 3268

UN Number: 1263

UN Hazard Class: 3.2

IMO Packaging Group: I/II *

Subsidiary Risk Label: -

EMS Number: 3-05

MED First Aid Guide NUM: 310

=====
Detail IATA Information
=====

=====
IATA PSN Code: SXI

IATA UN ID Num: 1263

IATA Proper Shipping Name: PAINT

IATA PSN Modifier: (INCLUDING

PAINT,LACQUER,ENAMEL,STAIN,SHELLAC,VARNISH,POLISH,LIQUID FILLER AND LIQUID LACQUER BASE)

IATA UN Class: 3

IATA Label: FLAMMABLE LIQUID

UN Packing Group: II

Packing Note Passenger: 305

Max Quant Pass: 5L

Max Quant Cargo: 60L

Packaging Note Cargo: 307

Exceptions: A7,A72

=====
Detail AFI Information
=====

=====
AFI PSN Code: SXI

AFI Proper Shipping Name: PAINT OR PAINT RELATED MATERIAL

AFI PSN Modifier: (INCLUDING PAINT,LACQUER,ENAMEL,STAIN,SHELLAC

SOLUTIONS,VARNISH,POLISH,LIQUID FILLER AND LIQUID LACQUER BASE) OR (INCLUDING PAINT THINNING OR REDUCING COMPOUNDS)

AFI Hazard Class: 3

AFI UN ID NUM: UN1263

AFI Packing Group: II

Special Provisions: P5

Back Pack Reference: A7.3

=====
HAZCOM Label
=====

=====

Product ID: EC-3924 BRUSHABLE STRUCTURAL ADHESIVE PRIMER (XD)

Cage: 52152

Company Name: MINNESOTA MINING & MFG CO INDUSTRIAL TAPE & SPECIALTIES
DIV

Street: 3M CENTER

City: ST PAUL MN

Zipcode: 55144-1000

Health Emergency Phone: 612-733-1110

Label Required IND: Y

Date Of Label Review: 02/09/1995

Status Code: C

Label Date: 02/09/1995

Origination Code: F

Chronic Hazard IND: Y

Eye Protection IND: YES

Skin Protection IND: YES

Signal Word: DANGER

Respiratory Protect

ion IND: YES

Health Hazard: Moderate

Contact Hazard: Moderate

Fire Hazard: Severe

Reactivity Hazard: None

Hazard And Precautions: FLAMMABLE! MAY CAUSE CNS DEPRESSION IF INHALED OR SWALLOWED. INHALATION MAY CAUSE RESPIRATORY TRACT IRRITATION, LIVER/KIDNEY EFFECTS. INGESTION MAY CAUSE GI TRACT IRRITATION, ASPIRATION. CONTACT MAY CAUSE MODERATE EYE IRRITATION OR ALLERGIC SKIN REACTION. PROLONGED/REPEATED EXPOSURE MAY CAUSE SKIN ULCERATIONS. FIRST AID: INHALATION-REMOVE TO FRESH AIR. RESTORE BREAT

HING. GET MEDICAL ATTN. EYE-IMMEDIATELY FLUSH WITH LOTS OF WATER FOR 15 MINUTES. GET MEDICAL ATTN IMMEDIATELY. SKIN-WASH WITH SOAP & WATER. REMOVE CONTAMINATED CLOTHING. INGESTION-DO NOT INDUCE VOMITING, UNLESS INSTRUCTED BY DR. GET MEDICAL ATTN IMMEDIATELY. TARGET ORGANS: CNS, LIVER, KIDNEY, SKIN, LUNGS

=====

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense.

The United States of America in no manner whatsoever expressly or implied warrants, states, or intends said information to have any application, use or viability by or to any person or persons outside the Department of Defense nor any person or persons contracting with any instrumentality of the United States of America and disclaims all liability for such use. Any person utilizing this instruction who is not a military or civilian employee of the United States of Ame

rica should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation regardless of similarity to a corresponding Department of Defense or other government situation.