

NAUGHTON ENERGY CORP -- IMP-L-15W-40 MIL-L-2104E QUAL MC-3589 -- 9150-00-582-5480  
===== Product Identification =====

Product ID:IMP-L-15W-40 MIL-L-2104E QUAL MC-3589

MSDS Date:12/09/1991

FSC:9150

NIIN:00-582-5480

MSDS Number: BWMQD

=== Responsible Party ===

Company Name:NAUGHTON ENERGY CORP

Address:SULLIVAN RD

Box:709

City:POCONO PINES

State:PA

ZIP:18350

Country:US

Info Phone Num:717-646-0422

Emer

gency Phone Num:717-646-0422

CAGE:1DL10

=== Contractor Identification ===

Company Name:NAUGHTON ENERGY CORP

Address:RT 940

Box:709

City:POCONO PINES

State:PA

ZIP:18350-0709

Country:US

Phone:570-646-0422

CAGE:1DL10

===== Composition/Information on Ingredients =====

Ingred Name:LUBE OIL BASE STOCK/REFINED HEAVY PARAFFINIC DISTILLATES

CAS:64741-88-4

Fraction by Wt: 80.5%

Other REC Limits:NONE SPECIFIED

OSHA PEL:5 MG/M3 (OIL MIST)

ACGIH TLV:5 MG/M3 (OIL MIST)

Ingred Name:PROPRIE

TARY ADDITIVES - THE COMPOSITION OF THESE IS  
PROPRIETARY TO LUBRIZOL, CONTACT THEM FOR MORE INFORMATION.

Fraction by Wt: 19.5%

Other REC Limits:NONE SPECIFIED

=====  
Hazards Identification  
=====

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:WHILE THIS PRODUCT MAY IRRITATE THE  
SKIN FROM PROLONGED CONTACT, THERE IS NO MEDICAL OR TOXICOLOGICAL  
EVIDENCE THAT IT IS AN IRRITANT, A CORROSIVE OR A CARCINOGEN. IT  
H

AS A LOW ORDER OF ORAL & DERMAL TOXICITRY. INHALATION OF MIST MAY  
CAUSEPULMONARY PROBLEMS WHICH IF LEFT UNATTENDED COULD CAUSE  
PULMONARY INJURY.

Explanation of Carcinogenicity:NO AVAILABLE DATA

Effects of Overexposure:FROM HUMAN EXPERIENCE AND THE AVAILABLE  
TECHNICAL DATA CONCERNING THIS PRODUCT AND DUE TO ITS LOW ORDER OF  
DERMAL, ORAL AND INGESTIVE TOXICITY THE SIGNS AND SYMPTOMS OF  
OVEREXPOSURE ARE UNKNOWN.

Medical Cond Aggravated by Exposure:DIRECT CONTACT WITH THE EYES  
MAY

CAUSE EYE ITTITATION. PROLONGED SKIN CONTACT MAY CAUSE SKIN  
IRRITATION.

=====  
First Aid Measures  
=====

First Aid:IF SWALLOWED DO NOT INDUCE VOMITING. CALL A PHYSICIAN  
IMMEDIATELY. IF SPLASHED IN EYES, PURGE WITH COPIOUS AMOUNTS OF  
WATER. IN CASE OF SKIN CONTACT, CLEANSE WITH SATERLESS HAND CLEANER  
OR BY THOROUGH LY WASHING WITH SOAP AND WATER.

=====  
Fire Fighting Measures  
=====

Flash Point:450F,2  
32C

Extinguishing Media:CARBON DIOXIDE, WATER FOG, DRY CHEMICAL, FOAM.

Fire Fighting Procedures:USE WATER SPRAY TO COOL FIRE EXPOSED SURFACES  
AND TO PROTECT PERSONNEL. USE MESA/NIOSH APPROVED BREATHING  
APPARATUS.

=====  
Accidental Release Measures  
=====

Spill Release Procedures:DIKE & CONTAIN SPILL WITH INERT MATERIAL  
(SAND,EARTH,FULLERS EARTH ETC.).TRANSFER LIQUID TO DRUMS OR OTHER  
CONTAINERS FOR RECOVERY OR DISPOSAL.AREA MAY BE SLIPPERY.CARE  
SHO

