

=====
Product Identification
=====

Product ID:EPK 0151 RESIN AA0151

MSDS Date:11/02/1993

FSC:8040

NIIN:00-061-8303

Kit Part:Y

MSDS Number: BWQYV

=== Responsible Party ===

Company Name:DEXTER CORP; AUTOMOTIVE MATERIALS DIVISION

Address:ONE DEXTER DRIVE

City:SEABROOK

State:NH

ZIP:03874

Country:US

Info Phone Num:603-474-5541

Emergency Phone Num:800-424-9300 (CHEMTREC)

Preparer

's Name:KEN DECOSTA

CAGE:1JB33

=== Contractor Identification ===

Company Name:DEXTER CORP THE HYSOL DIV

Address:1 DEXTER DR

Box:City:SEABROOK

State:NH

ZIP:03874

Country:US

Phone:603-474-5541/FAX: 603-474-5545

CAGE:1JB33

=====
Composition/Information on Ingredients
=====

Ingred Name:EPOXY RESIN (THIS RESIN IS NOT REGULATED UNDER OSHA'S
HAZARD COMMUNICATION STANDARD)

CAS:25068-38-6

Fraction by Wt: 60-100%

Other REC Limits:NONE RECOMMENDED

=====
Hazards Ide
=====

ntification =====

Health Hazards Acute and Chronic:EYE: MODERATELY IRRITATING. CONTACT WITH PRODUCT AT ELEVATED TEMPERATURES CAN RESULT IN THERMAL BURNS. SKIN: MODERATELY IRRITATING, CAUSE SKIN SENSITIZATION. THERMAL BURNS AT ELEVATED TEMPERATURES. INHALATION: NOT LIKELY BECAUSE OF LOW VOLATILITY. INGESTION: PRESUMED TO HAVE LOW ORDER OF ACUTE ORAL TOXICITY.

Effects of Overexposure:IRRITATION AS NOTED. SKIN SENSITIZATION (ALLERGY) MAY BE EVIDENCED BY RASHES, ESPECIALLY HIVES.

Medical Conditions Aggravated by Exposure:PRE-EXISTING SKIN AND EYE DISORDERS MAY BE AGGRAVATED BY EXPOSURE TO THIS PRODUCT. PRE-EXISTING SKIN OR LUNG ALLERGIES MAY INCREASE CHANCE OF DEVELOPING INCREASED ALLERGY SYMPTOMS FROM EXPOSURE.

===== First Aid Measures =====

First Aid:EYE:FLUSH W/H2O 15 MIN,HOLD EYELID OPEN.GET MED AID.IF CONTACT W/HOT PRODUCT,IMMEDIATELY FLUSH W/COOL H2O 15 MIN.GET MED AID.SKIN:REMOVE CONTAMINATED CLOTH/SHOES.WIPE EXCESS FROM SKIN.FLUSH W/H2O.WASH W/SOAP & H2O .IF IRRITATED,GET MED AID.DESTROY CONTAMINATED LEATHER.IF CONTACT W/HOT PRODUCT,IMMEDIATELY FLUSH W/COOL H2O 15 MIN.REMOVE CLOTH W/CARE,IF CONTACT W/HOT PRODUCT.IF STUCK,DON'T PULL MATERIAL OFF,CUT AROUND BURN AREA. *

===== Fire Fighting Measures =====

Flash Point Method:CC
Flash Point:155F,68C
Lower Limits:0.4
Upper Limits:1.3
Extinguishing Media:CARBON DIOXIDE, DRY CHEMICAL FOR SMALL FIRES. FOAM FOR LARGE FIRES.
Fire Fighting Procedures:NONE
Unusual Fire/Explosion Hazard:NONE

===== Accidental Release Measures =====

Spill Release Procedures:CLEANUP AND DISPOSAL SHOULD BE IN ACCORDANCE WITH FEDERAL, STATE, AND LOCAL ENVIRONMENTAL CONTROL REGULATIONS.

===== Handling and Storage =====

Handling and Storage Precautions:WARNING: MAY CAUSE SKIN SENSITIZATION AND OTHER ALLERGIC RESPONSES.
Other Precautions:USE ONLY WITH ADEQUATE VENTILATION

NTILATION, PARTICULARLY IF
HEATED OR SPRAYED. AVOID CONTACT WITH SKIN OR EYES.

===== Exposure Controls/Personal Protection =====

Respiratory Protection: AIR SUPPLIED MASK IN CONFINED SPACE.
Ventilation: LOCAL EXHAUST PREFERRED, MECHANICAL EXHAUST ACCEPTABLE.
Protective Gloves: RUBBER OR PLASTIC GLOVES
Eye Protection: SAFETY GLASSES OR GOGGLES
Other Protective Equipment: SAFETY SHOWER AND EYE BATH. USE COVERALLS OR
APRON TO PROTECT AGAINST SKIN AND CLOTHING CONTAMINATION.

W

ork Hygienic Practices: WASH CONTAMINATED CLOTHING BEFORE REUSE.

Supplemental Safety and Health

* INHALATION: REMOVE TO FRESH AIR & GIVE OXYGEN IF BREATHING DIFFICULT.
GET MED AID. INGESTION: DON'T INDUCE VOMITING. IN GENERAL, NO
TREATMENT NECESSARY UNLESS LRG QTY INGESTED. HOWEVER, GET MED ADVI
CE. NOTE TO DR: IN GENERAL, EMESIS INDUCTION UNNECESSARY IN HIGH
VISCOSITY, LOW VOLAILITY PRODUCTS (NEAT EPOXY RESIN).

===== Physical/Chemical Properties =====

HCC: V4

Boiling Pt: B.P. Text: 284F, 140C

Vapor Pres: 2

Vapor Density: 3.8

Spec Gravity: 1.14

Evaporation Rate & Reference: >1

Solubility in Water: