Product ID:SUPER QUADROLUBE 80W90 GEAR

MSDS Date:12/15/1994

FSC:9150

NIIN:01-035-5393

MSDS Number: BWRKX === Responsible Party ===

Company Name: QUAKER STATE OIL REFINING CORP

Address:255 ELM ST

Box:989 City:OIL CITY State:PA

ZIP:16301-1412 Country:US

Info Phone Num:814-676-2726

Emergency Phone Num:814-676-2726 Preparer's Name:D.W. CRALLEY

CAGE:D O899

=== Contractor Identification ===

Company Name: QUAKER STATE CORPORATION Address: 255 E JOHN CARPENTER FREEWAY

Box:City:IRVING

State:TX ZIP:75062 Country:US

Phone:800-562-5928

CAGE:77493

Company Name: QUAKER STATE OIL REFINING CORPORATION

Address:Box:989 City:OIL CITY State:PA

ZIP:16301 Country:US

Phone:814-676-7676

CAGE:DO899

====== Composition/Information on Ingredients ========

Ingred Name:MINERAL OIL, PETROLEUM DISTILLATE, SOLVENT DEWAXED (MILD), HEAVY PARAFFINIC

CAS:64

742-65-0 RTECS #:PY8038500 Fraction by Wt: 25-30% Other REC Limits: 5 MG/M3 (OIL MIST)

Ingred Name: SOLVENT DEWAXED RESIDUAL OIL (PETROLEUM)

CAS:64742-62-7

Fraction by Wt: 60-65%

Other REC Limits:5 MG/M3 (OIL MIST)

Ingred Name: OLEFIN SULFIDE

CAS:72162-26-6 Fraction by Wt: 2-4%

Other REC Limits: NONE RECOMMENDED

Ingred Name: ALKYLAMINE SALTS OF PHOSPHORIC ACID ESTERS

CAS:71888-91-0 Fraction by Wt: 0-2%

Other REC Limits: NONE RECOMMENDED

============= Hazards Identification ===========

Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic: CONTACT MAY CAUSE EYE IRRITATION. PROLONGED OR REPEATED SKIN CONTACT MAY CAUSE IRRITATION OR DERMATITIS. INHALATION OF HIGH CONCENTRATIONS OF MISTS OR VAPOR MAY CAUSE UPPER RESPIRATORY TRACT IRRITATIO N; POSSIBLE CNS DEPRESSION. ASPIRATION DURING SWALLOWING OR VOMITING MAY CAUSE PULMONARY INJURY.

Explanation of Carcinogenicity:NO

INGREDIENT OF A CONCENTRATION OF 0.1%

OR GREATER IS LISTED AS A CARCINOGEN OR SUSPECTED CARCINOGEN.

Effects of Overexposure: EYES-REDNESS, BURNING SENSATION, TEARING. SKIN-IRRITATION, DERMATITIS. INHALED-IRRITATION, DIZZINESS, NAUSEA, HEADACHE, LOSS OF COORDINATION, WEAKNESS. INGESTED-PULMONARY INJURY.

Medical Cond Aggravated by Exposure: NONE SPECIFIED BY MANUFACTURER.

============== First Aid Measures ===========================

First Aid:INHALATION-REMOVE TO FRESH AIR.

| GIVE MOUTH-TO-MOUTH RESUSCITATION IF NOT BREATHING. GET MEDICAL ATTENTION. EYE-FLUSH WITH WATER FOR 15 MINUTES. GET MEDICAL ATTENTION IMMEDIATELY. SKIN-WASH WITH SOAP & WATER. REMOVE CONTAMINATED CLOTHING. INGESTION-DO NOT INDUCE VOMITING. NOTHING BY MOUTH IF UNCONSCIOUS. |
|--|
| GET MEDICAL ATTENTION. |
| ====================================== |
| Flash Point Method:COC |
| Flash Point:390F,199C Extinguishing Media:WATER, CARBON DIXOIDE, DRY CHEMICAL, FOAM. Fire |
| Fighting Procedures:USE WATER SPRAY TO COOL FIRE-EXPOSED CONTAINERS AND AS A PROTECTIVE SCREEN. DO NOT POINT WATER STREAM DIRECTLY AT BURNING OIL, IT MAY SPREAD THE FIRE. |
| Unusual Fire/Explosion Hazard:"EMPTY" CONTAINERS RETAIN PRODUCT RESIDUE AND CAN BE DANGEROUS. |
| ========= Accidental Release Measures ========== |
| Spill Release Procedures:ABSORB WITH INERT MATERIALS SUCH AS DRY CLAY, SAND, DIATOMACEOUS EARTH, OR RECOVER WITH PUMPS. SCOOP UP USED ABSORBENT |
| INTO DRUMS. DO NOT ALLOW INTO PUBLIC DRAINAGE SYSTEM OR OPEN WATERWAYS. WEAR APPR OPRIATE CLOTHING/EQUIPMENT. Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER. |
| ====================================== |
| Handling and Storage Precautions:STORE AWAY FROM STRONG OXIDIZING AGENTS. |
| Other Precautions:EMPTY DRUMS SHOULD BE COMPLETELY DRAINED, PROPERLY |

BUNGED & PROMPTLY RETURNED TO A DRUM RECONDITIONER OR PROMPTLY DISPOSED OF.

| ======================================= | Exposure | Controls/ |
|---|----------|-----------|
| Personal Protectio | n ===== | ====== |

Respiratory Protection: IF ENGINEERING CONTROLS FAIL OR NON-ROUTINE USE OR EMERGENCY OCCURS; USE NIOSH/MSHA APPROVED RESPIRATOR OR SUPPLIED AIR RESPIRATOR OR SCBA, AS REQUIRED. USE IAW 29 CFR 1910.134 AND MANUFACTURER'S RECO MMENDATIONS.

Ventilation: USE GENERAL VENTILATION AND USE LOCAL EXHAUST WHERE POSSIBLE IN CONFINED OR ENCLOSED SPACES.

Protective Gloves:NITRILE, VITON.

Eye Protection: NONE NORMALLY REQUIRED.

Other Protective Equipment: NONE S

| PECIFIED BY MANUFACTURER. DLA-HMIS: |
|--|
| EYE WASH STATION & SAFETY SHOWER AVAILABLE FOR EMERGENCY USE. Work Hygienic Practices: WASH HANDS AFTER USE AND BEFORE EATING, |
| DRINKING, OR SMOKING. LAUNDER CONTAMINATED CLOTHES BEFORE REUSE |
| Supplemental Safety and Health |
| ====================================== |
| HCC:V6 |
| Spec Gravity:0.88-0.90 |
| Viscosity:674 SUS @100F |
| Appearance and Odor:BROWN, VISCOUS LIQUID. |
| ========= Stability and Reactivity Data ========= |
| == |
| Stability Indicator/Materials to Avoid:YES |
| STRONG OXIDIZING AGENTS (SUCH AS CHLORINE, PEROXIDES), STRONG ACIDS. |
| Stability Condition to Avoid: EXCESSIVE HEAT, FORMATION OF MISTS. |
| Hazardous Decomposition Products:CARBON MONOXIDE, CARBON DIOXIDE, |
| AND |

OXIDES OF SULFUR, NITROGEN, BORON AND PHOSPHOROUS. Conditions to Avoid Polymerization: WILL NOT OCCUR.

========= Disposal Considerations =================

Waste Disposal Methods: MATERIAL, IF DISCARDED, IS NOT EXPECTED TO BE A CH

ARACTERISTIC WASTE UNDER RCRA. USED OIL CAN BE RETURNED TO A COLLECTION POINT OR PROVIDED TO A LICENSED RECYCLER. ALL WASTES MUST BE HANDLED IAW LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.