

QUAKER STATE OIL REFINING CORP -- SUPER QUADROLUBE 85W140 GEAR -- 9150-01-048-4591
===== Product Identification =====

Product ID: SUPER QUADROLUBE 85W140 GEAR
MSDS Date: 12/15/1994
FSC: 9150
NIIN: 01-048-4591
MSDS Number: BWRLF
=== Responsible Party ===
Company Name: QUAKER STATE OIL REFINING CORP
Address: 255 ELM ST
Box: 989
City: OIL CITY
State: PA
ZIP: 16301-1412
Country: US
Info Phone Num: 814-676-2726
Em
ergency Phone Num: 814-676-2726
Preparer's Name: D.W. CRALLEY
CAGE: DO899
=== Contractor Identification ===
Company Name: QUAKER STATE CORPORATION
Address: 255 E JOHN CARPENTER FREEWAY
Box: City: IRVING
State: TX
ZIP: 75062
Country: US
Phone: 800-562-5928
CAGE: 77493
Company Name: QUAKER STATE OIL REFINING CORPORATION
Address: Box: 989
City: OIL CITY
State: PA
ZIP: 16301
Country: US
Phone: 814-676-7676
CAGE: DO899

===== Composition/Information on Ingredients =====

Ingred Name: SOLVENT DEWAXED RESI

DUAL OIL (PETROLEUM)

CAS:64742-62-7

Fraction by Wt: 90-95%

Other REC Limits:5 MG/M3 (OIL MIST)

Ingred Name:OLEFIN SULFIDE

CAS:72162-26-6

Fraction by Wt: 2-4%

Other REC Limits:NONE RECOMMENDED

Ingred Name:ALKYLAMINE SALTS OF PHOSPHORIC ACID ESTERS

CAS:71888-91-0

Fraction by Wt: 0-2%

Other REC Limits:NONE RECOMMENDED

===== Hazards Identification =====

Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health

Short Hazards Acute and Chronic:CONTACT MAY CAUSE EYE IRRITATION.

PROLONGED OR REPEATED SKIN CONTACT MAY CAUSE IRRITATION OR DERMATITIS. INHALATION OF HIGH CONCENTRATIONS OF MISTS OR VAPOR MAY CAUSE UPPER RESPIRATORY TRACT IRRITATION; POSSIBLE CNS DEPRESSION. ASPIRATION DURING SWALLOWING OR VOMITING MAY CAUSE PULMONARY INJURY.

Explanation of Carcinogenicity:NO INGREDIENT OF A CONCENTRATION OF 0.1%

OR GREATER IS LISTED AS A CARCINOGEN OR SUSPECTED CARCINOGEN.

Effects of Over

exposure:EYES-REDNESS, BURNING SENSATION, TEARING.

SKIN-IRRITATION, DERMATITIS. INHALED-IRRITATION, DIZZINESS, NAUSEA, HEADACHE, LOSS OF COORDINATION, WEAKNESS. INGESTED-PULMONARY INJURY.

Medical Conditions Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

===== First Aid Measures =====

First Aid:INHALATION-REMOVE TO FRESH AIR. GIVE MOUTH-TO-MOUTH

RESUSCITATION IF NOT BREATHING. GET MEDICAL ATTENTION. EYE-FLUSH WITH WATER FOR 15 MINUTES.

GET MEDICAL ATTENTION IMMEDIATELY.
SKIN-WASH WITH SOAP & WATER. REMOVE CONTAMINATED CLOTHING.
INGESTION-DO NOT INDUCE VOMITING. NOTHING BY MOUTH IF UNCONSCIOUS.
GET MEDICAL ATTENTION.

=====
===== Fire Fighting Measures =====

Flash Point Method:COC
Flash Point:400F,204C
Extinguishing Media:WATER, CARBON DIXOIDE, DRY CHEMICAL, FOAM.
Fire Fighting Procedures:USE WATER SPRAY TO COOL FIRE-EXPOSED
CONTAINERS AND AS A PROTECTIVE SCREEN. DO NOT POINT WATER
STREAM
DIRECTLY AT BURNING OIL, IT MAY SPREAD THE FIRE.
Unusual Fire/Explosion Hazard:"EMPTY" CONTAINERS RETAIN PRODUCT RESIDUE
AND CAN BE DANGEROUS.

=====
===== Accidental Release Measures =====

Spill Release Procedures:ABSORB WITH INERT MATERIALS SUCH AS DRY CLAY,
SAND, DIATOMACEOUS EARTH, OR RECOVER WITH PUMPS. SCOOP UP USED
ABSORBENT INTO DRUMS. DO NOT ALLOW INTO PUBLIC DRAINAGE SYSTEM OR
OPEN WATERWAYS. WEAR APPR OPRIATE CLOTHING/EQUIPMENT.
Neutr
alizing Agent:NONE SPECIFIED BY MANUFACTURER.

=====
===== Handling and Storage =====

Handling and Storage Precautions:STORE AWAY FROM STRONG OXIDIZING
AGENTS.
Other Precautions:EMPTY DRUMS SHOULD BE COMPLETELY DRAINED, PROPERLY
BUNGED & PROMPTLY RETURNED TO A DRUM RECONDITIONER OR PROMPTLY
DISPOSED OF.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF ENGINEERING CONTROLS FAIL OR NON-ROUTINE USE
OR EMERG
ENCY OCCURS; USE NIOSH/MSHA APPROVED RESPIRATOR OR SUPPLIED
AIR RESPIRATOR OR SCBA, AS REQUIRED. USE IAW 29 CFR 1910.134 AND
MANUFACTURER'S RECO MMENDATIONS.
Ventilation:USE GENERAL VENTILATION AND USE LOCAL EXHAUST WHERE
POSSIBLE IN CONFINED OR ENCLOSED SPACES.
Protective Gloves:NITRILE, VITON.
Eye Protection:NONE NORMALLY REQUIRED.
Other Protective Equipment:NONE SPECIFIED BY MANUFACTURER. DLA-HMIS:
EYE WASH STATION & SAFETY SHOWER AVAILABLE FOR EMERGENCY USE.
Work Hygienic Pra

ctices:WASH HANDS AFTER USE AND BEFORE EATING,
DRINKING, OR SMOKING. LAUNDRER CONTAMINATED CLOTHES BEFORE REUSE.
Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:V6
Spec Gravity:0.89-0.90
Viscosity:1759 SUS@100F
Appearance and Odor:BROWN, VISCOUS LIQUID.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZING AGENTS (SUCH AS CHLORINE, PEROXIDES), STRONG ACIDS.
Stability Condition to Avoid:EXCESSIVE HEAT, FORMATION OF MISTS.
Hazardous Decomposition Products:CARBON MONOXIDE, CARBON DIOXIDE,
OXIDES OF SULFUR, NITROGEN, BORON AND PHOSPHOROUS.
Conditions to Avoid Polymerization:WILL NOT OCCUR.

===== Disposal Considerations =====

Waste Disposal Methods:MATERIAL, IF DISCARDED, IS NOT EXPECTED TO BE A
CHARACTERISTIC WASTE UNDER RCRA. USED OIL CAN BE RETURNED TO A
COLLECTION POINT OR PROVIDED TO A LICENSED RECYCLER. ALL WASTES
MUST BE HANDLED IAW LOCAL , STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.